

LIST OF TABLES

	<u>Page</u>
1. Chemical composition of agents in finish recipe.	48
2. Preliminary data of the fabric.	76
3. Determination of tensile strength of fabrics after flat abrasion.	83
4. Determination of tensile strength of fabrics after rotary abrasion.	86
5. Determination of tensile strength of fabrics after impact abrasion.	90
6. Determination of tensile strength of treated fabrics (2.5%) after flat abrasion.	101
7. Determination of tensile strength of treated fabrics (5%) after flat abrasion.	102
8. Determination of tensile strength of treated fabrics (7.5%) after flat abrasion.	103
9. Determination of tensile strength of treated fabrics (10%) after flat abrasion.	104
10. Determination of tensile strength of treated fabrics (2.5%) after rotary abrasion.	118
11. Determination of tensile strength of treated fabrics (5%) after rotary abrasion.	119
12. Determination of tensile strength of treated fabrics (7.5%) after rotary abrasion.	120
13. Determination of tensile strength of treated fabrics (10%) after rotary abrasion.	121

### III

	<u>Page</u>
14. Determination of tensile strength of treated fabrics (2.5%) after impact abrasion.	135
15. Determination of tensile strength of treated fabrics (5%) after impact abrasion.	136
16. Determination of tensile strength of treated fabrics (7.5%) after impact abrasion.	137
17. Determination of tensile strength of treated fabrics (10%) after impact abrasion.	138
18. Determination of tensile strength of treated fabric A (5%) after dry and wet impact abrasion.	153
19. Determination of tensile strength of treated fabric B (5%) after dry and wet abrasion.	154
20. Determination of tensile strength of treated fabric C (5%) after dry and wet impact abrasion.	155
21. Effect of acrylamide finish on elongation of cotton fabric A, after flat, impact and rotary abrasions.	156
22. Effect of acrylamide finish on elongation of Polyester/Cotton (67/33) Fabric B after flat impact and rotary abrasion.	157-158
23. Effect of acrylamide finish on elongation of Polyester/Cotton (50/50) Fabric C, after flat, impact and rotary abrasion.	159
24. Determination of tearing strength with different concentration of acrylamide finish.	164

IV

	<u>Page</u>
25. Effect of acrylamide finish on stiffness of fabrics.	166
26. Wrinkle recovery of fabrics treated with different concentration of acrylamide finish.	168
27. Effect of acrylamide finish on air permeability.	172