
List of Tables

Table No	Title	Page No
3.1	Composition of membranes	48
3.2	Conductivity of mixed matrix membrane (M41) at different voltages	64
3.3	Viscosity values for polyethersulfone and sulfonated polyethersulfone in solvent NMP at 30°C	71
3.4	X-Ray diffraction values of PES and SPES	71
3.5	Mechanical properties of azide functionalized MWCNT incorporated PES membrane [M41] and click reaction modified membrane [C3]	79
4.1	Pure water flux values of the membranes at different pressure	82
4.2	Rejection studies of metal ions at pH 2.5 for azide functionalized MWCNT/PES membranes at pressure 71 psi and 98 psi	87
4.3	Rejection studies of heavy metal ions at pH 2.5 for oxidized MWCNT/PES membranes at pressure of 71 psi	90
4.4	Rejection studies of heavy metal ions at pH 2.5 for amide functionalized MWCNT/PES membranes at pressure of 71 psi	90
4.5	Rejection studies of heavy metal ions at pH 2.5 for azide functionalized MWCNT/PES membranes at pressure of 71 psi	91
4.6	Typical quality parameters of selected quality effluent	92
4.7	Rejection percentage of water quality parameters	94
4.8	Quality parameters of selected quality effluent after treatment	95
4.9	BSA rejection and fouling ratio of the PES/f-MWCNT mixed matrix membranes	97
4.10	Pure water flux values of the membranes at different pressure	99
4.11	Rejection studies of metal ions at pH 2.5 for azide functionalized MWCNT/PES membranes at pressure 71 psi and 98 psi	101
4.12	Rejection studies of heavy metal ions at pH 2.5 for oxidized MWCNT/PES membranes at pressure of 71 psi	104

4.13	Rejection studies of heavy metal ions at pH 2.5 for amide functionalized MWCNT/PES membranes at pressure of 71 psi	104
4.14	Rejection studies of heavy metal ions at pH 2.5 for azide functionalized MWCNT/PES membranes at pressure of 71 psi	105
4.15	Rejection percentage of water quality parameters	106
4.16	Quality parameters of selected quality effluent after treatment	107
4.17	BSA rejection and fouling ratio of the SPES/f-MWCNT mixed matrix membranes	109
4.18	Rejection capacity of Pristine PES (M1), 1% Az-MWCNT/PES (M41), Click reaction modified 1% Az-MWCNT/PES (C3) membranes	116
4.19	Rejection percentage of water quality parameters	117
4.20	Quality parameters of selected quality effluent after treatment	118
4.21	Values of flux recovery ratio (FRR), reversible fouling ratio (R_r) and irreversible fouling (R_{ir}) of membranes	120
5.1	Roughness parameter of Pristine PES, 0.03wt% Az-MWCNT/PES [M4003], 0.05wt% Az-MWCNT/PES [M4005], 0.07wt% Az-MWCNT/PES [M4007], 0.1wt% Az-MWCNT/PES [M401], 1wt% Az-MWCNT/PES [M41] mixed matrix membranes	124
5.2	Contact angle values of membranes	128
5.3	Variation of pore diameter and required pressure of membranes having 1% concentration of MWCNT, M1 (Pristine), M21 (oxidized), M31 (Amide), M41 (Azide)	131
5.4	SANS data of membrane soaked in D ₂ O	136
5.5	Roughness parameters of Pristine PES [M1], Pristine SPES [S1], 0.1wt% Az-MWCNT/SPES [S401], 0.5wt% Az-MWCNT/SPES [M405], 1wt% Az-MWCNT/SPES [M41] mixed matrix membranes	141
5.6	Contact angle values of pristine SPES and f-MWCNT/SPES mixed matrix membranes	143

5.7	SANS data of membrane soaked in D ₂ O	147
5.8	Roughness parameters of 1wt% Az-MWCNT/SPES [M41] and click reaction modified membranes	149
5.9	Contact angle values of membranes	151
5.10	SANS data of membrane soaked in D ₂ O, M1 (pristine PES), M41 (azide), C3 (click modified)	153