
List of Figures

Figure No	Title	Page No
1.1	Schematic for the type of membranes	2
1.2	Structure of Polyethersulfone	4
1.3	Schematic representation of Phase inversion process	9
1.4	Various conformations of carbon nanotubes	10
1.5	Structure of SWCNT	11
1.6	Structure of DWCNT	12
1.7	Structure of MWCNT	13
1.8	Methods for CNT synthesis	14
1.9	Schematic of arc discharge method for the synthesis of nanotubes	14
1.10	Schematic of laser ablation method for CNT synthesis	17
1.11	Schematic of CVD process for carbon nanotubes synthesis	18
1.12	Scenario of availability of renewable fresh water in India	27
3.1	Schematic representation of different steps of functionalized MWCNT	41
3.2	Illustration of phase inversion process for membrane preparation	42
3.3	Images of prepared pristine PES and 1wt % f-MWCNT/PES mixed matrix membranes	43
3.4	Images of prepared f-MWCNT/PES mixed matrix membranes having lower percentage of nanotubes	44
3.5	Schematic representations for the sulfonation of polyether sulfone	45
3.6	Images of prepared pristine SPES and f-MWCNT/SPES mixed matrix membranes	46
3.7	Reaction scheme of click reaction performed on the surface of the mixed matrix membrane	47
3.8	Images of click reaction modified and unmodified membranes	48
3.9	FTIR spectra of purified MWCNT(a) oxidized MWCNT(b) amide functionalized MWCNT(c) azide functionalized	57

	MWCNT(d)	
3.10	TGA spectra of functionalized multiwalled carbon nanotubes	58
3.11	FE-SEM micrographs of functionalized MWCNT (a) Oxidized [C1] (b) Acylated [C2] (c) Azide functionalized [C3] (d) Amide functionalized [C4]	59
3.12	Thermal stability of mixed matrix membranes as measured by TGA (b) Enlarged image	61
3.13	Stress vs Strain curve of pristine PES membrane [M1]	62
3.14	Stress vs strain curve of 1wt% Ox-MWCNT/PES [M21], 1wt% Am-MWCNT/PES [M31], 1wt% Az-MWCNT/PES [M41] membranes	63
3.15	Impedance spectra of Az-MWCNT/PES mixed matrix membrane	65
3.16	FTIR spectra of polyethersulfone (PES) and sulfonated polyethersulfone (SPES)	66
3.17	¹ H NMR spectra of PES and SPES polymer	67
3.18	¹³ C NMR spectra of Polyethersulfone polymer	68
3.19	¹³ C NMR spectra of sulfonated polyether sulfone polymer	69
3.20	TGA spectra of polyether sulfone and sulfonated polyethersulfone	70
3.21	TGA curves of SPES membrane and 0.1 wt% Az-MWCNT/SPES(S401), 0.5 wt% Az-MWCNT/SPES(S405), 1 wt% Az-MWCNT/SPES(S41) mixed matrix membranes	72
3.22	Stress vs strain curve of pristine SPES (a) 1wt% Ox-MWCNT/SPES (b) 1wt% Am-MWCNT/SPES (c) 1wt% Az-MWCNT/SPES membranes (d)	73
3.23	XPS spectra of (a) unmodified azide functionalized MWCNT membrane [M41] and (b) Alkyne treated membrane [C3]	76
3.24	TGA spectra of unmodified azide functionalized MWCNT membrane [M41] and Click reaction modified membrane	78

	[C3]	
3.25	Stress-strain curves of azide functionalized MWCNT incorporated PES membrane [M41] and click reaction modified membrane [C3]	79
4.1	Pure water flux of pristine PES and mixed matrix membranes containing different weight percentages of Ox-MWCNT at different pressure	81
4.2	Pure water flux of pristine PES and mixed matrix membranes containing different weight percentages of Am-MWCNT at different pressure	81
4.3	Pure water flux of pristine PES and mixed matrix membranes containing different weight percentages of Az-MWCNT at different pressure	82
4.4	Pure water flux versus time of 1%Am-MWCNT/PES (M31) membrane for different pH	84
4.5	Pure water flux versus time of 1%Az-MWCNT/PES (M41) membrane for different pH	85
4.6	Percentage rejection of metal ions at pH 2.5 for mixed matrix azide functionalized MWCNT/PES membranes containing different % of nanotubes at 71 psi pressure	88
4.7	Percentage removal of Cr(VI) metal ion at acidic and neutral pH for different mixed matrix azide functionalized MWCNT/PES membranes at 71psi pressure	89
4.8	Pure water flux values of f-MWCNT/SPES membranes	100
4.9	Percentage removal of Cr(VI) metal ion at acidic and neutral pH for different mixed matrix azide functionalized MWCNT/SPES membranes at 71psi pressure	102
4.10	Representation of BSA rejection (R), Flux recovery ratio (FRR), Reversible fouling ratio (Rr), Irreversible fouling ratio (Rir) of SPES and f-MWCNT/SPES mixed matrix membranes	111
4.11	Pure water flux versus time of click reaction modified membrane at different pH values	114

4.12	Effect of pH on rejection of Cr(VI) metal from unmodified (M41) and modified (C3) membranes	116
4.13	Fouling ratios of the pristine PES (M1), 1%Az MWCNT/PES and click reaction modified membranes	121
5.1	SEM micrograph of cross section of cold fractured membranes (a) M21 (b) M31 (b) (c) M41	123
5.2	FE-SEM images of the surface of the membranes (a) M1 (b1) M41 (higher magnification) (b2) M41	123
5.3	AFM images of Pristine PES (a) 0.03wt% Az-MWCNT/PES [M4003] (b) 0.05wt% Az-MWCNT/PES [M4005] (c) 0.07wt% Az-MWCNT/PES [M4007] (d) 0.1wt% Az-MWCNT/PES [M401] (e) 1wt% Az-MWCNT/PES [M41] (f) mixed matrix membranes	127
5.4	Contact angle of pristine PES as compared nanotubes incorporated membranes	129
5.5	The zeta potential value of pristine PES and mixed matrix membranes as a function of pH	130
5.6	SANS profile of Pristine PES (M1), 0.05 wt % Ox/PES (M2005), 0.05 wt % Am/PES (M3005) and 0.05 wt % Az/PES (M4005) membrane soaked in D ₂ O	134
5.7	SANS profile of Pristine PES (M1), 0.1 wt % Ox/PES (M201), 0.1 wt % Am/PES (M301) and 0.1 wt % Az/PES (M401) membrane soaked in D ₂ O	135
5.8	SANS profile of Pristine PES (M1), 1 wt % Ox/PES (M21), 1 wt % Am/PES (M31) and 1 wt % Az/PES (M41) membrane soaked in D ₂ O	135
5.9	Schematic representation of arrangement of pores in the (a) pristine membrane and (b) mixed matrix membrane	138
5.10	FE-SEM image of the surface of the Pristine SPES (a) 1wt% Ox-MWCNT/SPES (b) 1wt% Am-MWCNT/SPES (c) 1wt% Az-MWCNT/SPES (d) 0.5wt% Az-MWCNT/SPES	140
5.11	FE-SEM image of cross-section of Pristine SPES (a) and 1wt% Am-MWCNT/SPES membranes	140
5.12	AFM images of pristine PES (a) pristine SPES (b) 0.1wt% Az-MWCNT/SPES (c) 0.5wt% Az-MWCNT/SPES (d) 1wt% Az-MWCNT/SPES (e)	142

5.13	The zeta potential value of pristine PES (a) and mixed matrix membranes(b) as a function of pH	144
5.14	SANS profile of Pristine SPES (S1), 0.1 wt % Ox/SPES (S201), 0.1 wt % Am/SPES (S301) and 0.1 wt % Az/SPES (S401) membrane soaked in D ₂ O	145
5.15	SANS profile of Pristine SPES (S1), 0.5 wt % Ox/SPES (S205), 0.5 wt % Am/SPES (S305) and 0.5 wt % Az/SPES (S405) membrane soaked in D ₂ O	146
5.16	SANS profile of Pristine SPES (S1), 0.5 wt % Ox/SPES (S205), 0.5 wt % Am/SPES (S305) and 0.5 wt % Az/SPES (S405) membrane soaked in D ₂ O	146
5.17	FESEM images of azide functionalized MWCNT incorporated PES membrane (a) surface (c) cross section and click reaction modified membrane (b) surface (d) cross section	148
5.18	AFM images of 1wt% Az-MWCNT/PES [M41] (a) and Click reaction modified mixed matrix membranes	150
5.19	Contact angle of azide functionalized MWCNT incorporated PES membrane (a) and click reaction modified membrane (b)	151
5.20	The zeta potential value of pristine PES (a) and mixed matrix membranes (b) as a function of pH	152
5.21	SANS profile of 1 wt % Az-MWCNT/PES (M41) and click reaction modified membrane (C3) soaked in D ₂ O	153