

LIST OF FIGURES

Fig No.	Figure Title	Page No.
1.1	Luminescence phenomenon through band structure	5
1.2	TL Glow Curve Recorded for Quartz (Heating rate 2 ^o C/s)	7
1.3	Illustration of OSL Process	10
1.4	OSL Decay curve recorded for Quartz	11
1.5	OSL Model	16
2.1	Crystal Structure of α -quartz and β -quartz	22
2.2	Intrinsic defect centers in quartz	27
2.3	Al centers in quartz	27
2.4	Synthetic Quartz Growth	29
3.1	Energy levels of unpaired free electron with respect to applied magnetic field	36
3.2	The Risø TL/OSL reader (DA-20)	37
3.3	The Risø TL/OSL Controller	38
3.4	Schematic diagram of the cross section of the beta irradiator	39
3.5	Beta Irradiator attachment	41
3.6	Infrared/Blue Light Optically Stimulated Luminescence (OSL) attachment	41
3.7	Sample discs/cups and sample carrousel	43
3.8	Detection Filters	44
3.9	Picture of the heating element in the measurement position	46
3.10	Schematic diagram of the combined blue and IR LED OSL unit	47
3.11	Picture of the OSL stimulation unit and the U-340 detection filter	48
3.12	The emission spectrum of IR and blue	49
4.1	TL recorded for different beta doses	60
4.2	TL dose response curve of 110 ^o C TL glow peak	62
4.3	TL recorded for 400 ^o C annealed sample for different beta doses	64
4.4	TL recorded for 600 ^o C annealed sample for different beta doses	65
4.5	TL recorded for 800 ^o C annealed sample for different beta doses	66
4.6	TL recorded for 1000 ^o C annealed sample for different beta doses	66
4.7	Comparison of 110 ^o C TL glow peak sensitivity	67
4.8	Comparison of % growth of 110 ^o C TL glow peak sensitivity between Un annealed and annealed samples for different beta dose	67
4.9	TL dose response curve of 110 ^o C TL glow peak for 400 ^o C annealed sample	69

4.10	TL dose response curve of 110°C TL glow peak for 600°C annealed sample	70
4.11	TL dose response curve of 110°C TL glow peak for 800°C annealed sample	70
4.12	TL dose response curve of 110°C TL glow peak for 1000°C annealed sample	71
4.13	TL dose response curve of 295°C TL glow peak for 600°C annealed sample	71
4.14	TL dose response curve of 300°C TL glow peak for 800°C annealed sample	72
4.15	TL dose response curve of 200°C TL glow peak for 1000°C annealed sample	72
4.16	TL from 0°C -200°C for annealed sample of 400°C at different cyclic sequence of physical condition (a) D ₀ (b) D ₀ +sequence+D ₁ (c) D ₀ +sequence+D ₁ + sequence+D ₂ (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀	75
4.17	TL from 0°C -200°C for annealed sample of 600°C at different cyclic sequence of physical condition (a) D ₀ (b) D ₀ +sequence+D ₁ (c) D ₀ +sequence+D ₁ + sequence+D ₂ (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀	76
4.18	TL from 0°C -200°C for annealed sample of 800°C at different cyclic sequence of physical condition (a) D ₀ (b) D ₀ +sequence+D ₁ (c) D ₀ +sequence+D ₁ + sequence+D ₂ (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀	77
4.19	TL from 0°C -200°C for annealed sample of 1000°C at different cyclic sequence of physical condition (a) D ₀ (b) D ₀ +sequence+D ₁ (c) D ₀ +sequence+D ₁ + sequence+D ₂ (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀	77
4.20	TL sensitivity of 110°C glow peak for different annealed samples at cyclic sequence of physical condition	78

4.21	TL from 0°C -450°C for annealed sample of 400°C at different cyclic sequence of physical condition (a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1 (c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ +(e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1 sequence+D ₂ + sequence+D ₃ + TB-1	80
4.22	TL from 0°C -450°C for annealed sample of 600°C at different cyclic sequence of physical condition (a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1 (c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ +(e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1 sequence+D ₂ + sequence+D ₃ + TB-1	81
4.23	TL from 0°C -450°C for annealed sample of 800°C at different cyclic sequence of physical condition (a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1 (c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ +(e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1 sequence+D ₂ + sequence+D ₃ + TB-1	82
4.24	TL from 0°C -450°C for annealed sample of 1000°C at different cyclic sequence of physical condition (a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1 (c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ +(e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1 sequence+D ₂ + sequence+D ₃ + TB-1	82
4.25	TL sensitivity of 215°C glow peak for different annealed samples at cyclic sequence of physical condition	83
4.26	TL dose response curve of 215°C TL glow peak for 400°C annealed sample	83
4.27	TL dose response curve of 207°C TL glow peak for 600°C annealed sample	84
4.28	TL dose response curve of 219°C TL glow peak for 800°C annealed sample	84
4.29	TL dose response curve of 219°C TL glow peak for 1000°C annealed sample	85

4.30	OSL at 125 ^o C for annealed sample of 400 ^o C at different cyclic sequence of physical condition (a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1 (c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + TB-1 (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1	90
4.31	OSL at 125 ^o C for annealed sample of 600 ^o C at different cyclic sequence of physical condition (a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1(c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + TB-1 (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1	91
4.32	OSL at 125 ^o C for annealed sample of 800 ^o C at different cyclic sequence of physical condition (a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1 (c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + TB-1 (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1	92
4.33	OSL at 125 ^o C for annealed sample of 1000 ^o C at different cyclic sequence of physical condition(a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1 (c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + TB-1 (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1	92
4.34	Sensitivity of OSL at 125 ^o C for different annealed samples at cyclic sequence of physical condition (a) D ₀ +TB-1 (b) D ₀ +sequence+D ₁ + TB-1(c) D ₀ +sequence+D ₁ + sequence+D ₂ + TB-1 (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + TB-1 (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + TB-1	93
4.35	OSL dose response for 400 ^o C annealed sample	95
4.36	OSL dose response for 600 ^o C annealed sample	95
4.37	OSL dose response for 800 ^o C annealed sample	96

4.38	OSL dose response for 1000°C annealed sample	96
4.39	OSL at 125°C for annealed sample of 400°C at different cyclic sequence of physical condition (a) D ₀ +sequence (b) D ₀ +sequence+D ₁ + sequence (c) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + sequence	104
4.40	OSL at 125°C for annealed sample of 600°C at different cyclic sequence of physical condition (a) D ₀ +sequence (b) D ₀ +sequence+D ₁ + sequence (c) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + sequence	105
4.41	OSL at 125°C for annealed sample of 800°C at different cyclic sequence of physical condition (a) D ₀ +sequence (b) D ₀ +sequence+D ₁ + sequence (c) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + sequence	106
4.42	OSL at 125°C for annealed sample of 1000°C at different cyclic sequence of physical condition (a) D ₀ +sequence (b) D ₀ +sequence+D ₁ + sequence (c) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence (d) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence (e) D ₀ +sequence+D ₁ + sequence+D ₂ + sequence+D ₃ + sequence+D ₀ + sequence	106
4.43 (A)	4.43(A) Effect of thermal bleaching temperature on OSL Intensity	110
4.43 (B)	Effect of thermal bleaching temperature on OSL Intensity	111
4.44	Effect of annealing temperature on OSL Intensity at different thermal bleaching temperature	112
4.45	Effect of annealing temperature on components of OSL decay curve at identical dose and thermal bleaching temperature	113

4.46	TL Recorded from 0°C to 450°C for different annealed temperature subjected to dose, TB, and Optical stimulation	114
5.1	Electron Spin	119
5.2	Block Diagram of ESR set-up	120
5.3	Defects paired in SiO ₂	122
5.4	ESR spectra-I	125
5.5	ESR Spectra-II	126
5.6	ESR Spectra-III	127
5.7	ESR Spectra-IV	127
5.8	ESR Spectra-V(a)	128
5.9	ESR Spectra-V(b)	129
5.10	ESR Spectra-VI(a)	130
5.11	ESR Spectra-VI(b)	130