

List of Figures

Chapter 1

Figure 1(a): Scenario before ionisation	5
Figure 1(b): Ionisation	5
Figure 1(c): Trapping centres with occupied trap charges—holes and electrons	5
Figure 1(d): de-trapping and recombination	5
Figure 2: Glow curve from a TL phosphor	8
Figure 3: OSL decay curve	13
Figure 4: A basic block diagram of a typical TL/OSL system	17
Figure 5: Technical requirements of the TL/OSL system	18

Chapter 2

Figure 1: A basic PMT	38
Figure 2: Silicon Photomultiplier with its equivalent circuit	45
Figure 3: A Digital Silicon Photomultiplier	48
Figure 4: Block diagram of a system based on analogue SiPM and digital SiPM	49
Figure 5: EMCCD cameras	50
Figure 6: Comparison of QE/PDE of PMT, SiPM, and digital SiPM.	53
Figure 7: Minimum detectable power verses wavelength for bialkali (blue sensitivity) PMT, multialkali (red sensitivity) PMT, SiPM, and dSiPM	54

Chapter 3

Figure 1: Block diagram of the TL/OSL system	73
Figure 2: Driving signal, Temperature signal and Error signal graph for heater unit	74
Figure 3: Thermocouple filter and amplifier circuit	78
Figure 4: Trigger circuit for EMCCD	79
Figure 5: OSL feedback and LED driver circuit	82
Figure 6: Aluminium LED Holder focussing the light on the centre	83
Figure 7: Set-up of the System	84
Figure 8: Driving signal, Temperature signal and Error signal graph for the OSL unit	85
Figure 9: Spartan-6 LX9 micro board with ADC and DAC kits attached to it	87

Figure 10: Sine wave	89
Figure 11: Symmetrical Square wave	89
Figure 12: Interrupted Symmetrical Wave	90
Figure 13: Unidirectional Rectangular Wave	90
Figure 14: H-bridge circuit	92
Figure 15: Shape and size of ETD 34/17/11	93
Figure 16: Labview based GUI with the visual display of the stimulation process	94
Figure 17: Andor iXON DU-897 EMCCD camera	95
Figure 18: Spectral range of iXON DU-897 EMCCD camera	96
Figure 19: Design of the mechanical housing for the optics	99
Figure 20: Linearity in thermal stimulation for TL done up to 500 °C at 10 °C/s with 7 s hold-time	101
Figure 21: Error in thermal stimulation for TL done up to 500 °C at 10 °C/s with 7 s hold-time	101
Figure 22: Histogram of deviations from linearity for 500 °C at 10°C/s with 7 s hold-time	102
Figure 23: Linearity in thermal stimulation for TL done up to 500 °C at 9 °C/s with 7 s hold-time	103
Figure 24: Error in thermal stimulation for TL done up to 500 °C at 9 °C/s with 7 s hold-time	103
Figure 25: Histogram of deviations from linearity for 500 °C at 9 °C/s with 7 s hold-time	104
Figure 26: Linearity in thermal stimulation for TL done up to 500 °C at 8 °C/s heating rate	105
Figure 27: Error in thermal stimulation for TL done up to 500 °C at 8 °C/s heating rate	105
Figure 28: Histogram of deviations from linearity for 500 °C at 8 °C/s heating rate	106
Figure 29: Linearity in thermal stimulation for TL done up to 500 °C at 7 °C/s with 7 s hold-time	107
Figure 30: Error in thermal stimulation for TL done up to 500 °C at 7 °C/s with 7 s hold-time	107
Figure 31: Histogram of deviations from linearity for 500°C at 7 °C/s with 7 s hold-time	108
Figure 32: Linearity in thermal stimulation for TL done up to 500 °C at 6 °C/s with	

5 s hold-time	109
Figure 33: Error in thermal stimulation for TL done up to 500 °C at 6 °C/s with	
5 s hold-time	109
Figure 34: Histogram of deviations from linearity for 500°C at 6 °C/s with	
5 s hold-time	110
Figure 35: Linearity in thermal stimulation for TL done up to 500 °C at 5 °C/s with	
7 s hold-time	111
Figure 36: Error in thermal stimulation for TL done up to 500 °C at 5 °C/s with	
7 s hold-time	111
Figure 37: Histogram of deviations from linearity for 500°C at 5 °C/s with	
7 s hold-time	112
Figure 38: Linearity in thermal stimulation for TL done up to 500 °C at 4 °C/s with	
5 s hold-time	113
Figure 39: Error in thermal stimulation for TL done up to 500 °C at 4 °C/s with	
5 s hold-time	113
Figure 40: Histogram of deviations from linearity for 500°C at 4 °C/s with	
5 s hold-time	114
Figure 41: Linearity in thermal stimulation for TL done up to 500 °C at 3 °C/s with	
5 s hold-time	115
Figure 42: Error in thermal stimulation for TL done up to 500 °C at 3 °C/s with	
5 s hold-time	115
Figure 43: Histogram of deviations from linearity for 500°C at 3°C/s with	
5 s hold-time	116
Figure 44: Linearity in thermal stimulation for TL done up to 500 °C at 2 °C/s with	
5 s hold-time	116
Figure 45: Error in thermal stimulation for TL done up to 500 °C at 2 °C/s with	
5 s hold-time	117
Figure 46: Histogram of deviations from linearity for 500°C at 2 °C/s with	
5 s hold-time	117
Figure 47: Linearity in thermal stimulation for TL done up to 500 °C at 1 °C/s with	
7 s hold-time	119
Figure 48: Error in thermal stimulation for TL done up to 500 °C at 1 °C/s with	
7 s hold-time	120
Figure 49: Histogram of deviations from linearity for 500 °C at 1 °C/s with 7 s hold-time	120

Figure 50: Linearity in thermal stimulation for TL done up to 350 °C at 0.5 °C/s	120
Figure 51: Error in thermal stimulation for TL done up to 350 °C at 0.5 °C/s	121
Figure 52: Histogram of deviations from linearity for 350°C at 0.5 °C/s	121
Figure 53: Linearity in optical stimulation for ramping upto 100% intensity at 0.1 %/s rate with 15 s hold-time	123
Figure 54: Error in optical stimulation for OSL done up to 100% at 0.1 %/s with 15 s hold-time	123
Figure 55: Histogram for 100% at 0.1 %/s with 15 s hold-time	123
Figure 56: Linearity in optical stimulation for ramping upto 100% intensity at 0.5 %/s rate with 15 s hold-time	124
Figure 57: Error in optical stimulation for OSL done up to 100% at 0.5 %/s with 15 s hold-time	125
Figure 58: Histogram for 100% at 0.5 %/s with 15 s hold-time	125
Figure 59: Linearity in optical stimulation for ramping upto 100% intensity at 1 %/s rate with 15 s hold-time	126
Figure 60: Error in optical stimulation for OSL done up to 100% at 1 %/s with 15 s hold-time	127
Figure 61: Histogram for 100% at 1 %/s with 15 s hold-time	127
Figure 62: Linearity in optical stimulation for ramping upto 100% intensity at 1.5 %/s rate with 15 s hold-time	128
Figure 63: Error in optical stimulation for OSL done up to 100% at 1.5 %/s with 15 s hold-time	129
Figure 64: Histogram for 100% at 1.5 %/s with 15 s hold-time	129
Figure 65: Linearity in optical stimulation for ramping upto 100% intensity at 2 %/s rate with 15 s hold-time	130
Figure 66: Error in optical stimulation for OSL done up to 100% at 2 %/s with 15 s hold-time	130
Figure 67: Histogram for 100% at 2 %/s with 15 s hold-time	131
Figure 68: Error in optical stimulation for CW-OSL (step profile) at 70% intensity for 30 s	132
Figure 69: Histogram for optical stimulation for CW-OSL (step profile) at 70% intensity for 30s	132
Figure 70: Luminescence from quartz	133
Figure 71: Luminescence from Feldspar	134

Figure 72: Counts versus dose graph for the Daybreak system	135
Figure 73: Counts versus dose graph for the Risoe system	136
Figure 74: Luminescence from Calcium Fluoride	137

Chapter 4

Figure 1: Powder X-ray diffraction patterns	146
Figure 2: Structure of CaF ₂	147
Figure 3: Optical absorption spectrum of CaF ₂ nanocrystals	151
Figure 4: Energy band gap plot of pure CaF ₂ nanocrystals	151
Figure 5: Schematic of PL instrument	154
Figure 6: PL emission spectrum of CaF ₂ nanocrystals excited at 235 nm.	155

Chapter 5

Figure 1: Transmission curve for Schott bg39 filter of 2 mm thickness.	161
Figure 2: Glow curves of CaF ₂ annealed in vacuum and in air	161
Figure 3: Glow curves of CaF ₂ annealed at different temperature	163
Figure 4: TL sensitivity of CaF ₂ for different annealing temperature at a fixed annealing duration of 1.5 h	163
Figure 5: FWHM for different annealing temperature at a fixed annealing duration of 1.5 h	164
Figure 6: T _m with respect to different annealing temperatures for a fixed annealing duration of 1.5 h	164
Figure 7: Annealing at various duration while keeping the temperature fixed at 500 °C and at 600 °C	166
Figure 8: Glow curves for different duration of annealing for fixed temperature of 500 °C	166
Figure 9: TL sensitivity for different duration of annealing for fixed temperature of 500 °C	167
Figure 10: FWHM for different duration of annealing for fixed temperature of 500 °C	167
Figure 11: Peak temperature (T _m) for different duration of annealing for fixed temperature of 500 °C	168
Figure 12: Effect of different heating rate on the glow curve	169
Figure 13: Difference between first order kinetic and second order kinetics	

glow-curve	172
Figure 14: Transmission curve for Schott bg39 filter of 2 mm thickness.	173
Figure 15: TL glow curve of the phosphor at sequentially increasing temperatures	175
Figure 16: Graph of $\ln(I)$ vs $1/kT$ for TL up to 180 °C	176
Figure 19: Activation energy at different temperatures	178
Figure 17: Graph of $\ln(I)$ vs $1/kT$ for TL up to 200 °C	177
Figure 18: Graph of $\ln(I)$ vs $1/kT$ for TL up to 220 °C	177
Figure 20: Geometrical parameters for the glow curve method of analysis	179
Figure 21: Relation between the symmetry factor (μ) and the order of kinetics (b)	180
Figure 22: Effect of various heating rate on the glow curve	184
Figure 23: Graph of $\ln\left(\frac{\beta}{T_M^2}\right)$ versus $\left(\frac{1}{kT_M}\right)$ to calculate the activation energy	185
Figure 24: TL dose response of CaF ₂	186
Figure 25: Saturation exponential	187
Figure 26: CW-OSL mode stimulation and emission	190
Figure 27: LM-OSL mode stimulation and emission	190
Figure 28: POSL mode stimulation and emission	191
Figure 29: Transmission curve for schott bg39 filter of 2 mm thickness	193
Figure 30: Transmission curve for Hoya u340 filter of 7.5 mm thickness	193
Figure 31: Transmission curve for Corning 7-59 filter of 4 mm thickness.	194
Figure 32: The green curve is the resultant transmission of the bg39 and Corning 7-59 filter	194
Figure 33: Decay curve for IR OSL with bg39 filter	195
Figure 34: Decay curve for IR-OSL with bg39 +7-59 filter	196
Figure 35: Decay curve for IR-OSL with u340 filter	196
Figure 36: Decay curve for blue OSL with u340 filter	197
Figure 37: OSL dose response	198
Figure 38: OSL dose response	199
Figure 39: Glow-curve of CaF ₂	201
Figure 40: OSL decay curve without any prior TL	201
Figure 41: TL till 120 °C to remove the first peak	202
Figure 42: OSL decay curve after the first peak was thermally removed	202
Figure 43: TL till 400 °C to remove the second peak	203

