

List of Tables

| Table | Title | Page |
|--------------|--|-------------|
| 2.1 | Roughness Coefficients for New Pipes (Rossman 2000) | 19 |
| 2.2 | Bulk chlorine decay kinetic models (Powell et al. 2000 b) | 41 |
| 2.3 | Kinetic decay model evaluated against experimental chlorine decay data (Helbling et al. 2009) | 45 |
| 2.4 | First order decay constants (Powell et al., 2000 a) | 51 |
| 2.5 | Optimization methods used for optimal scheduling, operation and location of booster stations | 72 |
| 2.6 | Objective functions used for the optimization methods | 72 |
| 2.7 | Major findings of various researchers by application of booster chlorination | 74 |
| 3.1 | Sample network node and link properties (Example 1) | 81 |
| 3.2 | Results of hydraulic parameters (Example 1) | 83 |
| 3.3 | Concentration of residual chlorine at various nodes at the end of different travelling time for two cases | 93 |
| 3.4 | Mass rate of chlorine applied at various locations (Example Network) | 95 |
| 4.1 | Reduction in chlorine mass rate for different scenario, cases and mode of water supply (Example Problem) | 105 |
| 4.2 | Consumer and Pump Demand Multipliers (Case Study 1) | 110 |
| 4.3 | Injection rates of chlorine for booster stations (A to F) for Case Study 1 | 111 |
| 4.4 | Source and quantity of water supply (VMSS; https://vmc.gov.in) | 116 |
| 4.5 | Present and Future water demand (VMSS; https://vmc.gov.in) | 117 |
| 4.6 | Population forecasting and command area for each tank and Zone (VMSS; https://vmc.gov.in) | 118 |
| 4.7 | Determination of Chlorine Decay Coefficient (Case Study 2) | 124 |
| 4.8 | Variations in pressure, chlorine and THM (EPS of 10 days for last 24 hours) for Case Study 2 | 127 |
| 4.9 | Distribution of residual chlorine at different nodes (Case Study 3). | 136 |
| 4.10 | Injection rates of chlorine for booster stations (Case Study 4) | 139 |
| 4.11 | Pressure at all nodes after 10 days extended period simulation(Case Study 4) | 141 |
| 4.12 | Injection rates of chlorine for booster stations (Case Study 5) | 147 |
| 5.1 | Impulse response coefficients for the sample network (Fig 3.4) | 158 |
| 5.2 | Impulse response coefficients for the example network (Fig 3.5) | 159 |

| | | |
|------|---|-----|
| 5.3 | Value of Impulse response coefficients at critical nodes. (Case Study 6: MJ-1H-LP) | 166 |
| 5.4 | Total mass rate of chlorine applied for combination of two booster stations with source application(Case Study 6: MJ-1H-LP) | 167 |
| 5.5 | Optimization results for chlorine application (Case study: 6: MJ-1H-LP) | 168 |
| 5.6 | Sensitivity analysis for bulk decay coefficient (Case study: 6: MJ-1H-LP) | 171 |
| 5.7 | Value of Impulse response coefficients at critical nodes (Case study 7: MJ-2H-LP) | 173 |
| 5.8 | Total mass rate of chlorine applied for combination of two booster stations with source application(Case study 7: MJ-2H-LP) | 174 |
| 5.9 | Optimization results for chlorine application(Case study 7: MJ-2H-LP) | 175 |
| 5.10 | Value of Impulse response coefficients at critical nodes (Case study 8 :NH-1H-LP) | 182 |
| 5.11 | Total mass rate of chlorine applied for combination of two booster stations with source application(Case study 8 :NH-1H-LP) | 183 |
| 5.12 | Optimization results for chlorine application (Case study 8 :NH-1H-LP) | 184 |
| 5.13 | Value of Impulse response coefficients at critical nodes (Case study 9: NH-2H-LP) | 190 |
| 5.14 | Total mass rate of chlorine applied for combination of two booster stations with source application(Case study 9: NH-2H-LP) | 192 |
| 5.15 | Optimization results for chlorine application(Case study 9: NH-2H-LP) | 192 |
| 5.16 | Value of Impulse response coefficients at critical nodes for case II (Case study 10: NH-2HD-LP) | 195 |
| 5.17 | Total mass rate of chlorine applied for combination of one booster station with source application(Case study 10: NH-2HD-LP) | 196 |
| 5.18 | Total mass rate of chlorine applied for combination of two booster stations with source application(Case study 10: NH-2HD-LP) | 197 |
| 5.19 | Optimization results for chlorine application(Case study 10: NH-2HD-LP) | 198 |
| 5.20 | Summary Table for different flow conditions and water supply hours (NH and MJ using LP Optimization Method) | 203 |
| 5.21 | Values of impulse response coefficients at critical nodes for case II and III (Case Study 11: NH-2HD-PSO) | 211 |

| | | |
|------|---|-----|
| 5.22 | Fitness Function value for different Mass rate application of Chlorine (Case Study 11: NH-2HD-PSO) | 215 |
| 5.23 | Sensitivity analysis for PSO parameters (Two decision variables) for Case Study 11: NH-2HD-PSO) | 217 |
| 5.24 | Sensitivity analysis for three decision variables (Case Study 11: NH- 2HD-PSO) | 218 |
| 5.25 | Chlorine mass rate to be applied at various locations after using Optimization (Case Study 11: NH-2HD-PSO) | 219 |
| 5.26 | Chlorine mass rate at optimum locations after using PSO Optimization (Case Study 12: NH-2HD-PSO-OL) | 221 |
| 5.27 | Sensitivity analysis for the various parameters of PSO (Case Study 12: NH-2HD-PSO-OL) | 221 |
| 5.28 | Chlorine mass rate at various locations after using PSO Optimization (Case Study 13: NH-1H-PSO-OL) | 223 |
| 5.29 | Sensitivity analysis for various PSO parameters (Case Study 13: NH- 1H-PSO-OL) | 223 |
| 5.30 | Chlorine mass rate at various locations after using PSO Optimization (Case Study 13: NH-2H-PSO-OL) | 224 |
| 5.31 | Chlorine mass rate at optimum locations after using PSO Optimization. (Case Study 14: MJ-1H-PSO-OL) | 225 |
| 5.32 | Sensitivity analysis for PSO parameters (Case Study 14: MJ-1H-PSO- OL) | 226 |
| 5.33 | Chlorine mass rate at optimum locations after using PSO Optimization (Case Study 14: MJ-2H-PSO-OL) | 226 |
| 5.34 | Chlorine mass rate to be applied at optimum locations of booster stations (MJ-1H-LP & MJ-1H-PSO-OL, Fig 5.3) | 228 |
| 5.35 | Chlorine mass rate to be applied at optimum locations of booster stations (MJ-2H-LP & MJ-2H-PSO-OL, Fig 5.3) | 229 |
| 5.36 | Chlorine mass rate to be applied at optimum locations of booster stations (NH-1H-LP & NH-1H-PSO-OL, Fig. 5.15) | 230 |
| 5.37 | Chlorine mass rate to be applied at optimum locations of booster stations (NH-2H-LP & NH-2H-PSO-OL, Fig. 5.15) | 231 |
| 5.38 | Chlorine mass rate to be applied at various locations (NH-2HD-LP , NH-2HD-PSO & NH-2HD-PSO-OL, Fig.5.24) | 232 |

| | | |
|------|---|-----|
| 5.39 | Impact Matrix for booster chlorination station (North Harni DWDS for 2 hour duration with deficit flow condition) | 235 |
| 5.40 | Impact Matrix for booster chlorination station (Manjalpur DWDS for 2 hour duration) | 237 |
| 5.41 | Cost analysis for the optimum solution of booster chlorination station (NH-2HD) | 240 |
| 5.42 | Cost analysis for the optimum solution of booster chlorination station (MJ-1H) | 240 |