

List of Figures

2.1	Functional Evaluation of Mechanical Spring and Electrical Spring.	18
2.2	System of ES, Comprising of Smart Load and Critical Load.	19
2.3	System of ES Considered as a Network for the Execution of Mathematical Model.	21
2.4	Frequency Response Plot of the LC Filter, Tested Against the Prospective Loads of ES	29
2.5	Absolute Spectrum of Results Gathered from Test-Bench(0-6s)	29
2.6	Results Associated with R_1 - L Load.	30
2.7	Results Associated with R_2 - L Load.	30
2.8	Results Associated with R_1 - C Load.	31
2.9	Results Associated with R_2 - C Load.	31
2.10	Results Associated with R_1 Load.	32
2.11	Results Associated with R_2 Load.	32
2.12	Spectrum of Results showing the Ripples.	33
2.13	FFT spectrum of Results Associated with Inverter.	33
2.14	Simulation Test Bench of the system of Electric Spring.	34
2.15	Results of the Simulation Test Bench, without the Presence of Electric Spring.	35
3.1	Standar Structure of a Phase-Locked-Loop (PLL).	37
3.2	Experimental Test System, for Checking the Robustness of PLL	42
3.3	T/3 Delay PLL , using Clarke's Transformation.	43
3.4	Results of the $T/3$ -Delay PLL , amidst (a) Presence of 3^{rd} and 5^{th} Har- monics, (b) Change in signal Magnitude and Phase Jump, and (c) Change in Frequency.	44

3.5	<i>SOGI-PLL</i> Structure Employing a <i>Lead</i> Compensator.	46
3.6	Performance Analysis of <i>SOGI</i> through (a) Bode Plot of u'/u , and (b) Bode Plot of qu/u	48
3.7	Performance Analysis of <i>SOGI</i> through Step Response Employing u'/u . . .	49
3.8	Performance Analysis of <i>SOGI</i> through Instantaneous Variation of u , u' and qu	49
3.9	Performance Analysis of <i>SOGI</i> through (a) u and qu in the presence of 3^{rd} and 5^{th} Harmonics, and (b) <i>FFT</i> of u and qu in the presence of 3^{rd} and 5^{th} Harmonics.	50
3.10	Frequency Response of Controller Employing <i>Lead</i> Compensator.	52
3.11	Absolute Spectrum of the Results Fached through <i>SOGI-PLL</i>	52
3.12	Results of <i>SOGI-PLL</i> Showing Start-up Delay.	53
3.13	Performance of <i>SOGI-PLL</i> in the Presence of Harmonics.	53
3.14	Performance of <i>SOGI-PLL</i> Amidst Step Change Applied in the Magnitude of the Input Signal.	54
3.15	Performance of <i>SOGI-PLL</i> Amidst Step Change Applied in the Phase of the Input Signal.	54
3.16	<i>E-PLL</i> Structure.	56
3.17	Absolute Spectrum of <i>E-PLL</i> Results.	58
3.18	Spectrum of <i>E-PLL</i> Results Showing Start-up Delay.	58
3.19	Spectrum of <i>E-PLL</i> Results Showing Frequency Jump.	59
3.20	Spectrum of <i>E-PLL</i> Results Showing Step Change in the Amplitude. . . .	59
3.21	Spectrum of <i>E-PLL</i> Results Showing Phase Jump.	60
3.22	Performance of <i>E-PLL</i> in the Presence of Harmonics in the Input.	60
3.23	<i>E-PLL</i> Results Showing the <i>FFT</i> Spectrum of the Input and Output Signals. .	61
3.24	Absolute Spectrum of Comparative Results associated with u and y for (a) Instantaneous Per Unit Values, (b) Instantaneous Phase Variation, (c) Amplitude Variation and (d) Frequency Variation, of input and corresponding output of <i>E-PLL</i> and <i>SOGI-PLL</i>	63
3.25	Magnified View of the Comparative Results Showing Start-up Delay. . . .	64
3.26	Magnified View of the Comparative Results Showing Step Change in the Magnitude.	64

3.27 Magnified View of the Comparative Results Showing Step Change in Frequency.	65
3.28 Magnified View of the Comparative Results Showing Phase Jump.	66
3.29 Magnified View of the Comparative Results Showing Simultaneous Step Change in Amplitude and Frequency.	66
3.30 Magnified View of the Comparative Results for Harmonically Molested Signal.	67
4.1 Control Block of <i>ES</i> Employing <i>PI</i> Controller.	71
4.2 Frequency Response Plot and Step Response of System of <i>ES</i> Employing <i>PI</i> Controller.	73
4.3 Instantaneous and RMS Variations in the System Parameters at the Wake of Step Changes in Load and Grid Voltage.	74
4.4 Instantaneous and RMS Variations in the System Parameters with R_1 - L Load, at the Wake of Step Change in v_g	75
4.5 Instantaneous and RMS Variations in the System Parameters with R_2 - L Load, at the Wake of Step Change in v_g	75
4.6 Instantaneous and RMS Variations in the System Parameters with R_1 - C Load, at the Wake of Step Change in v_g	76
4.7 Instantaneous and RMS Variations in the System Parameters with R_2 - C Load, at the Wake of Step Change in v_g	76
4.8 Instantaneous and RMS Variations in the System Parameters with R_1 Load, at the Wake of Step Change in v_g	77
4.9 Instantaneous and RMS Variations in the System Parameters with R_2 Load, at the Wake of Step Change in v_g	77
4.10 Control Block of <i>ES</i> Employing Loop-in-Loop Controller.	78
4.11 Frequency Response Plots of the loop gains employing (a) PI_i , (b) PI_v Controllers	80
4.12 Results of Cascade Control having Step Changes Applied to v_g and Load. .	81
4.13 Results of Cascade Control having Step Changes in v_{cr} , for R_1 - L Load. . .	82
4.14 Results of Cascade Control having Step Changes in v_{cr} , for R_2 - L Load. . .	82
4.15 Results of Cascade Control having Step Changes in v_{cr} , for R_1 - C Load. . .	83
4.16 Results of Cascade Control having Step Changes in v_{cr} , for R_2 - C Load. . .	83

4.17	Results of Cascade Control having Step Changes in v_{cr} , for R_1 Load. . . .	84
4.18	Results of Cascade Control having Step Changes in v_{cr} , for R_2 Load. . . .	84
4.19	Performance Comparison of Cascade Control having feedback through i_{lf} and I_{cf} and Corresponding variation in i_{lf} and I_{cf}	85
4.20	Comparison of Results of Cascade Control having feedback through I_{lf} and I_{cf}	85
4.21	Comparison of Results, Achieved from Two Control Strategies, Pertaining to (a) Voltage Signals, (b) Current Signals and Power.	89
5.1	Frequency Response plot of <i>Lead-Lag</i> Controller, while Evolving through its Design.	94
5.2	Step Response of the Uncontrolled System, and that being Controlled by a <i>Lead-Lag</i> Compensator.	96
5.3	<i>SPWM</i> Controlled <i>ES</i>	96
5.4	Results of <i>Lead-Lag</i> (SPWM) Control having Step Changes Applied to v_g and Load.	98
5.5	Results of <i>Lead-Lag</i> (SPWM) Control having Step Changes in v_{cr} , for R_1 - L Load.	99
5.6	Results of <i>Lead-Lag</i> (SPWM) Control having Step Changes in v_{cr} , for R_2 - L Load.	99
5.7	Results of <i>Lead-Lag</i> (SPWM) Control having Step Changes in v_{cr} , for R_1 - C Load.	100
5.8	Results of <i>Lead-Lag</i> (SPWM) Control having Step Changes in v_{cr} , for R_2 - C Load.	100
5.9	Results of <i>Lead-Lag</i> (SPWM) Control having Step Changes in v_{cr} , for R_1 Load.	101
5.10	Results of <i>Lead-Lag</i> (SPWM) Control having Step Changes in v_{cr} , for R_2 Load.	101
5.11	Comparison of Results of <i>Lead-Lag</i> Controlled <i>ES</i> and that with no <i>ES</i> , under the influence of Step Changes in v_g and Load.	102
5.12	<i>SVPWM</i> Controlled <i>ES</i> using <i>Lead-Lag</i> Compensator.	104
5.13	Results of <i>Lead-Lag</i> (SVPWM) Control having Step Changes Applied to v_g and Load.	106

5.14 Results of <i>Lead-Lag</i> (SVPWM) Control having Step Changes in v_{cr} , for R_1 - L Load.	106
5.15 Results of <i>Lead-Lag</i> (SVPWM) Control having Step Changes in v_{cr} , for R_2 - L Load.	107
5.16 Results of <i>Lead-Lag</i> (SVPWM) Control having Step Changes in v_{cr} , for R_1 - C Load.	107
5.17 Results of <i>Lead-Lag</i> (SVPWM) Control having Step Changes in v_{cr} , for R_2 - C Load.	108
5.18 Results of <i>Lead-Lag</i> (SVPWM) Control having Step Changes in v_{cr} , for R_1 Load.	108
5.19 Results of <i>Lead-Lag</i> (SVPWM) Control having Step Changes in v_{cr} , for R_2 Load.	109
5.20 Results (RMS values) of <i>SVPWM</i> Controlled <i>ES</i> , using <i>Lead-Lag</i> Compensator, being Compared with the Scenario of Absence of <i>ES</i> , in the presence of Step Changes Applied to v_g and Load.	109
5.21 Control Parameters (Instantaneous Values) of <i>SVPWM</i> Controlled <i>ES</i> . .	110
5.22 Magnified Spectrum of the Control Parameters (Instantaneous Values) of <i>SVPWM</i> Controlled <i>ES</i> , Showing R_1 Load and Step Changes Applied to v_g	110
5.23 FFT Spectrum of Results presented in Fig:5.22.	111
5.24 Comparative Results (RMS values of Voltages) of <i>SVPWM</i> and <i>SPWM</i> Controlled <i>ES</i> , using <i>Lead-Lag</i> Compensator, having Step Changes Applied to v_g and Load.	112
5.25 Comparative Results (RMS values of Currents and Power) of <i>SVPWM</i> and <i>SPWM</i> Controlled <i>ES</i> , using <i>Lead-Lag</i> Compensator, having Step Changes Applied to v_g and Load.	112
6.1 Schema of State Feedback controlled <i>ES</i> , using <i>LQI</i> controller.	120
6.2 The control block of <i>ES</i> , with <i>LQI</i> control.	126
6.3 Bode plot of the system under various system conditions.	127
6.4 Step response of uncontrolled system, <i>LQR</i> controlled system and <i>LQI</i> controlled system.	128

6.5	Absolute Spectrum of LQI Control having Step Changes Applied to v_g and Load.	130
6.6	Results of LQI Control having Step Changes in v_{cr} , for R_1 - L Load.	130
6.7	Results of LQI Control having Step Changes in v_{cr} , for R_2 - L Load.	131
6.8	Results of LQI Control having Step Changes in v_{cr} , for R_1 - C Load.	131
6.9	Results of LQI Control having Step Changes in v_{cr} , for R_2 - C Load.	132
6.10	Results of LQI Control having Step Changes in v_{cr} , for R_1 Load.	132
6.11	Results of LQI Control having Step Changes in v_{cr} , for R_2 Load.	133
6.12	Comparison of Results of LQI Controlled ES and that with no ES , under the influence of Step Changes in v_g and Load.	133
6.13	Phasors of LQI controlled system, with (a) R Load when $v_g < v_{ref}$, (b) R Load when $v_g > v_{ref}$, (c) R - C Load when $v_g < v_{ref}$, (d) R - C Load when $v_g > v_{ref}$, (e) R - L Load when $v_g < v_{ref}$, and (f) R - L Load when $v_g > v_{ref}$. .	134
7.1	Results (RMS values) of having Step Changes Applied to V_g and Load, and corresponding V_{cr} in the absence of ES	138
7.2	Variation in V_{cr} in the Presence of PI , $SPWM_{LL}$, $Cascaded-PI$, $SVPWM_{LL}$, and optimal- LQI Controlled ES , having Step Changes Applied to V_g and Load.	139
7.3	Variation in V_{nc} in the Presence of PI , $SPWM_{LL}$, $Cascaded-PI$, $SVPWM_{LL}$, and optimal- LQI Controlled ES , having Step Changes Applied to V_g and Load.	140
7.4	Variation in V_{es} in the Presence of PI , $SPWM_{LL}$, $Cascaded-PI$, $SVPWM_{LL}$, and optimal- LQI Controlled ES , having Step Changes Applied to V_g and Load.	140
7.5	Variation in I_g in the Presence of PI , $SPWM_{LL}$, $Cascaded-PI$, $SVPWM_{LL}$, and optimal- LQI Controlled ES , having Step Changes Applied to V_g and Load.	141
7.6	Variation in I_{nc} in the Presence of PI , $SPWM_{LL}$, $Cascaded-PI$, $SVPWM_{LL}$, and optimal- LQI Controlled ES , having Step Changes Applied to V_g and Load.	142

7.7	Variation in I_{cr} in the Presence of PI , $SPWM_{LL}$, $Cascaded-PI$, $SVPWM_{LL}$, and optimal- LQI Controlled ES , having Step Changes Applied to V_g and Load.	142
7.8	Variation in I_{inv} in the Presence of PI , $SPWM_{LL}$, $Cascaded-PI$, $SVPWM_{LL}$, and optimal- LQI Controlled ES , having Step Changes Applied to V_g and Load.	143
7.9	Variation in $Power$ in the Presence of PI , $SPWM_{LL}$, $Cascaded-PI$, $SVPWM_{LL}$, and optimal- LQI Controlled ES , having Step Changes Applied to V_g and Load.	144
7.10	Simulation Test Bench for Testing the Performance of ES and hence Controller.	145
7.11	Variations Applied to V_g , Z_g , V_{dc} and Critical Load (Z_c).	146
7.12	Performance Evaluation of $Cascaded-PI$ Controlled ES (inner loop feedback from i_{lf}), through V_{cr} , having Step Changes Applied to V_g , Z_g , V_{dc} and Z_c	146
7.13	Performance Evaluation of PI Controlled ES , through V_{cr} , having Step Changes Applied to V_g , Z_g , V_{dc} and Z_c	146
7.14	Performance Evaluation of $Lead-Lag$ compensated and $SPWM$ Controlled ES , through V_{cr} , having Step Changes Applied to V_g , Z_g , V_{dc} and Z_c	147
7.15	Performance Evaluation of $Lead-Lag$ compensated and $SVPWM$ Controlled ES , through V_{cr} , having Step Changes Applied to V_g , Z_g , V_{dc} and Z_c	147
7.16	Performance Evaluation of Optimal LQI Controlled ES , through V_{cr} , having Step Changes Applied to V_g , Z_g , V_{dc} and Z_c	148
7.17	Performance Evaluation of $Cascaded-PI$ Controlled ES (inner loop feedback from i_{cf}), through V_{cr} , having Step Changes Applied to V_g , Z_g , V_{dc} and Z_c	148