

# *List of Figures*

| <b>Figure No</b>   | <b>TITLE</b> | <b>Page No</b> |
|--|--------------|----------------|
| Fig.1. 1General Control Structure.....   |              | 2              |
| Fig.1. 2 Control Performance Criteria using PSO algorithm.....                     |              | 6              |
| Fig.1. 3Multiple Model Adaptive Control Scheme .....                               |              | 7              |
| Fig.1. 4 Block diagram for Processor in loop configuration using ezdsp 28335.....  |              | 9              |
| Fig.1. 5 System Set up for Processor in loop configuration using ezdsp 28335.....  |              | 9              |
| Fig.1. 6 Organizing structure of thesis.....                                       |              | 10             |
| <br>   |              |                |
| Fig. 2.1 Local oscillations.....   |              | 15             |
| Fig. 2.2Interplant oscillations .....  |              | 15             |
| Fig. 2.3Inter area oscillations.....   |              | 15             |
| Fig. 2.4 Adaptive control .....  |              | 20             |
| Fig. 2.5Classification of various control problems.....                            |              | 23             |
| Fig. 2.6 Structuring of soft computing for power system stabilization .....        |              | 24             |
| Fig. 2.7Development a Structure of robust MMAC for power system stabilization..... |              | 25             |
| <br>   |              |                |
| Fig. 3. 1 The basic block diagram of CPSS .....                                    |              | 26             |
| Fig. 3. 2Basic block diagram of Power system configuration for SMIB system.....    |              | 27             |
| Fig. 3. 3The Block diagram representation of PSS for SMIB System .....             |              | 28             |
| Fig. 3. 4 A single machine infinite bus system [8] .....                           |              | 29             |
| Fig. 3. 5 Torque angle loop.....   |              | 30             |
| Fig. 3. 6 Flux decay loop [8]......  |              | 31             |
| Fig. 3. 7 Excitation system loop.....  |              | 31             |
| Fig. 3. 8 Overall block diagram of the system.....                                 |              | 33             |
| Fig. 3. 9Modelling of multimachine Infinite bus system.....                        |              | 35             |
| Fig. 3. 10 Multimachine system.....  |              | 36             |
| Fig. 3. 11Transmission network for multimachine system.....                        |              | 36             |
| Fig. 3. 12Fuzzy logic controllers with two inputs and output .....                 |              | 39             |

|   |    |
|---|----|
| Fig. 3. 13Membership function for speed deviation .....   | 40 |
| Fig. 3. 14Membership function for acceleration.....   | 40 |
| Fig. 3. 15Membership function for voltage signal.....   | 40 |
| Fig. 3. 16Artificial neural network models.....   | 42 |
| <br>  |    |
| Fig. 4. 1Simulink model for 5% change in mechanical torque input With CPSS .....                                | 46 |
| Fig. 4. 2Simulink model Multimachine system with CPSS .....   | 46 |
| Fig. 4. 3 Location of PSS (Subsystem of Fig 4.2) .....  | 47 |
| Fig. 4. 4 Rotor Angle Performance of PSS installed in multimachine system for light loading condition .....     | 47 |
| Fig. 4. 5 Rotor Angle Performance of PSS installed in multimachine system for normal loading condition .....    | 48 |
| Fig. 4. 6 Rotor Angle Performance of PSS installed in multimachine system for heavy loading condition .....     | 49 |
| Fig. 4.7Voltage performance of PSS installed in multimachine system for light loading condition .....           | 49 |
| Fig. 4.8Voltage performance of PSS installed in multimachine system for normal loading.....                     | 50 |
| Fig. 4.9Voltage performance of PSS installed in multimachine system for heavy loading .....                     | 50 |
| Fig. 4.10Real power performance of PSS installed in multimachine system for light loading condition .....       | 51 |
| Fig. 4. 11 Real power performance of PSS installed in multimachine system for normalt loading condition .....   | 51 |
| Fig. 4. 12 Real power performance of PSS installed in multimachine system for heavy loading condition .....     | 52 |
| Fig. 4. 13Reactive power performance of PSS installed in multimachine system for light loading condition .....  | 52 |
| Fig. 4. 14Reactivepower performance of PSS installed in multimachine system for normal loading condition .....  | 53 |
| Fig. 4. 15 Reactive power performance of PSS installed in multimachine system for heavy loading condition ..... | 53 |
| Fig. 4.16Simulink model for 5% change in mechanical torque input With FPSS.....                                 | 54 |
| Fig. 4.17Simulink model for multimachine system With FPSS .....   | 55 |
| Fig. 4.18Simulink model for 5% change in mechanical torque input With ANNPSS .....                              | 56 |

|           |  |    |
|-----------|--|----|
| Fig. 4.19 | Simulink model for Multimachine system with ANNPSS .....                             | 57 |
| Fig. 4.20 | Rotor angle comparisons for multimachine system (Light Loading Condition).....       | 59 |
| Fig. 4.21 | Rotor angle comparisons for multimachine system (Normal Loading Condition) .....     | 59 |
| Fig. 4.22 | Rotor angle comparisons for multimachine system (Heavy Loading Condition) .....      | 60 |
| Fig. 4.23 | Voltagecomparisons for multimachine system(Light Loading Condition) .....            | 61 |
| Fig. 4.24 | Voltagecomparisons for multimachine system (Normal Loading Condition) .....          | 62 |
| Fig. 4.25 | Voltagecomparisons for multimachine system (Heavy Loading Condition) .....           | 62 |
| Fig. 4.26 | Real power comparisons for multimachine system (Light Loading Condition) .....       | 63 |
| Fig. 4.27 | Real power comparisons for multimachine system (Normal Loading Condition).....       | 64 |
| Fig. 4.28 | Real power comparisons for multimachine system(Heavy Loading Condition) .....        | 64 |
| Fig. 4.29 | Reactive power comparisons for multimachine system(Light Loading Condition).....     | 66 |
| Fig. 4.30 | Reactive power comparisons for multimachine system (Normal Loading Condition) ..     | 66 |
| Fig. 4.31 | Reactive power comparisons for multimachine system (Heavy Loading Condition)....     | 67 |
| Fig. 4.   | 32four quadrants operation of power meter connected to register positive power ..... | 68 |

|           |   |    |
|-----------|---|----|
| Fig. 5.1  | PIL configuration for Single Machine Infinite bus system .....  | 74 |
| Fig. 5.2  | PIL configuration for Multi Machine system .....  | 75 |
| Fig. 5.3  | HIL configuration for Single Machine Infinite bus system.....   | 76 |
| Fig. 5.4  | HIL configuration for Multi Machine system .....  | 76 |
| Fig. 5.5  | Simulink model for the generation of PIL & HIL for SMIB system .....  | 77 |
| Fig. 5.6  | Photograph of Hardware in loop configuration for SMIB system .....  | 77 |
| Fig. 5.7  | Simulink model for the generation of PIL & HIL for multimachine system .....  | 78 |
| Fig. 5.8  | Rotor Angle Variation for the generation of HIL Implemented PSS for multimachine underLight Loading Condition .....       | 79 |
| Fig. 5.9  | Real Power M1 for the generation of HIL Implemented PSS for multimachine under Light Loading Condition.....               | 80 |
| Fig. 5.10 | Voltage of M1 and M2 for the generation of HIL Implemented PSS for multimachine under Light Loading Condition .....       | 80 |
| Fig. 5.11 | Photograph of Hardware in loop configuration for Multimachine system.....   | 81 |
| Fig. 5.12 | Reactive Power of M1 and M2for the generation of HIL Implemented PSS for multimachine under Light Loading Condition ..... | 81 |
| Fig. 6.1  | Graphical user interface for Robust MMAC .....  | 87 |

|   |     |
|---|-----|
| Fig. 6.2 Controller 1 (Conventional control) is activated for the power system stabilization..... | 88  |
| Fig. 6.3 Controller 2 (Intelligent control) is activated for the power system stabilization ..... | 89  |
| Fig. 6.4 Performance comparisons of developed Controllers.....                                    | 90  |
| Fig. 6.5 Controller 3 (Smart control) is activated for the power system stabilization .....       | 91  |
| <br>  |     |
| Fig. E. 1 Soft Computational Fields.....  | 126 |
| Fig. E. 2 Schematic diagrams of MATLAB's main features.....                                       | 127 |
| Fig. E. 3 MATLAB Desktop.....   | 128 |
| Fig. E. 4 Command Window .....  | 129 |
| Fig. E. 5 Facilities of Simulink .....  | 130 |
| Fig. E. 6 Simulink library browser.....   | 131 |
| Fig. E. 7 Basic structure of fuzzy logic system.....  | 135 |
| Fig. E. 8 Components of Fuzzy controller.....   | 136 |
| Fig. E. 9The Biological Neurons .....   | 138 |
| Fig. E. 10Simple model of an Artificial Neuron.....   | 139 |
| Fig. E. 11 Multilayer Networks .....  | 140 |