

LIST OF FIGURES

Fig No.	Description	Page No.
2.1	PET polymer through DMT route	08
2.2	Process flowchart	10
2.3	Schematic diagram of melt-spinning process	16
2.4	Die swell	21
2.5	Dependence of critical shear rate on polydispersity index (PDI)	23
2.6	Typical fractured extrudate appearances of polymers	23
2.7	Draw resonance	24
2.8	Different zones of velocity and velocity gradient observed during melt spinning of fibers	26
2.9	Force balance on a spinning filament undergoing extension in spinning zone	31
2.10	Dependence of various forces on take-up velocity	32
2.11	Dependence of shear viscosity on molecular weight and shear rate of a polymer	34
2.12	Elongation fluid flow	39
2.13	Comparison of (a) shear flow and (b) elongation flow	40
2.14	Effect of strain rate on change in elongation viscosity with time for LDPE	41
2.15	Effect of strain rate on change in elongation viscosity with time for nylon -6	41
2.16	Fiber structure formation	42
2.17	Schematic diagram of PET melt spinning	44
2.18	Process variables in melt spinning	47
2.19	(a)CIQ (Circular Inflow Quench) system (TMT Machinery Inc.) (b)COQ (Circular Outflow Quench) system (TMT Machinery Inc.)	48
2.20	Circular inflow quench air system (TMT Machinery Inc.)	49

2.21	Force along the thread path for melt spinning with cross-flow air quench	50
2.22	(1) Influence of the cross-flowing air cooling on the filament temperature ($m=4.5$ gm /mm, spinneret hole dia. =0.9 mm)	52
	(2) Heat transfer coefficient between the cooling air & the filament surface as a function of the distance from the spinneret (a- with, b- without air quench)	
	(3) Filament surface temperature as a function of the time after leaving the spinneret hole (data as in 1)	
2.23	Cross quench air flow	54
2.24	(a) Effect of drawing velocity and viscosity	56
	(b) Relation of capillary wave failure	
2.25	(a) Temperature viscosity and tension in the polymer stream	58
	(b) Force equilibrium of spinning filament	
2.26	Principle of the high-pressure spinning process	60
2.27	Schematic drawing of a melt shroud	61
2.28	Spin draw process for PET	61
2.29	Different types of spin finish application system	62
2.30	Spin finish lick roll for installation in the quench chamber	64
2.31	Spin finish applicator rod	65
2.32	Metered spin finish application (a) Closed execution (b) Open execution	66
2.33	Double-sided metered spin finish application in the quench chamber	67
2.34	Spin finish pump assembly	67
2.35	Metered spin finish application system	68
2.36	Shear of fluids between plates	71
2.37	Stress-strain curve	72
2.38	Forms of viscosity	73
2.39	Types of viscometers	77

2.40	A diaphragm bursting strength tester	80
2.41	Ball bursting strength testing machine	81
2.42	Ball bursting strength tester attachment	82
2.43	Fabric tensile tester(before breakage)	84
2.44	Fabric tensile tester (after breakage)	86
4.1	Heat flow balance of a filament volume element	101
4.2	Quench screen length before and after modification	109
4.3	Quench screen width before and after modification	110
4.4	Quench chambers of two adjacent positions before increasing width of screens	111
4.5	Quench cambers of two adjacent positions after increasing width of quench screens	111
4.6	New screen size of 2500mm length and 1000mm width supplied by TMT, Japan	112
4.7	Jet spray finish application system	113
4.8	240/12 Four end PET mother yarn with kiss roll finish application system	114
4.9	Kiss roll spin finish application system	115
4.10	Kiss roll spin finish application system at two adjacent spinning positions	115
4.11	Take up with 8 ends winder	116
4.12	Modified take up with 4 ends winder	117
4.13	Umbrella type splitting machine top view	118
4.14	Umbrella type splitting machine full view	119
4.15	High-speed warp splitting machine, China made	120
4.16	Creel of warp splitting machine	121
4.17	Monofilament formation process at warp splitter	122
4.18	High-speed warp knitting machine	123
4.19	Alpha MNR spin finish tester	129