

LIST OF FIGURES

Fig. No.	Title	Page
2.1	World consumption of technical for textiles composites	6
2.2	Proportion of various textile reinforcement materials for composite (Year 2004-2005)	7
2.3	Organizations involved in the activities of reinforcement for (Year 2004-2005)	7
2.4	Break up of activities on reinforcement (Year 2004-2005)	8
2.5	Organisation involved in activities of matrix materials (Year 2004-2005)	8
2.6	Break up of activities on matrix materials	9
2.7	Distribution of end use applications of composites (Year 2005)	9
2.8	Conventional process and New process of composite manufacture	11
2.9	Role of performs in composite processing	13
2.10	Various structures of preform structures	15
2.11	Different structure of hybrid yarns showing fibre orientation	19
2.12	SEM of distribution of reinforce and matrix material in final composite in different type of hybrid yarn structure	21
2.13	Schematic diagram showing commingling process	22
2.14	Various nip structures	25
2.15	Various design of mingling nozzle	31
2.16	Air texturing units	37-38
	a) DS 90 MFB	
	b) DS 90 E	
	c) DT2-T SSM Staehe	

	d)	RM3T Digicon SSM Staehle	
2.17		Commingling Machine	38
	a)	Stahle DP3 C	
	b)	Fadis Air Covering Units	
2.18		Heberlein: Air texturing jet	39
2.19		Interlacing jets	40
	a)	Heberlein:slidjet	
	b)	Fibreguide	
	c)	TEMCO jet	
	d)	Interlace jet for Technical yarn	
2.20		Hollow spindles machine for the cover spinning process: MSE 150	42
2.21		Spindle assembly showing individual drives and intergrated bearing	42
2.22		Model Structure of commingled yarn	43
2.23		Interlacing counter RICa	45
2.24		The Scanning Electron Microscope	48
2.25		The SEM of various hybrid yarns	49
2.26		SEM of Glass/Polypropylene hybrid composite	49
2.27		Various models representing filament distribution in composite yarn	50
2.28		Various applications of thermoplastic composite	52
2.29		Applications of thermoplastic composites	53
	a)	Aircraft structure	
	b)	Wind turbine blade	
	c)	Wind mill	
	d)	Door-post	
	e)	Overhead panel	
	f)	Preforms	
2.30		Ring spinning	57
2.31		Open and spinning	57
2.32		Various frictional spinning syatem (Cover spinning)	58

	a)	Dref-II	
	b)	Dref-III	
2.33		Different twist direction of wrap yarns	59
2.34		Side-by –Side and Sheath-Core yarn	59
2.35		Variation in cross section of bicomponent yarns	60
2.36	a)	ASTM D257 Test Cell	64
	b)	Surface Resistivity Measurement using Meohmmeter	64
2.37		Press-Forming of thermoplastic composite sheets	66
2.38		Type-laying of thermoplastic composites	68
2.39		Liquid Moulding of a Thermoset Resin	68
2.40		Liquid Moulding of Thermoplastic Composite	68
3.1		Principle of hollow spindle wrapping process	72
3.2		Hollow spindle wrapping machine	73
	a)	Feed of parent yarns and winding of hybrid yarns	
	b)	Hollow spindle assemble	
3.3		Train of gears with wrap change gear	73
3.4		Schematic diagram showing detail of drive to spindle and winding unit	74
3.5		Raw material and sample prepared	78
3.6		Lloyd Tensile Tester	81
3.7	a)	Effect of linear density of core yarn on linear density of hybrid yarn	82
	b)	Effect of twist level on linear density of hybrid yarn	82
	c)	Effect of core linear density on breaking load of hybrid yarn	83
	d)	Effect of core yarn linear density on tenacity of hybrid yarn	83
	e)	Effect of core yarn linear density on extension of hybrid yarn	83
3.8	a)	Effect of wrap yarn linear density on linear density of hybrid yarn	84
	b)	Effect of wrap yarn linear density on breaking load of	85

	hybrid yarn	
	c) Effect of wrap yarn linear density on tenacity of hybrid yarn	85
	d) Effect of wrap yarn linear density on extension of hybrid yarn	85
3.9	a) Effect of core yarn material on breaking load of hybrid yarn	86
	b) Effect of core yarn materials on tenacity of hybrid yarn	87
	c) Effect of core yarn materials on extension of hybrid yarn	87
3.10	Effect of twist level on hybrid yarn properties	88
3.11	a) SEM of Glass/Polyester hybrid yarn	89
	b) SEM of Glass-Polypropylene/Polypropylene hybrid yarn	
4.1	Glass and Copper yarn packages used for hybrid yarn preparation	93
4.2	Material flow through the hollow spindle machine	94
4.3	Schematic model of hybrid yarn structures	95
4.4	Flat bed knitting machine	96
4.5	Hot press machine set up	97
4.6	Hot press machine outline	97
4.7	Thickness gauge	98
4.8	Knitted fabric structure	99
4.9	Universal testing machine	100
4.10	Sample mounting for flexural test	100
4.11	Principle of measurement dielectric strength	101
4.12	Set up for measuring dielectric strength	102
4.13	High resistance meter (Model: 4329 A)	103
4.14	Scanning electron micrograph	104
4.15	Linear density of conductive hybrid yarns	106
4.16	(a) Breaking load of parent and conductive hybrid yarns	106
	(b) Breaking extensions of parent and conductive hybrid yarns	107
	(c) Tenacity of parent and conductive hybrid yarns	107

	(d)	Contribution of parent yarn in breaking load of conductive hybrid yarn at 10mm elongation	108
4.17		Percentage contribution of component yarn in conductive hybrid yarn	109
4.18		Tensile strength and Flexural rigidity of hybrid yarn laminates	111
4.19		Dielectric strength of laminates	112
4.20		Resistivity of laminates ($\times 10^{12}$)	113
4.21	(a)	Hybrid conductive yarn (GC ₂ P ₂) P ₁	114
	(b)	SEM of hybrid yarn laminate	115
5.1	(a)	Schematic Diagram of Commingling Machine Set Up	119
	(b)	Nozzle Attachment and Control unit for Commingling Set up	120
5.2		Design specifications of guide brackets	121
	(a)	Angle bracket	
	(b)	Sliding bracket	
5.3		Various design aspects of mingling jet	122
	(a)	Pre-opening jet	
	(b)	Mingling jet	
5.4		Schematic diagram showing yarn of passage with glass and one polypropylene yarn passing through pre-opening (P ₁)	124
5.5		Schematic diagram showing yarn of passage with only glass yarn passing through pre-opening jet (P ₂)	125
5.6		Schematic diagram showing yarn passage with glass yarn and two polypropylene yarns passing through only mingling jet (P ₃)	126
5.7	(a)	Effect of air pressure and take-up speed on tenacity of hybrid yarn(Passage 1)	130
	(b)	Effect of air pressure and take-up speed on tenacity of hybrid yarn(Passage 2)	131
	(c)	Effect of yarn passage on tenacity of hybrid yarn	131

5.8	(a)	Effect of air pressure and take-up speed on modulus of hybrid yarn(Passage 1)	132
	(b)	Effect of air pressure and take-up speed on modulus of hybrid yarn(Passage 2)	133
	(c)	Effect of yarn path on modulus of hybrid yarn	133
5.9	(a)	Effect of air pressure and take-up speed on nip frequency of hybrid yarn(Passage 1)	135
	(b)	Effect of air pressure and take-up speed on nip frequency of hybrid yarn (Passage 2)	136
	(c)	Effect of yarn path on nip frequency of hybrid yarn	136
5.10	(a)	Effect of air pressure and take-up speed on nip stability of hybrid yarn (Passage 1)	137
	(b)	Effect of air pressure and take-up speed on nip stability of hybrid yarn (Passage 2)	137
	(c)	Effect of yarn path on nip stability of hybrid yarn	138
5.11	(a)	Effect of pressure and take-up speed on nip length of hybrid yarn (Passage 1)	138
	(b)	Effect of pressure and take-up speed on nip length of hybrid yarn (Passage 2)	139
	(c)	Effect of yarn path on nip length of hybrid yarn	139
5.12	(a)	SEM of hybrid yarn: Passage 1(100 m/min, 6 bar)	140
	(b)	SEM of hybrid yarn: Passage 3(50 m/min, 6 bar)	140
	(c)	SEM of hybrid yarn: Passage 2(50 m/min, 6 bar)	141
	(d)	SEM of hybrid yarn: Passage 1(50 m/min, 6 bar)	141
	(e)	SEM of hybrid yarn: Passage 2(50 m/min, 6 bar)	141
5.13	(a)	Schematic diagram of commingling machine	146
	(b)	Details of driving unit	147
	(c)	Commingling machine with hollow spindle unit	148
5.14	(a)	Frame work	149
	(b)	Assembling	150
	(c)	Inverter drive	151
	(d)	Final finishing	152

	(e)	Attachments	153
6.1		Passage of yarn through commingling	160
6.2		Ceramic jet with circular cross section from Himson	162
6.3		Metallic jet with semi circular cross section from Fiberguide	162
6.4	(a)	Effect of air pressure on hybrid yarn linear density at 0% overfeed	164
	(b)	Effect of air pressure on hybrid yarn linear density at 1% overfeed	165
	(c)	Effect of air pressure on hybrid yarn linear density at 2% overfeed	165
6.5	(a)	Effect of air pressure on hybrid yarn tenacity at 0% overfeed	166
	(b)	Effect of air pressure on hybrid yarn tenacity at 1% overfeed	166
	(c)	Effect of air pressure on hybrid yarn tenacity at 2% overfeed	167
6.6	(a)	Effect of air pressure on hybrid yarn extension at 0% overfeed	167
	(b)	Effect of air pressure on hybrid yarn extension at 1% overfeed	167
	(c)	Effect of air pressure on hybrid yarn extension at 2% overfeed	168
6.7	(a)	Effect of air pressure on nip frequency of hybrid yarn at 0% overfeed	168
	(b)	Effect of air pressure on nip frequency of hybrid yarn at 1% overfeed	169
	(c)	Effect of air pressure on nip frequency of hybrid yarn at 2% overfeed	169
6.8	(a)	Effect of air pressure on nip stability of hybrid yarn at 0% overfeed	170

	(b)	Effect of air pressure on nip stability of hybrid yarn at 1% overfeed	170
	(c)	Effect of air pressure on nip stability of hybrid yarn at 2% overfeed	171
6.9	(a)	Effect of air pressure on nip regularity of hybrid yarn at 0% overfeed	172
	(b)	Effect of air pressure on nip regularity of hybrid yarn at 1% overfeed	172
	(c)	Effect of air pressure on nip regularity of hybrid yarn at 2% overfeed	172
6.10		SEM of Glass/Polypropylene hybrid yarn at two different nozzle	173
6.11	(a)	Various commingled hybrid yarn linear density with different Glass:Polypropylene content	174
	(b)	Various commingled hybrid yarn tenacity at different Glass:Polypropylene content	175
	(c)	Various commingled hybrid yarn extension at different Glass:Polypropylene content	175
	(d)	Various commingled hybrid yarn modulus at different Glass:Polypropylene content	176
	(e)	Various commingled hybrid yarn characteristics at different Glass:Polypropylene content	176
6.12		SEM of hybrid yarn at different Glass:Polypropylene content	177
7.1	(a)	Contour plots of hybrid yarn linear density at different processing parameters	187
	(b)	Surface plots of hybrid yarn linear density at different processing parameters	188
	(c)	Residual plots for linear density as response	188
7.2	(a)	Contour plots of hybrid yarn tenacity at different processing parameter	189
	(b)	Surface plots of hybrid yarn tenacity at different	190

	processing parameter	
	(c) Residual plots for tenacity as response	190
7.3	(a) Contour plots of hybrid yarn extension at different processing parameter	191
	(b) Surface plots of hybrid yarn extension at different processing parameter	192
	(c) Residual plots for extension as response	192
7.4	(a) Contour plots of hybrid yarn nip frequency at different processing parameter	193
	(b) Surface plots of hybrid yarn nip frequency at different processing parameter	194
	(c) Residual plots for t nip frequency as response	194
7.5	(a) Contour plots of hybrid yarn nip stability at different processing parameter	195
	(b) Surface plots of hybrid yarn nip stability at different processing parameter	196
	(c) Residual plots for t nip stability as response	196
7.6	(a) Contour plots of hybrid yarn nip regularity at different processing parameter	197
	(b) Surface plots of hybrid yarn nip regularity at different processing parameter	198
	(c) Residual plots for t nip regularity as response	198
7.7	Various commingled hybrid yarn cross section of sample (S ₁ -S ₁₅)	199-201
	(a) S ₁ (5 bar, 0%, 75 m/min)	
	(b) S ₂ (7 bar, 0%, 75 m/min)	
	(c) S ₃ (5 bar, 2%, 75 m/min)	
	(d) S ₄ (7 bar, 2%, 75 m/min)	
	(e) S ₅ (5 bar, 1%, 50 m/min)	
	(f) S ₆ (7 bar, 1%, 50 m/min)	
	(g) S ₇ (5 bar, 1%, 100 m/min)	
	(h) S ₈ (5 bar, 1%, 100 m/min)	

	(i)	S ₉ (6 bar, 0%, 50 m/min)	
	(j)	S ₁₀ (6 bar, 2%, 50 m/min)	
	(k)	S ₁₁ (6 bar, 0%, 100 m/min)	
	(l)	S ₁₂ (6 bar, 2%, 100 m/min)	
	(m)	S ₁₃ (6 bar, 1%, 75 m/min)	
	(n)	S ₁₄ (6 bar, 1%, 75 m/min)	
	(o)	S ₁₅ (6 bar, 1%, 75 m/min)	
7.8		Friction Spun hybrid yarn	203
7.9		Hollow spindle wrapped hybrid yarn	204
7.10		Commingled hybrid yarn	204
7.11		Hybrid wrapping yarn with Commingled core	204
7.12	(a)	Knitted preforms made from hybrid wrapping yarn with commingled core	205
	(b)	Laminates made from hybrid wrapping yarn with commingled core	205