

List of Figures and Tables.

Page No.

Chapter 1: Introduction

- 12 Figure 1.1 Fringed miscella concept of polymer morphology.
15 Figure 1.2 Models proposed for chain folding in single crystals of polymers.
17 Figure 1.3 Model representations of the amorphous state
(a) interpenetrating coils
(b) and (c) honeycomb and meander model
(d) folded chain fringed micellar grains
(e) fringed micellar domain structure
19 Figure 1.4 (a) Cross-Sectional view of the structure of semi-crystalline polymers.
19 Figure 1.4 (b) View from parallel to the machine drawing plane of the structure of semi-crystalline polymers.
40 Figure 1.5 Energy partitioning in SRIM
45 Figure 1.6 Variation of stopping power (dE/dX) as a function of velocity of the particle.
49 Figure 1.7 Artist's rendition of ion track which shows physical core
57 Figure 1.8 Various functional chemical entities created by irradiation.

Chapter 2: Instrumentation and Techniques

- 73 Figure-2.1 A Schematic diagram showing the basic principle of acceleration in Pelletron.
74 Figure-2.2 A Schematic diagram of the accelerator facilities at NSC
77 Figure-2.3 Schematic diagram of the NSC multi-cathode ion source.
92 Figure 2.4 Schematic diagram of an optical absorption experiment.
92 Figure 2.5 The basic components of an interferometer.
95 Figure 2.6 Construction of compound microscope.
98 Figure 2.7 Block diagram of a scanning electron microscope.
104 Figure 2.8 Block diagram of Instron Tensile Tester.
107 Figure 2.9 Diagram showing principle of TGA.

Chapter 3: Experimental.

- 124 Table 3.1 Typical Properties of polymers used in the present work.
127 Figure 3.1 Picture of Two roll mill.
129 Table 3.2: Thickness of the polymers.
130 Table 3.3 Details of the irradiation of the polymers.
137 Figure 3.2 FTIR Spectroscopy set up.

- 138 Figure 3.3 Experimental set up to measure electrical properties.
 138 Figure 3.4 Sample Holder to measure electrical properties.

- 140 Figure 3.5 Hardness Measurement Instrument

Chapter 4: Results and Discussions

- 149 Figure 4.1 FTIR spectra of pristine and irradiated PP samples.
 150 Figure 4.2 Plot of log Resistivity v/s log Frequency at different Temperature ($^{\circ}\text{C}$), keeping fluence constant.
 151 Figure 4.3 Plot of log Resistivity v/s log Frequency at different fluence keeping temperature constant.
 152 Figure 4.4 Plot of Conductivity v/s log frequency for pristine and irradiated PP samples at ambient temperature.
 154 Figure 4.5 Plot of dissipation factor ($\tan\delta$) v/s temperature for pristine and irradiated PP samples at 10kHz frequency.
 154 Figure 4.6 Plot of dissipation factor ($\tan \delta$) v/s Temperature ($^{\circ}\text{C}$) at different frequency.
 155 Figure 4.7 Plot of $\tan \delta$ v/s log Frequency at different temperature, keeping fluence constant.
 156 Figure 4.8 Plot of dissipation factor ($\tan\delta$) v/s log frequency at different fluence at ambient temperature.
 157 Figure 4.9 Plot of Dielectric Constant v/s Log Frequency at different fluences.
 158 Figure 4.10 Plot of Dielectric Constant v/s Temperature($^{\circ}\text{C}$) at different fluences.
 159 Figure 4.11 TGA thermograms of pristine and irradiated PP
 160 Table 4.1 Data derived from TGA thermogram of pristine and irradiated PP denoting their thermal decomposition behaviour.
 166 Figure 4.12 FTIR spectra of Pristine and irradiated PET samples.
 167 Figure 4.13 Plot of log Resistivity v/s log Frequency at different temperature ($^{\circ}\text{C}$), keeping fluence constant.
 168 Figure 4.14 Plot of log Resistivity v/s log Frequency at different fluence keeping temperature constant.
 169 Figure 4.15 Plot of Conductivity v/s log frequency for pristine and irradiated PET samples at ambient temperature.
 171 Figure 4.16 Plot of dissipation factor ($\tan \delta$) v/s temperature ($^{\circ}\text{C}$) for pristine and irradiated PET samples at 10 kHz frequency.
 171 Figure 4.17 Plot of dissipation factor ($\tan \delta$) v/s Temperature ($^{\circ}\text{C}$) at different Frequency keeping fluence constant.
 172 Figure 4.18 Plot of $\tan \delta$ v/s log Frequency at different temperature ($^{\circ}\text{C}$), keeping fluence constant.
 173 Figure 4.19 Plot of dissipation factor ($\tan \delta$) v/s log Frequency at different fluence at ambient temperature .

174	Figure 4.20	Plot of Dielectric Constant v/s log Frequency at different fluences.
175	Figure 4.21	Plot of Dielectric Constant v/s Temperature ($^{\circ}\text{C}$) at different fluences.
176	Figure 4.22	TGA thermograms of pristine and irradiated PET.
177	Table 4.2	Data derived from TGA thermogram of pristine and irradiated PET denoting their thermal decomposition behaviour.
178	Figure 4.23	Plot of Hardness v/s Applied load on PET samples irradiated with different fluences.
178	Figure 4.24	Plot of Hardness v/s fluence of PET samples.
184	Figure 4.25 (a)	Un-Irradiated Kapton Film.
184	Figure 4.25(b)	Kapton Film irradiated with fluence of 5.2×10^{13} ions/cm ²
184	Figure 4.25(c)	Optical Micrographs of Implanted Kapton Film with a fluence of 10.4×10^{13} ions/cm ² .
185	Figure 4.26(a)	Plot of SEM Pictures of irradiated Kapton (fluence 5.2×10^{13} ions/cm ²).
185	Figure 4.26(b)	Plot of SEM Pictures of irradiated Kapton (fluence 1.0×10^{14} ions/cm ²).
185	Figure 4.26(c)	Plot of SEM Pictures of irradiated Kapton (fluence 1.0×10^{14} ions/cm ²).
187	Figure 4.27	Plot of Hardness v/s load applied to Pristine and irradiated PI samples.
189	Figure 4.28	FTIR Spectra of Pristine and irradiated Kapton films.
192	Figure 4.29	FTIR spectra of pristine and irradiated PVC + PET samples.
194	Figure 4.30	Plot of log Resistivity v/s log Frequency at different Temperatures ($^{\circ}\text{C}$), keeping fluence (1.3×10^{14} ions/cm ²) constant.
194	Figure 4.31	Plot of log Resistivity v/s log Frequency at different fluence keeping temperature constant.
195	Figure 4.32	Plot of Conductivity v/s log Frequency for pristine and irradiated PVC + PET samples at ambient temperature.
197	Figure 4.33	Plot of dissipation factor ($\tan \delta$) v/s temperature ($^{\circ}\text{C}$) for pristine and irradiated PET samples at 10kHz frequency.
197	Figure 4.34	Plot of dissipation factor ($\tan \delta$) v/s Temperature($^{\circ}\text{C}$) at different Frequency keeping fluence (1.5×10^{14} ions/cm ²) constant.
198	Figure 4.35	Plot of $\tan \delta$ v/s log Frequency at different emperature ($^{\circ}\text{C}$) keeping fluence (1.5×10^{14} ions/cm ²) constant.
199	Figure 4.36	Plot of dissipation factor ($\tan \delta$) v/s log Frequency at different fluence at ambient temperature.
200	Figure 4.37	Plot of Dielectric constant v/s log Frequency at different fluences.
201	Figure 4.38	Plot of Dielectric constant v/s Temperature($^{\circ}\text{C}$) at different

		fluences.
202	Figure 4.39	Plot of thermogram of pristine and irradiated PVC + PET .
203	Table 4.3	Data derived from TGA thermogram of pristine and irradiated PVC + PET denoting their thermal decomposition behaviour.
205	Figure 4.40	Schematic diagram of experimental set up for the study of gas sensor.
207	Figure 4.41	Plot of surface resistivity as a function of H ₂ gas concentration at various fluences.
208	Figure 4.42	Plot of sensitivity factor as a function of H ₂ gas concentration at various fluences.
208	Figure 4.43	Plot of response and recovery times of irradiated polymers as a function of fluence for 500ppm of H ₂ gas.
213	Table 4.4	Sample's specification with instrument settings.
213	Figure 4.44	Load – elongation curves.
214	Table 4.5	Mechanical properties of the samples.
215	Figure 4.45	FTIR spectra of pure and blended pristine and irradiated samples.
217	Figure 4.46	TGA thermograms of pristine PVC, EVA and their blends.
219	Table 4.6	Thermal decomposition temperatures at different zones for PVC, EVA and their blend.
219	Figure 4.47	TGA thermograms of pristine PVC, EVA and their blends irradiated at 10 ¹⁴ ions/cm ² .
220	Table 4.7	Thermal decomposition temperature of pristine and irradiated samples.