LIST OF TABLES

Table No. Title

- 3.1 Loss Coefficients for Tee, Elbow and valves in laminar flow
- 5.1 Calibration of rotameter with indifferent electrolyte 0.5
 NaOH, Temperature 29 32° C.
- 5.2 Calibration of flow rate vs polarising current, Temperature 32 - 34° C
- 6.1 Flow profile for Experimental Collector, Asymmetric Flow, $Q_{in} = 76.4388 E-6 m^{-3}s^{-1}, T = 32^{\circ} C$
- 6.2 Flow profile for Experimental Collector, Asymmetric Flow, $Q_{in} = 58.7388 E-6 m^{-3}s^{-1}, T = 32^{\circ} C$
- 6.3 Flow profile for Experimental Collector, Asymmetric Flow, Qin = 41.039 E-6 m⁻³s⁻¹, T = 32° C
- 6.4 Flow profile for Experimental Collector, Asymmetric Flow, Qin = 23.339 E-6 m⁻³s⁻¹, T = 32° C

í

- 6.5 Flow profile for Experimental Collector, Symmetric Flow, $Q_{in} = 76.4388 E-6 m^{-3}s^{-1}, T = 32^{\circ} C$
- 6.6 Flow profile for Experimental Collector, Symmetric Flow, $Q_{in} = 58.7388 \text{ E-6 m}^{-3}\text{s}^{-1}, T = 32^{\circ} \text{ C}$
- 6.7 Flow profile for Experimental Collector, Symmetric Flow, Qin = 41.039 E-6 m⁻³s⁻¹, T = 32° C
- 6.8 Flow profile for Experimental Collector, Symmetric Flow, Qin = 23.339 E-6 m⁻³s⁻¹, T = 32° C
- 6.9 Non-uniformity Factors for the experimental collector module
- 6.10 Details of collector geometry
- 6.11 Pressure drop, non-uniformity factor and collector
 efficiency for 5-module collector array, Asymmetric,
 G = 0.0075 kgs^{-1m-2}. Riser diameter = 9 mm.
- 6.12 Pressure drop, non-uniformity factor and collector efficiency for 5-module collector array, Symmetric,
 G = 0.0075 kgs⁻¹m⁻². Riser diameter = 9 mm.
- 6.13 Pressure drop for 5-module collector array, Asymmetric and Symmetric, G = 0.0075 kgs⁻¹m⁻². Manifold diameter = 25 mm.

6.14 Performance of 10 module collector array.