

LIST OF FIGURES

Fig. No.	Title
1.1	Solar collector Geometries
1.2	Array Flow Configurations in Solar Collector Array with collectors in parallel
3.1	Flow at Tee Junction and Numbering Nomenclature.
3.2	Loss Coefficients for sharp edged 90° dividing 'T'
3.3	Loss Coefficients for sharp edged 90° combining 'T'
3.4	Effect of Reynold Number on Loss Coefficients for sharp bend
3.5	Collector Hydraulic and Equivalent Resistance Network for Asymmetric Flow
3.6	Collector Hydraulic and Equivalent Resistance Network for Symmetric Flow

- 3.7 Circuit Matrix for Asymmetric and Symmetric Flow
- 3.8 Modifications in the Network during Flow Reversal in flow ratio and circuit matrix in Asymmetric flow
- 3.9 Modification in resistance network due to flow reversal in Asymmetric flow
- 3.10 Flow Chart for solving Collector Hydraulic Network (Asymmetric and Symmetric)
- 5.1 Experimental Test Setup (Electrochemical)-Hydraulic Circuit
- 5.2 Calibration Test Setup (Electrochemical)
- 5.3 Collector Test Setup
- 5.4 Electrical Circuit for Electrochemical Flow Measurement
- 5.5 Rotameter Calibration
- 5.6 Polarisation Curves at different flow rates of 0.5N NaOH, 0.01 N $K_4 Fe(CN)_6$ and 0.01 N $K_3 Fe(CN)_6$
- 5.7 Polarising current vs flow rate of electrolyte

- 6.1 Flow Profile for Exp Module, Asymmetric, $G=0.0312 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.2 Flow Profile for Exp Module, Asymmetric, $G=0.0239 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.3 Flow Profile for Exp Module, Asymmetric, $G=0.0167 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.4 Flow Profile for Exp Module, Asymmetric, $G=0.0095 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.4a Comparative Flow for Exp Module, Asymmetric, Effect of Flow Rate
- 6.5 Flow Profile for Exp Module, Symmetric, $G=0.0312 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.6 Flow Profile for Exp Module, Symmetric, $G=0.0239 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.7 Flow Profile for Exp Module, Symmetric, $G=0.0167 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.8 Flow Profile for Exp Module, Symmetric, $G=0.0095 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.8a Comparative Flow for Exp Module, Symmetric, Effect of Flow Rate
- 6.8b Comparison of Present Model with McPhedran (1983) for Evacuated Solar Collector
- 6.9a-d Pressure Profile for Exp Module, Asymmetric, $G = 0.0312, 0.0239, 0.0167 \text{ and } 0.0095 \text{ kg s}^{-1}\text{m}^{-2}$

- 6.10a-d Pressure Profile for Exp Module, Symmetric, $G = 0.0312, 0.0239, 0.0167$ and $0.0095 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.11a-b Flow Profile for 5 Module, $a=0.05$, Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.12a-b Flow Profile for 5 Module, $a=0.10$, Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.13a-b Flow Profile for 5 Module, $a=0.20$, Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.13c-d Flow Profile for 3 Module, $a=0.20$, Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.14a-b Flow Profile for 5 Module, $a=0.40$, Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.15 Comparative Flow for 5 Modules, Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.15a-f Flow Profile for 5 Modules, $a=0.05-0.20$, Asymmetric, $G=0.0075 \text{ kg s}^{-1}\text{m}^{-2}$ (Fixed Manifold Diameter)
- 6.16a-b Flow Profile for 5 Module, $a=0.20$, Asymmetric, $G = 0.0050 \text{ kg s}^{-1}\text{m}^{-2}$

- 6.16c Pressure Profile for 5 Module, $a=0.20$, Asymmetric, $G = 0.0050 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.16d-e Flow Profile for 5 Module, $a=0.20$, Asymmetric, $G = 0.0150 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.16f Pressure Profile for 5 Module, $a=0.20$, Asymmetric, $G = 0.0150 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.16g Comparative Flow for 5 Module, $a=0.20$, Asymmetric, Effect of Flow Rate
- 6.17a-c Pressure Profile for 5 Module, $a=0.05, 0.10$ and 0.20 , Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.17d Pressure Profile for 3 Module, $a=0.20$, Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.17e-g Pressure Profile for 5 Module, $a=0.05, 0.10$ and 0.20 , Asymmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.18a-b Flow Profile for 5 Module, $a=0.05$, Symmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.19a-b Flow Profile for 5 Module, $a=0.10$, Symmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$

- 6.20a-b Flow Profile for 5 Module, $a=0.20$, Symmetric, $G = 0.0075$
 $\text{kg s}^{-1}\text{m}^{-2}$
- 6.21a-b. Flow Profile for 5 Module, $a=0.40$, Symmetric, $G = 0.0075$
 $\text{kg s}^{-1}\text{m}^{-2}$
- 6.22 Comparative Flow for 5 Modules, Symmetric, $G = 0.0075$
 $\text{kg s}^{-1}\text{m}^{-2}$, Effect of area Ratio
- 6.23a-b Flow Profile for 5 Module, $a=0.20$, Symmetric, $G = 0.0050$
 $\text{kg s}^{-1}\text{m}^{-2}$
- 6.23c Pressure Profile for 5 Module, $a=0.20$, Symmetric, $G =$
 $0.0050 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.23d-e Flow Profile for 5 Module, $a=0.20$, Symmetric, $G = 0.0150$
 $\text{kg s}^{-1}\text{m}^{-2}$
- 6.23f Pressure Profile for 5 Module, $a=0.20$, Symmetric, $G =$
 $0.0150 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.23g Comparative Flow for 5 Modules, Symmetric, $a=0.20$, Effect
of Flow Rate
- 6.24a-c Pressure Profile for 5 Module, $a=0.05, 0.10$ and 0.20 ,
Symmetric, $G = 0.0075 \text{ kg s}^{-1}\text{m}^{-2}$

- 6.25 Flow Profile for 5 Module, $a=0.20$, Asymmetric, $G = 0.0075$
 $\text{kg s}^{-1}\text{m}^{-2}$ (Collector spacing = 0.30 m)
- 6.26 Pressure Profile for 5 Module, $a=0.20$, Asymmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$ (Collector spacing = 0.30 m)
- 6.27 Flow Profile for 5 Module, $a=0.05$, Asymmetric, $G = 0.0075$
 $\text{kg s}^{-1}\text{m}^{-2}$ (Riser spacing = 0.07 m)
- 6.28 Pressure Profile for 5 Module, $a=0.05$, Asymmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$ (Riser spacing = 0.07 m)
- 6.29 Flow Profile for 5 Module, $a=0.20$, Asymmetric, $G = 0.0075$
 $\text{kg s}^{-1}\text{m}^{-2}$ (Riser spacing = 0.07 m)
- 6.30 Pressure Profile for 5 Module, $a=0.20$, Asymmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$ (Riser spacing = 0.07 m)
- 6.31-32 Flow Profile for 10 Module, $a=0.05$, Asymmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.33 Pressure Profile for 10 Module, $a=0.05$, Asymmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$
- 6.34-35 Flow Profile for 10 Module, $a=0.10$, Asymmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$

6.36 Pressure Profile for 10 Module, $a=0.10$, Asymmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$

6.37-38. Flow Profile for 10 Module, $a=0.05$, Symmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$

6.39 Pressure Profile for 10 Module, $a=0.05$, Symmetric, $G =$
 $0.0075 \text{ kg s}^{-1}\text{m}^{-2}$