LIST OF TABLES :

1.1 Consumption of petroleum products in India	· 1
1.2 Lube-base stock production capacily in India	2
2.3 Lube-base stock potential of few crudes	4
1.4 Operating parameters of MEK dewaxing	13
1.5 Effect of solvent dilution in filteration rate	17
1.6 Role of hydrocarbon type in flow properties of	19
lube oil	
2.1 Hydrocarbon assimilating microorganisms	¹ 34
2.2 Summary of production capacity of SCP from	44
hydrocarbon	* .
2.3 Growth parameters of yeasts on hydrocarbons	46
2.4 Proximate composition of Bacteria and yeast used	for 54
SCP production	
2.5 Amino acid profile of yeast and other selected	. 56
stuffs	
2.6 Recomended standards for SCP from hydrocarbons	60
2.7 Physical properties of the vacuum distillates	63
3.1.2 Composition of medium	64
3.1.4 Fermentor dimensions	68
4.1.1 Screening of yeast strains	8,5
4.2.1 Effect of temperature on so. growth rate	97
4.2.2 Determination of activation energy	. 98
4.2.3 Effect of temperature on yield and pour pt.	99
4.2.4 Effect of pH on sp. growth rate	105
4.2.6 Effect of oil conc. on dewaxing	, 110
4.3.1 Dewaxing of vacuum distillates by batch operati	on 118
4.3.2 Yield of biomass on vacuum distillate	115
4.3.3 Yield of dewaxed oil	120
4.3.4 Dewaxing by semicontinuous operation	122
4.3.5 Batch and semi-continuous operation	122
4.4.2 Oxygen transfer capacity as different aeration	134
rate	•
4.4.3 K a values at different aeration rate	134
4.4.4 Impellers Reynolds number of fermentors	138
4.4.5 Calculation of net nower per unit volume (P/V)	. 1'4.1

	4.4.6	Effect of P/V on sp. growth rate	142
	4.4.7	Comparison of scale up data	151
	4.5.1	Effect of solvent composition on oil recovery	157
	4.5.2	Effect of solvent / emulsion ratio on recovery	158
1	4.5.3	Composition of different streams in the leaching	160
		operation	
	4.6.1	Properties of the microbial and solvent dewaxed oil	167
	4.6.2	Changes of hydrocarbon composition	168
	4.6.3	Changes in individual hydrocarbon types in sample	169
		'A' due to microbial dewaxing	
	4.6.4	Composition of SCP from different petroleum	170
		fractions	