

REFERENCES

- Acharjee, D. K., Bhat, P. A., Mitra, A. K., and Roy, A. N., (1975), Studies on momentum transfer in vertical liquid jet ejectors, *Indian Journal of Technology*, 13, 205-210.
- Agrawal, K. S. (1999), *Studies on Ejector*, M.E. Dissertation, The Maharaja Sayajirao University of Baroda, Vadodara.
- Ahari, J. S., Forsat, K., Djenab, M. H., Mohammadbigy, K., Vahidi, M., and Shafiei, Z., (2008), Predictive model of hydrogen sulfide absorption by chelate solution in a venturi scrubber, *Chemical Engineering Technology*, 31(10), 1481-86.
- Akafuah Nelson Kudzo, (2009), *Visualization and characterization of ultrasonic cavitating atomizer and other automotive paint sprayers using infrared thermography*, A dissertation submitted in partial fulfillment of the requirements for the degree of Doctor of Philosophy in the College of Engineering at the University of Kentucky.
- Alvarez-Fuster, C., Midoux, N., Laurent, A., and Charpentier, J. C., (1981), Chemical kinetics of the reaction of CO₂ with amines in pseudo m-nth order conditions in polar and viscous organic solutions, *Chemical Engineering Science*, 36, 1513-1518.
- Alvarez-Fuster, C., Midoux, N., Laurent, A., and Charpentier, J. C., (1980), Chemical kinetics of the reaction of carbon dioxide with amines in pseudo m-nth order conditions in aqueous and organic solutions, *Chemical Engineering Science*, 35, 1717-1723.
- Ananthanarayanan, N. V., and Viswanathan, S., (1999), Predicting the liquid flux distribution and collection efficiency in cylindrical venturi scrubbers, *Ind. Eng. Chem. Res.*, 38, 223-232.
- Ananthanarayanan, N. V., and Viswanathan, S. (1998), Estimating Maximum Removal Efficiency in Venturi Scrubbers, *AIChE Journal*, 44(11), 2539-2560.
- Appusamy, A., Iyyaswamy, R. and Murugesan T., (2008), Gas holdup and energy dissipation in liquid-gas ejectors, *Journal of Chemical Technology and Biotechnology*, 83, 1064-1071.
- Asai, S., Yasuhiro, K., and Hiroaki, Y., (1986), Mass transfer with chemical reaction in two phases, *Ind. Eng. Chem. Fundam*, 25, 3452-454.

Ashour, S. S., Edward, R. B., and Orville, C., (1996), Absorption of chlorine into aqueous bicarbonate solutions and aqueous hydroxide solutions, *AIChE Journal*, 42(A3), 671-682.

Atay I., Gordon, L., and Richard, T., (1987), Fluid flow and gas absorption in an ejector venturi scrubber, *Environmental Progress*, 6 (3), 198-203.

Atay, I., (1986), Fluid flow and gas absorption, in an ejector venturi scrubber, *Dissertationly for the degree of Doctor of Engineering Science*, New Jersey Institute of Technology.

Azad, M., and Sultana, R. A., (2006), Numerical model for bubble size distribution in turbulent gas-liquid dispersion, *Journal of Chemical Engineering, IEB.*, 24(1), 25-34.

Azzopardi, B. J., Teixeira, S., Govan, A., and Bott, T., (1991), An improved model for pressure drop in venturi scrubbers, *Trans. Inst. Chem. Eng.*, B 69, 55-64.

Bailer Frank Oliver, (2001), *Mass Transfer Characteristics of a Novel Gas-Liquid Contactor, The Advanced Buss Loop Reactor*, A Dissertation submitted to the Swiss Federal Institute of Technology for degree of Doctor of Technical Sciences, Zurich.

Bakshi, B.R., Jiang, P. and Fan, L. S., (1995), Analysis of flow in gas-liquid bubble columns using multi-resolution methods, *Proceedings of the 2nd International Conference on Gas-Liquid-Solid Reactor Engineering, Cambridge, U.K.*, 27-29 March, pp. A1-A8.

Balamurugan, S., Gaikar, V. G., and Patwardhan, A. W., (2008), Effect of ejector configuration on hydrodynamic characteristics of gas-liquid ejectors, *Chemical Engineering Science*, 63, 721-731.

Balamurugan, S., Lad, M. D., Gaikar, V. G., and Patwardhan, A. W., (2007), Effect of geometry on mass transfer characteristics of ejectors, *Ind. Eng. Chem. Res.*, 46, 8505-8517

Bandyopadhyay Amitava and Biswas Manindra, N., (2006), Prediction of the removal efficiency of a novel two-stage hybrid scrubber for flue gas desulfurization, *Chem. Eng. Technol.*, 29, 1, 130-145.

Bandyopadhyay Amitava and Biswas Manindra, N., (2007a), SO₂ scrubbing in a tapered bubble column scrubber, *Chemical Engineering Communications*, 193(12), 1562-1580.

Bandyopadhyay Amitava and Biswas Manindra, N., (2007b), Spray scrubbing of particulates with a critical flow atomizer, *Chem. Eng. Technol.* 30, 12, 1674-1685.

Barreras, F., Amaveda, H., Lozano, A., (2002), Transient high-frequency ultrasonic water atomization, *Experiments in Fluids*, 33, 405–413.

Beg, S.A., and Taheri, M., (1974), Gas absorption studies in butterfly valve scrubber, *Atmos. Environ.*, 8, 947–955.

Beltran, F. J., Fernandez, L. A., Alvarez P., and Rodriguez E., (1998), Comparison of kinetic data from film and Danckwerts theories, *Ozone Science and Engineering*, 20, 403-420.

Ben Ebrahim, A., Prevost, M., and Bugarel, R., (1984), Momentum transfer in a vertical down flow liquid jet ejector: case of self aspiration and emulsion flow, *International Journal of Multiphase Flow*, 10 (1), 79-94.

Bergwerk, W., (1959), Flow pattern in diesel nozzle spray holes, *Proceedings of the Institution of Mechanical Engineers*, 173, 655.

Bhat, P.A., Mitra, A.K., Roy, A.N., (1972), Momentum transfer in a horizontal liquid jet ejector, *Canadian Journal of Chemical Engineering*, 50, 313-317.

Bhatt Nirav, Amrhein Michael, and Bonvin Dominique, (2007), Incremental Identification of Reaction and Mass Transfer Kinetics Using the Concept of Extents, *Ind. Eng. Chem. Res.*, A-O.

Bhatt Nirav, Amrhein Michael, and Bonvin Dominique, (2010), Extents of Reaction, Mass Transfer and Flow for Gas-Liquid Reaction Systems, *Ind. Eng. Chem. Res.*, 49, 7704–7717.

Bhutada, S.R., and Pangarkar, V.G., (1987), Gas induction and hold-up characteristics of liquid jet loop reactors, *Chemical Engineering Communications* 61, 239-261.

Bin, A. K., (1993), Gas entrainment by plunging liquid jet, *Chem Eng Science*, 48, 3585–3630.

- Biswas, M. N., and Mitra, A. K., (1981), Momentum transfer in horizontal multi-jet liquid gas ejector, *Canadian Journal of Chemical Engineering*, 59, 634-637.
- Biswas, M. N., Mitra, A. K., and Roy, A. N., (1975), Studies on gas dispersion in a horizontal liquid jet ejector, *Second Symposium on Jet Pumps and Ejectors and Gas Lift Techniques Cambridge, England*, March 24-26, BHRA, E3-27-42.
- Biswas, M. N., Mitra, A. K., and Roy, A. N., (1977), Effective interfacial area in a liquid-jet induced horizontal gas-liquid pipeline contactor, *Indian Chemical Engineering*, XIX (2), 15-21.
- Black, D. L., McQuay, M. Q., and Bonin, M. P., (1996), Laser-based techniques for particle size measurement: a review of sizing methods and their industrial applications, *Progress in Energy Combustion Science*, 22, 267-306.
- Blenke, H., Bohner, K., and Vollmerhaus, E., (1963), Investigations into the calculation of jet pump performance, *Cheme Ingenieur Technik*, 35(3), 201-208.
- Boll, R. H., (1973), Particle collection and pressure drop in venturi scrubbers, *Ind. Eng. Chem. Fund.*, 12(1), 40-50.
- Boll, R. H., Flais, L. R., Maurer, P. W., and Thompson, W. L., (1974), Mean drop size in a full scale venturi scrubber via transmissometer, *J. Air Pollut. Control Assoc.*, 24(10), 934-938.
- Bonnington, S. T., (1956), Water jet ejectors, *BHRA Publication*, RR540.
- Bonnington, S. T., (1960), Water driven air ejectors, *BHRA Publication*, SP664.
- Bonnington, S. T., (1964), A guide to jet pump design, *British Chemical Engineering*, 9(3), 150-154.
- Bonnington, S. T., and King, A. L., (1972), Jet pumps and ejectors, a state of the art review and bibliography, *Published by BHRA Fluid Engineering, Cranfield, Bedford, England*.
- Botton, R., Cosserat, D., and Charpentier, J. C., (1987), *A new laboratory apparatus for the study of International Chemical Engineering*, 27(2), 143.

- Boyadzhiev Kh., (1964), On the optimal flow rate of liquids during chemisorptions in a venturi tube, *Int. Chem. Eng.*, 4 22–26.
- Brennen, C.E., (1995), *Cavitation and Bubble Dynamics*, Oxford University Press.
- Brian, P. L. T. and Beaverstock, M. C., (1965), Gas absorption accompanied by a two-step chemical reaction, *Chem. Eng. Sci*, 20, 47-56.
- Brian, P. L. T., Vivian, J.E., and Piazza, C., (1966), The effect of temperature on the ratio of absorption of chlorine in to water, *Chem. Eng. Sci*, 21, 551.
- Calvert, S., (1970), Venturi and other atomizing scrubbers efficiency and pressure drop, *AIChE Journal*, 16(3), 392-396.
- Cao, J., and Christensen, R. N., (2000), Analysis of moving boundary problem for bubble collapse in binary solutions, *Numerical Heat Transfer, Part A: Applications*, 38(7), 681-699.
- Castleman, R. A., (1931), Mechanism of atomization of liquids, *U.S. National Bureau of Standard Journal Research*, 6, 281.
- Cents, A., Bruijn, H. G., F. T. de., Brilman, D. W. F., and Versteeg, G. F., (2005), Validation of the Danckwerts-plot technique by simultaneous chemical absorption of CO₂ and physical desorption of O₂, *Chemical Engineering Science*, 60, 5809–5818.
- Ceylan, K., Altunbas, A., and Kelbaliyev, G., (2001), A new model for estimation of drag force in the flow of Newtonian fluids around rigid or deformable particles, *Powder Technology*, 119, 250–256.
- Chandrasekhar, S., (1961), The capillary instability of a liquid jet, *In Hydrodynamic and Hydromagnetic Stability*, Oxford, Oxford University Press, 537-542.
- Charpentier, J. C., (1976), Review paper- recent progress in two phase gas -liquid mass transfer in packed beds, *Chemical Engineering Journal*, 11, 161-181.
- Charpentier, J. C., (1982), What's new in absorption with chemical reaction?, *Trans. Institute of Chemical Engineers*, 60, 131.

- Chaves, H., Knapp, M., Kubitzek, A., Obermeier, F., and Schneider, T., (1991), Experimental study of cavitation in the nozzle hole of diesel injectors using transparent nozzles, *Society of Automotive Engineers*, Paper No. 950290, 645-657.
- Chehroudi, B., Onuma, Y., Chen, S., and Bracco, F., (1985), On the intact core of full-cone sprays, SAE, Paper No. 850126.
- Chigier, N., and Reitz, R. D., (1996), Regimes of jetbreakup and breakup mechanisms (physical aspects). In *Recent Advances in Spray Combustion: Spray Atomization and Drop Burning Phenomena*, 1, 109-35.
- Chilton, T. H., and Colburn, A. P., (1934), Mass transfer (absorption) coefficients prediction from data on heat transfer and fluid friction, *Ind. Eng. Chem.*, 2(11), 1183-1187.
- Ciborowski, J., and Bin, A., (1972b), Investigation of the aeration effect of plunging liquid jets. *Ini. Chem.*, (Polish), 2, 557-577.
- Connick, A. E. and Chia, Y. T. (1959), The hydrolysis of chlorine and its variation with temperature, *J. Am. Chem. Soc.*, 81, 1280.
- Cooney, D. O., (1985), Modeling venturi scrubber performance for H₂S removal from oil-shale retort gases, *Chemical Engineering Communications*, 35, (1-6), 315-338.
- Cooney, D. O., (1992) Simultaneous absorption of an acid gas (H₂S) and a basic gas (NH₃) in a scrubbing device, *Chemical Engineering Communications*, 114 (1), 103-116.
- Cooney, D. O., and Daniel P. O., (1987), Absorption of SO₂ and H₂S in small-scale venturi scrubbers, *Chemical Engineering Communications*, 51, 1-6.
- Cramers, P. H. M. R., and Beenackers, A. A. C. M., (2001), Influence of the ejector configuration, scale and the gas density on the mass transfer characteristics of gas-liquid ejectors, *Chemical Engineering Journal*, 82, 131-141.
- Cramers, P. H. M. R., Beenackers, A. A. C. M. and Van Dierendonck, L. L., (1992). Hydrodynamics and mass transfer characteristics of a loop-venturi reactor with a down flow liquid jet ejector, *Chem. Engg. Sci.*, 47, 3557-3564.
- Crane, L., Birch, S., and McCormack, P. D., (1964), The effect of mechanical vibration on the breakup of a cylindrical water jet in air, *British Journal of Applied Physics*, 15, 743-750.

Crowder, J. W., Wu, T. K. L., and Winkle, W. V., (1981), Modeling of venturi scrubber performance, *Environmental Technology Letters*, 2, 8, 337-346.

Crowder, J.W., Noll, K.E., and Davis, W.T., (1982), Modeling of venturi scrubber efficiency, *Atmospheric Environment*, 16 (8), pp. 2009-2013.

Cunningham, R. G., (1974a), Gas Compression with the Liquid Jet Pump, *ASME Publication, Journal of Fluids Engineering*, 203-217.

Cunningham, R. G., and Dopkin, R. J., (1974b), Jet breakup and mixing throat lengths for the liquid jet gas pump, *Transactions on ASME, Journal of Fluids Engineering*, 96, 216-226.

Danckwert, P. V., Kennedy, A. M., and Roberts, D., (1963), Kinetics of CO₂ absorption in alkaline solutions-II, *Chemical Engineering Science*, 18, 63-72.

Danckwerts, P. V. and Gillham, P. V., (1966), The design of gas absorbers, *Trans. Inst. Chern. Engrs.*, 44, T42-TS4.

Danckwerts, P. V., (1950a), Absorption by simultaneous diffusion and chemical reaction. *Trans. Faraday Society*, 46, 300.

Danckwerts, P. V., (1950b), Unsteady-state diffusion or heat conduction with moving boundary, *Trans. Faraday Society*, 46, 701.

Danckwerts, P. V., (1951), absorption by simultaneous diffusion and chemical reaction into particles of various shapes and into falling drops, *Trans. Faraday Society*, 47, 1014.

Danckwerts, P. V., (1967), Gas-absorption accompanied by first-order reaction: concentration of product, temperature-rise and depletion of reactant, *Chemical Engineering Science*, 22, 472-473.

Danckwerts, P. V., (1968), Gas absorption with instantaneous reaction, *Chemical Engineering Science*, 23, 1045-1051.

Danckwerts, P. V., (1970), *Gas-Liquid Reactions*, Ed. McGraw-Hill, New York.

Danckwerts, P. V., and Kennedy, A. M., (1958), The kinetics of absorption of carbon dioxide into neutral and alkaline solutions, *Chemical Engineering Science-Genie Chimique*, 8, (3/4), 201-215.

Danckwerts, P. V., and Kennedy, B.E., (1954), Kinetics of liquid-film process in gas absorption. part I : Models of the absorption process, *Transactions of the Institution Chemical Engineers*, 32, S101-S104.

Danckwerts, P.V., and Sharma, M.M., (1966), Absorption of carbon dioxide into solutions of alkalis and amines, *The Chemical Engineer*, CE, 244-280.

Das, S. K., and Biswas, M. N., (2006), Studies on ejector-venturi fume scrubber, *Chemical Engineering Journal*, 119, 153-160.

Dasappa, S., Paul, P. J., and Mukunda, H. J., (1993), Fluid dynamic studies on ejectors for thermal applications of gasifiers, *Proceedings of Forth National Meet on Biogass Gassification and Combution*, Mysure.

Davies, (1972), *Turbulence Phenomena*, Academic, New York.

Davis, G.S., Mitra, A.K., and Roy, A.N., (1967), Momentum transfer studies in ejectors, *Industrial and Engineering Chemistry Process Design and Development*, 6, 293-299.

Davis, W. J., (1963), The effect of the Froude number in estimating vertical 2-phase gas-liquid friction losses, *Brit. Chem. Eng.*, 8, 462-465.

Dehkordi Asghar Molaei and Chiya Savari, (2011), Determination of interfacial area and overall volumetric mass-transfer coefficient in a novel type of two impinging streams reactor by chemical method, *Ind. Eng. Chem. Res.*, 50, 6426-6435.

DeJuhasz, K. J., (1960), Spray Literature Abstracts, New York, *American Society of Mechanical Engineers*, 1, 2, 3, 4.

Dennis Gary A., (1966), A study of injector spray characteristics in simulated rocket combustion chamber including longitudinal mode pressure oscillation, *NASA*, Technical Report No 730.

Dierendonck, L. L., Zahradnik, J., and Linek V., (1998), Loop venturi reactorsa feasible alternative to stirred tank reactors?, *Ind. Eng. Chem. Res.*, 37, 734-738.

Dimiccoli, A., Serio, M., and Santacesaria, E., (2000), Mass transfer and kinetics in spray-tower-loop absorbers and reactors, *Ind. Eng. Chem. Res.*, 39, 4082-4093.

Dirix, C. A. M. C., and Wiele, K., (1990), Mass transfer in jet loop reactors, *Chemical Engineering Science*, 45(8), 2333-2340.

Doraiswamy, L. K., and Sharma, M. M., (1984), *Heterogeneous Reactions: Analysis, Examples, and Reactor Design, In Fluid-Fluid-Solid Reactions Volume-2*, John Wiley and Sons, New York.

Dutta, N. N., and Raghawan, K. V., (1987), Mass transfer and hydrodynamic characteristics of loop reactors with down flow liquid jet ejector, *Chemical Engineering Journal*, 36, 111-121.

Economopoulou Alexia, A., and Harrison Roy, M., (2007), Graphical analysis of the performance of venturi scrubbers for particle abatement, Part I : Rapid collection efficiency evaluation, *Aerosol Science and Technology*, 41, 51-62.

Elgozali, A., Linek, V., Fialova, M., Wein, O., and Zahradnik, J., (2002), Influence of viscosity and surface tension on performance of gas-liquid contactors with ejector type gas distributor, *Chemical Engineering Science*, 57, 2987-2994.

Engel, O. G., (1958), Fragmentations of water drops in the zone behind an air shock, *Journal of Research of the National Bureau of Standards*, 60, 245.

Eroglu, H., Chigier, N., and Farago Z., (1991), Coaxial atomizer liquid intact lengths, *Phys. Fluids*, A.3, 303-308.

Evans, G. M., Jameson, G. J., and Atkinson, E. W., (1992), Prediction of the bubble size generated by a plunging liquid jet bubble column, *Chemical Engineering Science*, 47, 3265-3272.

Faeth, G., (1990), Structure and atomization properties of dense turbulent sprays, *In 23rd International Symposium on Combustion, The Combustion Institute*, 1345-1352.

Faeth, G., (1995), Structure and breakup properties of sprays, *International Journal of Multiphase Flow*, 21, 99-127.

Faeth, G., (1999), Liquid atomization in multiphase flows : a review, *In 30th AIAA Fluid Dynamics Conference*, Paper Number 99, 3639.

Fernandez, R., (2001), *Calculation of injector characteristics using a commercial CFD code*, Thesis for Diploma, The Institute of Thermal Turbo machines and Power plants, University of Technology, Vienna.

Frago, Z., and Chigier, N., (1992), Morphological classification of disintegration of round liquid jet in a coaxial airstream, *Atomization and sprays*, 2, 137–152.

Frank Thomas, (2005), Advances in computational fluid dynamics (CFD) of 3-dimensional gas-liquid multiphase flows, *NAFEMS Seminar: Simulation of Complex Flows (CFD)*, Niedernhausen/Wiesbaden, Germany April 25 - 26.

Fraser, R. P., and Paul Eisenklam Norman, (1962), Drop formation from rapidly moving liquid sheets, *AIChE Journal*, 8(5), 672-680.

Gamisans, X., Sarra, M., and Lafuente, F.J., (2004), The role of the liquid film on the mass transfer in venturi-based scrubbers, *Trans IChemE, Part A*, 82(A3), 372-380.

Gamisansa, X., Sarra, M., and Lafuente, F. J., (2002), Gas pollutants removal in a single and two-stage ejector venturi scrubber, *Journal of Hazardous Materials*, B90, 251-266.

Gandhi Ankit, B., Gupta Prashant, P., Joshi Jyeshtharaj, B., Valadi K. Jayaraman, and Kulkarni Bhaskar, D., (2009), Development of unified correlations for volumetric mass-transfer coefficient and effective interfacial area in bubble column reactors for various gas-liquid systems using support vector regression, *Ind. Eng. Chem. Res.*, 48, 4216–4236.

Gelfand, B., (1996), Droplet breakup phenomena in flows with velocity lag, *Progress in Energy and Combustion Sciences*, 22, 201–26.

Geschner, F., Chaves, H., and Obermeier, F. (2001), Investigation of Different Phenomena of the Disintegration of a Sinusoidally Forced Liquid Jet. *ILASS-Europe*, Zurich, 2-6 September.

Geschner, F., Chaves, H., and Obermeier, F. (2004), Non-Dimensional Map for the Appearance of Spray Structures of a Periodically Excited Liquid Jet, *DFG Schwerpunktprogramm Fluidzerstäubung und Sprühvorgänge DFG-Priority Program Atomization and Spray Processes*, Dortmund, 18-19 March.

Goel, K.C., and Hollands, K.G.T., (1977), Optimum design of venturi scrubbers, *Atmospheric Environment*, 11(9), 837-845.

Gokalp, I., and Chauveau, C., (2000), Improving droplet break-up and vaporization models by including high pressure and turbulence effects, *Atomization and Sprays*, 10, 475–510.

Gokalp, I., Chauveau, C., Morin, C., and Vieille, B., (2001), Cassure et vaporisation des gouttes : effets de la pression, *In Combustion Dans Les Moteurs Fusees, Actes du Colloque de Synthese du Groupe de Recherche, CNES/CNRS/ONERA/SNECMA*.

Gokalp, I., Vieille, B., and Bodele, E., (2000), Modeling droplet break-up effects for highpressure cryogenic spray combustion codes. *In 36th AIAA/ASME/SAE/ASEE Joint Propulsion Conference and Exhibits*, Huntsville (USA), July.

Gomez-Diaz, D., and Navaza, J. M., (2005), Gas/liquid mass transfer processes in a carbon ioxide/alkane system, *J Chem Technol Biotechnol*, 80, 812–818.

Gourich, B., Azher, N., Vial, C., Soulami, M. B., Ziyad, M., and Zoulalian, A., (2007), Influence of operating conditions and design parameters on hydrodynamics and mass transfer in an emulsion loop–venturi reactor, *Chemical Engineering and Processing*, 46, 139–149.

Govatos, G. C., (1981), The slurry pump, *Journal of Pipelines*, 1, 145-157.

Gulbeyi Dursun, and Cevdet, (2006), Akosman Gas–liquid interfacial area and mass transfer coefficient in a co-current down flow contacting column, *J Chem Technol Biotechnol*, 81, 1859–1865.

Haenlein A., (1932), On the Disruption of a Liquid Jet, *National Advisory Committee Aeronautics, Technical Memorandum*, 659.

Havelka P., V. Linek, J., Sinkule, J., Zahradnik, M., and Fialova, (2000), Hydrodynamic and mass transfer characteristics of ejector loop reactors, *Chemical Engg. Science*, 55, 535-549.

Havelka, P., Linek, V., Sinkule, J., Zahradnnik, J., and FialovaH. M., (1997), Effect of the ejector confuguration on the gas suction rate and gas hold-up in ejector loop reactors. *Chemical Engineering Science*, 52, 1701-1713.

Henzler, H.J., (1983), Design of ejectors for single-fluid material systems, *German Chemical Engineering*, 6, 292-30.

Herrero Edgar, Vallea, P., Del, E. M. M., and Galan, M. A., (2007), Instability study of an annular liquid sheet of polymer produced by atomization, *Proceedings of European Congress of Chemical Engineering (ECCE-6) Copenhagen*, 16-20 September.

Hikita H., Asai, S., and Takatsuka, T., (1876), Absorption of carbon dioxide in to aqueous sodium hydroxide and sodium carbonate-bicarbonate solutions, *The Chemical Engineering Journal*, 11, 131-141.

Hikita, H., Asai, S., and Takatsuka, T., (1972), Gas absorption with a two-step instantaneous chemical reaction, *The Chemical Engineering Journal*, 4 (1), 31-40.

Hikita, H., Asai, S., Himukashi Y., and Takatsuka, T., (1973), Absorption of chlorine into aqueous sodium hydroxide solutions, *Chemical Engineering Journal*, 5, 77-84.

Hills, J. H., (1976), The operation of a bubble column at high throughputs in gas holdup measurements, *Chem. Eng.*, 12, 89-99.

Hinze, J. O., (1949), Forced deformations of viscous liquid globules, *Applied Scientific Research*, 1(1), 263-272.

Hinze, J. O., (1955), Fundamentals of the hydrodynamic mechanism of splitting in dispersion processes, *AIChE J*, 1(3), 289-295.

Hinze, J., (1959), *Turbulence*, New-York : Mc Graw-Hill.

Hirner, W., and Blenke, H., (1969), *Gas gehalt und phascngren zflache in schlaufen und strahl reaktoren*, *Verfahrenstechnik* 11, York.

Hiroyasu H., Arai M., and Shimizu M., (1991), Breack up length of a liquid jet and internal flow in a nozzle, *Procedings of ICLASS-91*, Paper No. 26.

Hopfinger, E., (2001), Atomization of a Liquid Jet by a Coaxial Gas Jet : A Critical Review, *In Combustion Dans Les Moteurs Fusées, Actes du Colloque de Synthèse du Groupe de Recherche CNES/CNRS/ONERA/SNECMA, Toulouse, Cité de l'Espace (FRANCE)*, June.

Hwang, S., Z., Liu, and Reitz, R., (1996), Breakup mechanisms and drag coefficients of high-speed vaporizing liquid drops, *Atomization and Sprays*, 6, 353-376.

Ingebo Robert D., (1991), Effect of gas mass flux on cryogenic liquid jet breakup, *Paper Presented at Space Cryogenics Workshop*, Cleveland, OH, USA, June.

Jackson, M. L., (1964), Gas Absorption in Venturis, *A.I.Ch.E.J.*, 10.

Jhaveri, A. S. and Sharma, M.M., (1968), Effective interfacial area in packed column, *Chemical Engineering Science*, 23, 669-676.

Johnstone, H. F. Tassler, M. C., and Field, R. B., (1954), Gas absorption and aerosol collection in a venturi atomizer, *Industrial and Engineering Chemistry*, 46, 1601-1608.

Joosten, G. E. H., and Danckwerts, P. V., (1973), Chemical reaction and effective interfacial areas in gas absorption, *Chemical Engineering Science*, 28, 453-461.

Kandakure, M.T., Gaikar, V.G., and Patwardhan, A.W., (2005), Hydrodynamic aspects of ejectors, *Chemical Engineering Science*, 60, 6391-6402.

Kankkunen, A. and Nieminen, K., (1997), Black liquor sheet breakup mechanisms and the effect on drop size, *International Journal of Fluid Mechanics Research*, 24 (1-3), 350-357.

Kashdan, J. T., Shrimpton J. S., Booth H. J., and Whybrew A., (2000), Assessment of particle characterization via phase doppler anemometry and automated particle image analysis techniques, *Proceedings of the 10th International Symposium on Application of Laser Techniques to Fluid Mechanics*, Lisbon, Portugal, 10-13 July.

Kashdana J.T., Shrimptona J.S., Whybrew A., (2007), A digital image analysis technique for quantitative characterisation of high-speed sprays, *Optics and Lasers in Engineering*, 45, 106-115.

Kazuya Shibata, Seiichi Koshizuka, and Yoshiaki Oka, (2004), Numerical analysis of jet breakup behavior using particle method, *Journal of Nuclear Science and Technology*, 41, 7, 715-722.

Kendoush, A.A., Al-khatib, S.A.W., (1989), Flow regimes characterization in vertical downward two phase flow, In: *Chen, X.Z., Veziroglu, T.N., Tien, C.L. (Eds.), Multiphase Flow and Heat Transfer, Second International Symposium*, I, 215-220.

Kim M., Kim O, Leea D, Kim S., (2007), Numerical and experimental investigations of gas-liquid dispersion in an Ejector, *Chemical Engineering Science*, 62, 7133-7139.

- Kitscha, J. & Kocamustafaogullari, G., (1989), *Int. J. Multiphase Flow*, 15 (4), 573-588.
- Knapp, R.T, Daily, J.W., and Hammitt, F.G. (1970). *Cavitation*, New York, McGraw-Hill.
- Koetsier, W. T., Van Swaiij, W. P. M., and Van der Most. M., (1976), Maximum gas holdup in bubble columns, *J. Chem. Eng. (Japan)*, 9. 332-333.
- Kolmogorov, A., (1949), On the desintegration of drops by turbulent flows. dokl. acad. nauk. SSSR, 66, 825-828.
- Kordac, M., and Linek, V., (2008), Dynamic measurement of carbon dioxide volumetric mass transfer coefficient in a well-mixed reactor using a ph probe: analysis of the salt and supersaturation effects, *Ind. Eng. Chem. Res.*, 47, 1310-1317.
- Krauss, W. E., (1970), *Water Drop Deformation and Fragmentation Due to Shock Wave Impact*, Ph.D. Thesis, University of Florida.
- Kroll, A. E., (1947), The design of jet pump, *Chemical Engg. Progress*, 43(2), 21-24.
- Krzeczkowski Stefan A., (1980), Measurement of liquid droplet disintegration mechanisms, *In I. J. Multiphase Flow*, 6, 227-239.
- Kuferath, A., Wende, B., and Leuckel, W., (1999), Influence of liquid flow conditions on spray characteristics of internal-mixing twin fluid atomizers, *International Journal of Heat and Fluid Flow*, 20, 513-519.
- Kundu, G., Mukherjee, D., and Mitra, A.K., (1994), Gas entrainment and depth of penetration in a cocurrent gas liquid downflow bubble column, *Journal of Chemical Engineering of Japan*, 27 (5), 621-626.
- Kundu, G., Mukherjee, D., and Mitra, A.K., (1995), Experimental studies on a co-current gas-liquid downflow bubble column, *International Journal of Multifluid Flow*, 21 (5), 893-906.
- Kuznetsov, M.D., Oratovskii, V.I., (1962), Rate of chemisorption in a venturi-type apparatus, *Int. Chem. Eng.*, 2, 185-188.

Lahiri N., Yadav, G. D., and Sharma, M. M., (1983), Absorption of chlorine in aqueous solutions of sodium hydroxide desorption of hypochlorous acid followed by its dissociation to chlorine monoxide, *Chemical Engineering Science* , 38(7), 1119-1133

Lane, W. R., (1951), Shatter of Drops in Streams of Air, *Industrial and Engineering Chemistry*, 43, 1312.

Lang, R. J., (1962), Ultrasonic Atomization of Liquids, *Journal of the Acoustic Society of America*, 34(1), 6-8.

Laurent Andre, (1978), Fonteix christian, besson gerard and charpentier jean-claude, pilot-scale study of absorption with chemical reaction in a venturi-jet scrubber, atmospheric pollution, *Proceedings of the 13th International Colloquium, Pans, France*, April 25-28, Studies in Environmental Science, 1, 251-254.

Laurent, A., and Charpentier, J. C., (1974), Aires Interfaciales et coefficients de transfert de matiere dans les divers types d'absorbeurs et de reacteurs gaz-liquide, *The Chemical Engineering Journal*, 8, 85-101.

Lefebvre, H., (1989), *Atomization and Sprays*, Hemisphere Pub. Cor., New York.

Leick Philippe, (2008), *Quantitative investigations about the influence of nozzle geometry and ambient gas density on the primary break-up region of diesel sprays*, Dissertation submitted for Doctor of Engineering to Technical University Darmstadt.

Leith, D., and Cooper, D.W., (1980), Venturi scrubber optimization, *Atmos Environ*, 14, 657-664.

Leroux, S., Dumouchel, C., Ledoux, M., (1996), The Stability Curve of Newtonian liquid Jets, *Atomization and sprays*, 6, 623-647.

Levenspiel Octave, (1999), *Chemical Reaction Engineering*, Third ed., John Wiley & Sons, New York.

Levich, V. G., (1962), Physicochemical Hydrodynamics, *Prentice Hall, New York*.

Li, C., and Li, Y. Z., (2011), Investigation of entrainment behavior and characteristics of gas-liquid ejectors based on CFD simulation, *Chemical Engineering Science*, 66, 405-416.

- Li, M., and Christofides, P., (2005), Multiscale modeling and analysis of an industrial HVOF thermal spray process, *Chemical Engineering Science*, 60, 3649-3669.
- Li, X., and Tankin, R. S., (1987), Droplet size distribution: a derivative of a Nukiyama-Tanasawa type distribution function, *Combustion Science and Technology*, 56, 65-76.
- Li, X., and Tankin, R., S., (1988), Droplet size distribution in sprays by using information theory, *Combustion Science and Technology*, 60, 345-357.
- Lifshitz, A., and Perlmutter-Hayman, B. (1962), The kinetics of the hydrolysis of chlorine III, The reaction in the presence of various bases and discussion of the mechanism, *J. Phys. Chem.*, 66, 701-705.
- Lifshitz, A., and Perlmutter-Hayman, B., (1961), The kinetics of the hydrolysis of chlorine II, The hydrolysis in the presence of acetate, *J. Phys. Chem.*, 65, 753-757.
- Lin, S. P., and D. R. Woods. (1991), A branching liquid jet, *Physics of Fluids*, A3, 241- 244
- Lin, S. P., and Reitz, R.D., (1998), Drop and spray formation from a liquid jet, *Annual Review of Fluid Mechanics*, 30, 85-105.
- Littay, G., (1943), Sur l'atomisation of liquids, *Wydawnictwo Naukowo-Techniczne*.
- Liu, H., (2000), *Science and Engineering of Droplets: Fundamentals and Applications*, New York: Noyes Publications.
- Liu, Z., and Reitz, R., (1997), An analysis of the distortion and breakup mechanisms of high speed liquid drops, *Inter. J. of Multiphase Flow*, 23 (4), 631-650.
- Lydersen, A.L., (1983), *Mass transfer in engineering practice*, John Wiley & Sons, New York.
- Mahajani, V. V., and Sharma, M. M., (1981), Gas absorption with photochemical reaction, *Chemical Engineering Science*, 36, 295-597.
- Mahajani, V., and Sharma, M. M., (1979), Effetive interfacial area and liquid side mass transfer coefficient in trickle bed reactors, *Chemical Engineering Science*, 34, 1425-1428.
- Mahajani, V., and Sharma, M. M., (1980), Mass transfer in packed columns: co-current (downflow) operation- 1 m. and 1.5 m. metal pall rings and ceramic intalox saddles. multi

filament gauze packings in 20 cm and 38 cm I.D. columns, *Chemical Engineering Science*, 35, 941-947.

Majumder, S.K., Kundu, G., Mukherjee, D., (2005), Mixing mechanism in a modified co-current downflow bubble column, *Chemical Engineering Journal*, 112, 45-55.

Mandal Aj., (2010), Characterization of gas-liquid parameters in a down-flow jet loop bubble column, *Brazilian Journal of Chemical Engineering*, 27 (02), 253-264.

Mandal Ajay, Kundu Gautam and Mukherjee Dibyendu, (2004), Gas-holdup distribution and energy dissipation in an ejector-induced down flow bubble column: the case of non-Newtonian liquid, *Chemical Engineering Science*, 59, 2705 – 2713.

Mandal, A., Kundu, G. and Mukherjee, D., (2003b), Interfacial area and liquid-side volumetric mass transfer coefficient in a downflow bubble column, *Can J of Chem Eng*, 81, 212–219.

Mandal, A., Kundu, G. and Mukherjee, D., (2003a), Gas holdup and entrainment characteristics in a modified downflow bubble column with Newtonian and non-Newtonian liquid, *Chemical Engineering and Processing*, 42, 777-787.

Mandal, A., Kundu, G., and Mukherjee, D., (2005), A comparative study of gas holdup, bubble size distribution and interfacial area in a downflow bubble column, *Trans IChemE, Part A, Chemical Engineering Research and Design*, 83(A4), 423–428.

Mandal, A., Kundu, G., and Mukherjee, D., (2005a), Comparative study of two fluid gas-liquid flow in the ejector induced up flow and downflow bubble column, *International Journal of Chemical Reactor Engineering*, 3 Article A13.

Mandal, A., Kundu, G., and Mukherjee, D., (2005b.), Energy analysis and air entrainment in an ejector induced downflow bubble column with non-Newtonian motive fluid, *Chemical Engineering Technology*, 28 (2), 210-218.

Mansour, A. and Chigier, N., (1994), Effect of turbulence on the stability of liquid jets and resulting droplet size distributions, *Atomization and Sprays*, 4, 583-604.

Mansour, A., and Chigier, N., (1993), A phase doppler investigation of co-axial air blast atomizers, *Fluid Mechanics and Heat Transfer in Spray*, ASME 270, 95-101.

- McCabe, W. L., Smith, J. C., and Harriott Peter, (1993), *Unit Operations in Chemical Engineering, International Edition, 7th Edition*, McGraw- Hill Inc., New Delhi.
- McCarthy, M. J., and Molloy, N.A., (1974), Review of stability of liquid jets and the influence of nozzle design, *Chemical Engineering Journal*, 7, 1.
- McCormack, P.D., Crane, L., and Birch, S., (1965), An experimental and theoretical analysis of cylindrical liquid jets subjected to vibration, *British Journal of Applied Physics*, 16, 395-408.
- Meier, G.E.A., Loose, S., and Stasicki, B., (1997), Unsteady Liquid Jets, *Applied Scientific Research*, 58, 207-216.
- Meikap, B. C., Kundu, G., and Biswas, M. N., (2001), Prediction of the Interfacial Area of Contact in a Variable-Area Multistage Bubble Column, *Ind. Eng. Chem. Res.*, 2001, 40, 6194-6200.
- Meikap, B.C., and Biswas, M.M, (2004), Mass transfer characteristics of a cuurent multi-stage bubble column scrubber, *Journal of Chemical Engineering of Japan*, 37(10),1185-1193.
- Meyers Nicolas, (2006), *Mod'elisation de la combustion cryotechnique avec prise en compte de l'atomisation primaire du jet d'oxyg'ene liquide*, May, Universite D'aix-Marseille, France.
- Midoux N., Laurent A., Charpentier J. C., (1980), Limits of the chemical method for the determination of physical mass transfer parameters in mechanically agitated gas-liquid reactors, *AIChE Journal*, 26, 1, 157–162, January.
- Midoux, N., Morsi, B. I., Purwasasmita, M., Laurent, A., and Charpentier, J. C., (1984), Interfacial area and liquid side mass transfer coefficient in trickle bed reactors operating with organic liquids, *Chemical Engineering Science*, 39, 5, 781-794.
- Mitchell D., (1981), Improving the efficiency of free-jet scrubbers, *Environmental International*, 6, 21-24.
- Mitchell J. F. B., (1989), *Reviews of Geophysics*, 27 (1), 115-139, Paper number 89RG00094.
- Mitra, A. K., and Roy, A. N., (1964), Studies on the performance of ejector : correlation for air-air system, *Indian Journal of Technology*, 2(9), 315-316.
- Mitra, A. K., Guha, D. K., and Roy, A. N., (1963), Studies on the performance of ejector Part-I,air-air system, *Indian Chem. Eng. Trans.*, 5, 59.

- Mohebbi A., Taheri M., Fathikaljahi J., and Talaie M.R., (2003), Simulation of an orifice scrubber performance based on Eulerian/Lagrangian method, *Journal of Hazardous Materials*, A100, 13-25.
- Monabbati, M., Ayatollahi, S., and Taheri, M., (1989), Test of mathematical modeling for the design of high energy scrubbers, *J. Aerosol Sol.*, Vol. 20, No. 8, pp. 1441-1444.
- Moresi, M., Gianturco, G.B., and Sebastini, E., (1983), The ejector loop fermenter: description and performance of the apparatus, *Biotechnology and Bioengineering*, 25, 2889-2904.
- Morris, J. C., (1966), The Acid Ionization Constant of HOCl from 5⁰ to 35⁰, *J. Phys. Chem.*, 70, 3798.
- Morris, J.C, (1946), The mechanism of the hydrolysis of chlorine, *J Am Chem Soc.*, 68(9), 1692-4.
- Mukherjee, D., Biswas M. N., and Mitra, A. K., (1981), Holdup studies in liquid; liquid ejector system, *Institute of Chemical Engineers*, 1, 1-5.
- Mukherjee, D., Biswas M. N., and Mitra, A. K., (1988), Hydrodynamics of liquid-liquid dispersion in ejectors and vertical two phase flow, *Can. J.Chem. Eng.*, 66, 896-907.
- Mukherjee, S., Das, S.K., and Biswas, M.N., (2007), Absorption of carbon disulphide in alkaline solution in spray and ejector columns, *Chemical Engineering and Processing*, 46, 181-186.
- Nagel, O., Kurten, H., and Sinn, R., (1970), Strahldiisenreaktoren -Teil I, *Chem. Eng. Tech.*, 42, 474-479.
- Nasseh S., Mohebbi A., Sarrafi A., and Taheri M., (2009), Estimation of pressure drop in venturi scrubbers based on annular two-phase flow model, artificial neural networks and genetic algorithm, *Chemical Engineering Journal*, 150, 131-138.
- Neppiras, E.A., (1980), Acoustic Cavitation, *Physics Report*, 61, 160-251.
- Nijssing, R. A. T. O., Hendrikz, R. H., and Kramers, H., (1959), Absorption of carbondioxide in jets and falling films of electrolytic solutions, with and without chemical reactions, *Chem. Eng. Sci.*, 10, 88-104.

O'Rourke, P., and A. Amsden, (1987), The TAB method for numerical calculations of spray droplet breakup, *SAE Paper*, (872089).

Ogawa S., Yamaguchi H., Tone S. and Otake T., (1983), Gas-liquid mass transfer in the jet reactor with liquid jet reactor, *Journal of Chemical Engineering of Japan*, 16(5), 419-425.

Ohkawa, A., Kawai, Y., Ksibiraki, D., Saki, N. and Endoh, K., (1987), Bubble size, interfacial area and volumetric liquid-phase mass transfer coefficient in downflow bubble columns with gas entrainment by a liquid jet, *J of Chem Eng of Japan*, 20, 99-101.

Ohkawa, A., Kusabiraki, D., Kawai, Y., and Sakai, N., (1986), Some flow characteristics of a vertical liquid jet system having downcomers, *Chemical Engineering Science*, 41 (9), 2247-2361.

Ohnesorge, W., and Angew, Z., (1936), *Math. Mech.*, 11, 136-159.

Otake, T., Tone, S., Kuboi, R., Takahashi, Y., and Nakao, K., (1981), Dispersion of a gas by a liquid jet ejector, *Int. Chem. Eng.*, 21, 72-80.

Ott, Robert M., Wu, T. K. L., and Crowder Jerry W., (1987), Modelling of Surface tension Effects in Venturi Scrubbing, *Atmospheric Environment*, 21(3), 479-482.

Oyevaar, M.H., and Westerterterp, K.R., (1989), The use of the chemical method for the determination of interfacial areas in gas-liquid contactors, *Chemical Engineering Science*, 44(11), 2691-2701.

Pal, S. S., Mitra, A. K. and Roy, A. N., (1979), Pressure drop and holdup in a vertical two-phase counter current flow with improved gas mixing liquid, *Ind. Eng. Chem. Process Des. Dev.*, 19(1), 67-75.

Panchal, N.A., Bhutada, S.R., and Pangarkar, V.G., (1991), Gas induction and hold-up characteristics of liquid jet loop reactors using multi orifice nozzles, *Chem. Engg. Communication*, 102, 59-68.

Park, S. H., Suh, H. K., and Lee, C. S., (2008), Effect of cavitation flow on the flow and fuel atomization characteristics of biodiesel and diesel fuels, *Energy and Fuels*, 22, 605-613.

- Patel, H.J., (2004), *Studies on the performance and measurement of interfacial area generated by multi-jet ejector*, M.E. Dissertation, The Maharaja Sayajirao University of Baroda, Vadodara.
- Pawelczyk, R., and Pindur, K., (1999), A dynamic method for dispersing gases in liquids, *Chemical Engineering and Processing: Process Intensification*, 38 (2), 95-107.
- Perry, R.H., Green, D.W., and Maloney, J.O., (1997), *Perry's Chemical Engineers' Handbook*, Seventh ed., The McGraw-Hill Companies, Inc., New York.
- Pfeifer C., Kuhan D. and Class A., (2010), *Coupled measurement of droplet size distribution and velocity distribution in a fuel spray with digital imaging analysis under elevated pressure*, 15th Int Symo on Applications of Laser Techniques to Fluid Mechanics, Lisbon, July 5-8.
- Ping-fang and HanLi-xin Tang, (2005), Experimental study on the hydrodynamics and mass transfer characteristics of ultrasonic air lift loop reactor, *Canadian Journal of Chemical Engineering*, 83, 204.
- Plateau, J., (1873), Statique experimentale et the-orique des liquids soumie aux seules forcesmoleculaire, *Paris: cauthier vil-lars*, 1, 2, 450-495.
- Pohorecki, R., (1968), The absorption of CO₂ in carbonate—bicarbonate buffer solutions containing hypochlorite catalyst on a sieve plate, *Chemical Engineering Science*, 23, 1447-1451.
- Pulley, R.A., (1997), Modelling the Performance of Venturi Scrubber, *Chemical Engineering Journal*, 67, 9-18.
- Radhakrishnan, V. R., and Mitra, A. K., (1984), Pressure drop, holdup and interfacial area in vertical two-phase flow of multi-jet ejector induced dispersions, *The Canadian Journal of Chemical Engineering*, 62, 2, 170–178.
- Raghuram, P. T., (2009), Interfacial area measurement in gas-liquid ejector for a sodium chloride-air system, *Indian Journal of Chemical Technology*, 16, 278-282.
- Raghuram, P. T., and Mukherjee, A.K., and Das, T.R., (1992), Studies on a gas-liquid ejector-contactor, *Indian Chemical Engineer*, 34(1), 40-49.

Rahimi A., Taheri M. and Fathikalajahi J. (2004), Prediction of pressure drop in a venturi scrubber: effect of liquid film and re-entrainment, *Chemical Engineering Communications*, 191 (3), 315-334.

Rahimi, A., Niksiar, A., and Mobasheri, M., (2011), Considering roles of heat and mass transfer for increasing the ability of pressure drop models in venturi scrubbers, *Chemical Engineering and Processing*, 50, 104–112.

Rahman F., Umesh D.B., Subbarao D., and Ramasamy M., (2010), Enhancement of entrainment rates in liquid–gas ejectors, *Chemical Engineering and Processing*, 49, 1128–1135.

Ranger, A. A., and Nicholls, J. A., (1969), Aerodynamic shattering of liquid drops, *AIChE Journal*, 7, 285.

Ranz, W. E., (1956), On sprays and spraying, *Department of Engineering Resources, Pennsylvania State University*, Bulletin 65.

Ravi, G., Viswanathan, S., Gupta, S.K., and Ray, M. B., (2003), Multi-objective optimization of venturi scrubbers using a three-dimensional model for collection efficiency, *Chemical Engineering Technology and Biotechnology*, 78, 308-313.

Ravindram Maddury and Pyla Naidu, (1986), Modeling of a venturi scrubber for the control of gaseous pollutants, *Ind. Eng. Chem. Process Des. Dev.*, 25(1), 35-40.

Rayleigh L, (1879b), On the instability of jets, *Proc. London Math. Soc.*, 10, 406-46.


Rayleigh, L., (1879a), On the capillary phenomenon of jets., *Proc. R. Soc. London.*, 29, 71-97

Reitz Rolf, D., (2004), Modeling the primary breakup of high-speed jets, *Atomization and Spray*, 14 (1), 99.

Reitz, R. D., (1978), *Atomization and Other Breakup Regimes of a Liquid Jet*, Ph. D. Dissertation, Princeton University.

Reitz, R., and Bracco, F., (1982), Mechanism of atomization of a liquid jet, *Phys. Fluids*, 25 (10).

- Reitz, R., and Bracco, F., (1986), Mechanics of breakup of round liquid jets, *Volume 3, Chapter 10*, 233–249.
- Rice, R.G., and Littlefield, M.A., (1987), Dispersion coefficients for ideal bubbly flow in truly vertical bubble columns., *Chem. Engg. Sci.*, 42, 2045-2053.
- Richards, G. M., Ratliff, G. A., and Danckwert, P. V., (1964), Kinetics of CO₂ absorption-III, First-order reaction in a packed column, *Chemical Engineering Science*, 19, 325-328.
- Roy Sharmistha and Rochelle Gary, T., (2004), *Chlorine Absorption in Sulfite Solutions*, *Separation Science and Technology*, 39, 13, 3057-3077.
- Ruff, G., Wu, P., Bernal, L., and Faeth, G., (1992), Continuous and dispersed-phase structure of dense non-evaporating pressure-atomized sprays, *J. Prop. Power*, 8, 280–289.
- Rulz-Ibanez, G., Bldarlan, A., Davis, R.A., and Sandall, O.C., (1991) Solubility and diffusivity of oxygen and chlorine in aqueous hydrogen peroxide solutions , *J. Chem. Eng. Data*, 36, 459-466.
- Rushton, J. H. and Oldshue, J. Y., (1953), Mixing: present theory and practice, *Chem. Eng. Prog.*, 49, 161.
- Rusly, E., Aye, L., Charters, W.W.S., and Ooi, A., (2005), CFD analysis of ejector in a combined ejector cooling system, *International Journal of Refrigeration*, 28, 1092-1101.
- Rylek, M., and Zahradnik, J., (1984), Design of Venturi-tube gas distributors for bubble type reactors, *Collect. Czech. Chem. Commun.*, 49, 1939–1948.
- Sadek Shafik E., Nawrocki Daniel A., Sterbis Eugene E., and Vivian J. Edward, (1977), Absorption with reaction of sulfur dioxide and chlorine, *Ind. Eng. Chem., Fundam.*, 16(1), 36-39.
- Sahay, B. N., and Sharma, M. M., (1973), Effective interfacial area and liquid and gas side mass transfer coefficient in packed column, *Chemical Engineering Science*, 28, 41-47.
- Sandall, O. C., Goldberg, I. B., Hurlock, S. C., Laeger, H. O., Wagner, R. I., (1981), Solubility and rate of hydrolysis of chlorine in aqueous sodium hydroxide at 273K, *AIChE Journal*, 27(5), 856–859.



Schick, R. J., (2006), Spray Technology Reference Guide: Understanding Drop Size, *Bulletin* no. 4598 Wheaton, Illinois: Spraying Systems Co.

Schmidt, D., P., Rutland, C., J., and Corradini, M. L., (1997), A Numerical Study of Cavitating Flow Through Various Nozzle Shapes, *Society of Automotive Engineers, Paper* No. 971597.

Schugerl, K., (1982), New Bioreactors for Aerobic Processes, *Int. Chem. Eng.*, 22, 591–610.

Sedelies, R.S., A., Weinspach, P.M., (1987), Mass transfer area in different gas-liquid reactors as a function of liquid properties, *Chem. Eng. Technol.*, 10, 1-15.

Shabani Amir, Tavoosi Siamakl and Shahraki Bahram Hashemi, (2010), Calculation of effective interfacial area in a turbulent contact absorber, *International Journal of Chemical Engineering and Applications*, 1, 1, June.

Sharma, M. M., and Danckwerts, P. V., (1970), Chemical methods of measuring interfacial area and mass transfer coefficients in two-fluid systems, *Brit. Chem. Eng.*, 15, 522-528.

Shende, B. W., and Sharma, M. M., (1974), Mass transfer in packed columns: co-current Operation, *Chemical Engineering Science*, 29, 1763-1772.

Sheng, Y. Y. and Irons, G. A., (1995), *The Impact of Bubble Dynamics on the Flow in Plumes of Ladle Water Models*, Metallurgical Trans., B, 26B, 625-635.

Sherwood, T. K. and Pigford, R. L., (1952), *Absorption and Extraction*, 2nd Edn. McGraw-Hill, New York, 332.

Silva, A. M., Teixeira, J. C. F., Teixeira, S.F.C.F., (2009a), Experiments in a large-scale venturi scrubber Part I: Pressure drop, *Chemical Engineering and Processing*, 48, 59-67.

Silva, A. T. D., and Danckwert, P. V., (1973), The effect of halogens on the rate of absorption of carbon dioxide, *Chemical Engineering Science*, 28, 847-854.

Silva, A.M., Teixeira, J.C.F., Teixeira, S.F.C.F., (2009b), Experiments in large scale venturi scrubber Part II Droplet size, *Chemical Engineering and Processing*, 48, 424-431.

Silva, Marcela K., Avila Marcos, A. D., and Mori Milton, (2011), CFD modelling of a bubble column with an external loop in the heterogeneous regime, *The Canadian Journal of Chemical Engineering*, 89, 671-681.

Simonin, R. F., (1959), Recherches theoretiques et experimentales sur l'entrainement d'air par une veine d'eau cylindrique percutant dans mass d'eau, in *Proceedings of the 8th Congress of IAHR, Montreal*, 6-D.

Sindayihebura, D., and Bolle, L., (1998), Ultrasonic atomization of liquid: stability analysis of the viscous liquid film free surface. *Atomization Sprays*, 8, 217-233.

Singh, K. P., Purohit, N. K., and Mitra, A. K., (1974), Performance characteristics of a horizontal ejector: water-water system, *India Chemical Engineer*, XVI (3), 1-6.

Smallwood, G. J., and Gulder, O. L., (2000), Views on the structure of transient diesel sprays, *Atomization and Sprays*, 10 (3-5), 355-386.

Soteriou, R., Andrews, R., and Smith, M., (1995), Direct injection diesel sprays and the effect of cavitation and hydraulic flip on atomization, *Society of Automotive Engineers, Paper No. 950090*, 27-51.

Sou A., Maulana, M. I., Hosokawa, S. and Tomiyama, A., (2008), Ligament Formation Induced by Cavitation in a Cylindrical Nozzle, *Journal of Fluid Science and Technology*, 3,5, 633-644.

Sou, A., Hosokawa, S., and Tomiyama, A., (2009), Dimensionless Numbers on Cavitation in a Nozzle of Pressure Atomizers, *ICLASS 2009, 11th Triennial International Annual Conference on Liquid Atomization and Spray Systems*, Vail, Colorado USA, July.

Sou, A., Maulana, M. I., Hosokawa, S., and Tomiyama, A., (2007), Effect of cavitation in a nozzle on liquid jet atomization, *International Journal of Heat and Mass Transfer*, 50, 17-18, 3575-3582.

Sou, A., Tomiyama, A., Hosokawa, S., Nigorikawa, S., and Maeda, T., (2006), Cavitation in a two-dimensional nozzle and liquid jet atomization (ldv measurement of liquid velocity in a nozzle), *Japan Society of Mechanical Engineering, International Journal, Series B*, 49(4), 1253-1259.

Spalding C. W., (1962), Reaction kinetics in the absorption of chlorine in to aqueous, *A.I.Ch.E.J.*, 8, 685.

Priveerakul, T., Aphornratana, S., and Chunnanond, K., (2007), Performance prediction of steam ejector using computational fluid dynamics: part 1, Validation of the CFD results, *International Journal of Thermal Sciences*, 46, 812-822.

Stein, W.A., Schafer, H., (1984), Aeration of viscous liquids with a downward directed two-fluid nozzle, *Ger. Chem. Eng.*, 7, 115-125.

Sun, H, and Azzopardi, B. J., (2003), Modelling gas-liquid flow in venturi scrubbers at high pressure, *Trans.Institute of Chemical Engineers*, 81(B), 250-256.

Taheri Mahboobeh and Mohebbi Ali, (2008), Design of artificial neural networks using a genetic algorithm to predict collection efficiency in venturi scrubbers, *Journal of Hazardous Materials*, 157, (2008), 122–129.

Taheri Mahboobeh, Mohebbi Ali and Taheri Alireza, (2010), Simulation of SO₂ absorption in a venturi scrubber, *Chemical Engineering Communications*, 197, 7, 934-952.

Takahashi, T., Hatanaka, M., and Konaka, R., (1967), Absorption of chlorine into still liquid in a simple stop-cock type absorber, *Can. J. Chem Engrs*, 45, 145.

Talaie, M.R., Fathikalajahi, J., Taheri, M., (1997), Mathematical modeling of SO₂ absorption in a venturi scrubber, *J. Air Waste Manage. Assoc.*, 47, 1211–1215.

Tamaki N., Shimizu M., and Hiroyuki, (2001), Enhancement of the Atomization of a liquid jet by cavitation in a nozzle hole, *Atomization and Sprays*, 11, 2, 125-137.

Tamaki, N. A., Kato, K., Imano and Kato, K., (2010), Improvement of atomization characteristics of spray by multi-hole nozzle for pressure atomized type injector, *ILASS – Europe 2010, 23rd Annual Conference on Liquid Atomization and Spray Systems, Brno, Czech Republic*, September.

Tamaki, N., (2009), Effects of cavitation in a nozzle hole on atomization of spray and development of high-efficiency atomization enhancement nozzle, *11th International Conference on Liquid Atomization and Spray Systems*, Vail Colorado, USA, 26-30 July.

Tamaki, N., and Shimizu, M., (2002), Enhancement of atomization of high-viscous liquid jet by pressure atomized nozzle , *ILASS – Europe*, September 9-11.

Tamaki, N., Nishida, Y. and Hosokawa, T., (2007), Practical study on high-dispersion and high-penetration diesel injection nozzle: 1st report, effects of geometric shape of high-dispersion atomization enhancement nozzle on atomization of intermittent spray, *Proc. 21st Institute for Liquid Atomization and Spray Systems-Europe*, CD-R, 6.

Tamaki, N., Shimizu, M., Nishida, K., and Hiroyasu, (1998), Effects of cavitation and internal flow on atomization of a liquid jet, *Atomization and Sprays*, 8, 2, 179-197.

Tamir, A., Danckwerts, P.V., and Virkar, P. D., (1975), Penetration model for absorption with chemical reaction in the presence of heat generation, bulk flow and effects of the gaseous environment, *Chemical Engineering Science*, 30, 1243-1250.

Tang Liang-Guang, Li Xiao-Sen, Feng Zi-Ping, Lin Yu-La, and Fan Shuan-Shi, (2006), Natural Gas Hydrate Formation in an Ejector Loop Reactor: Preliminary Study, *Ind. Eng. Chem. Res.* 2006, 45, 7934-7940.

Terasaka, K., Tsuge, Hideki H, (1991), Mass transfer in highly viscous liquids in a bubble column with constant-flow nozzles, *Journal of Chemical Engineering of Japan*, 24(4), 424-429.

Tie Li Keiya, and Nishida Hiroyuki Hiroyasu, (2011), Droplet size distribution and evaporation characteristics of fuel spray by a swirl type atomizer, *Fuel*, 90, 2367-2376.

Tomotika, S., (1935), On the instability of a cylindrical thread of a viscous liquid surrounded by another viscous fluid, *Proc. R. Soc. London Ser. A.*, 150, 322-37.

Tseng, L., (1992a), Effects of gas density on the structure of liquid jets in still gases, *AIAA*, 30, 1537-1544.

Tseng, L., and Wu, P., (1992b), Dispersed-phase structure of pressure-atomized sprays at various gas densities, *J. Prop. Power*, 8, 1157-1166.

Tuve, (1953), *Heat. Piping Air Cond.*, 25(1), 181-191.

Uchida, S., and Wen, C.Y., (1973), Gas absorption by alkaline solutions in a venturi scrubber, *Ind. Eng. Chem. Process Des. Develop.*, 12 (4), 437-443.

Utomo, T., Jin, Z., Rahman, M., Jeong, H. and Chung, H., (2008), Investigation on hydrodynamics and mass transfer characteristics of a gas-liquid ejector using three-dimensional CFD modeling, *Journal of Mechanical Science and Technology*, 22, 1821-1829.

Vamos Lenard, (2010), Simulation models for aerosol characterization by elastic light scattering with special emphasis on photon correlation experiments in the nano-particle size range, *PhD Theses, Institute for Solid State Physics and Optics*, Budapest University of Technology and Economics, Budapest, Hungary.

Vidwans, A., D., and Sharma, M. M., (1967), Gas-side mass transfer coefficient in packed column, *Chemical Engineering Science*, 22, 673-683.

Vieth, W. R., Porter, J. H., and Sherwood, T. K., (1963), Mass transfer and chemical reaction in a turbulent boundary layer, *Ind. Eng. Chem. Fund*, 2(1), 1-3.

Virkar, P. D., and Sharma, M. M., (1975), Mass Transfer in Venturi Scrubbers, *Canadian Journal of Chemical Engineering*, 53, 512-516.

Viswanathan, S., Lim, D. S., and Ray, M. B., (2005), Measurement of drop size and distribution in an annular two-phase, two-component flow occurring in a venturi scrubber, *Ind. Eng. Chem. Res.*, 44, 7458-7468.

Viswanathan, S., (1997), Modeling of Venturi Scrubber Performance, *Ind. Eng. Chem. Research*, 36(10), 4308-4317.

Viswanathan, S., (1998), Examination of liquid film characteristics in the prediction of pressure drop in a Venturi scrubber, *Chemical Engineering Science*, 53(17), 3161-3175.

Viswanathan, S., Gnyp, A. W., and St. Pierre, C. C., (1985), Annular flow pressure drop model for Pease–Anthony type venturi scrubbers, *AIChE Journal*, 31, 1947–1958.

Volgin, B.P., Efimova, T.F., Gofman, M.S., (1968), Absorption of sulfur dioxide by ammonium sulfite-bisulfite solutions in a venturi scrubber, *International Chemical Engineering*, 1 (8), 113-118.

Volmuller, H., and Walburg, R., (1973), Blasengrope bei der Begasung mit Venturidiisen, *Chern. Ing. Tech.*, 45, 913-920.

Waal, K.J.A., and Beek, W.J., (1967), A comparison between chemical absorption with rapid first-order reactions and physical absorption in packed column, *Chemical Engineering Science*, 22, 585-593.

Weber, C.Z., (1931), Zum zerfall eines fluss-sigkeitsstrahles, *Math. Mech.*, 11, 136-54.

Weisweiler, W., and Rosch, S., (1978), Interfacial area and bubble-size distribution in jet reactors, *German Chemical Engineering*, 1(4), 212-218.

Wen, C. Y., and Fan, L. T., (1975), *Models for Flow Systems and Chemical Reactors*, 390-420, Marcel Dekker, New York.

Witte, J. H., (1969), Mixing shocks in two phase flow, *Journal of Fluid Mechanics*, 36, 639-655.

Wolfe, H. E., and Andersen, W.H., (1964), Kinetics mechanism and resultant droplet sizes of the aerodynamic breakup of liquid drops, *Aero jet General Corporation, CA, USA*, Report no-0395-04(18)SP.

Wu, P., and Faeth, M., (1993), Aerodynamic effects on primary breakup of turbulent liquids, *Atomization and Sprays*, 3, 265-289.

Wu, P., Miranda, R. and Faeth, G., (1995), Effect of initial flow conditions on primary breakup of nonturbulent and turbulent round liquid jets, *Atomization and Sprays*, 5, 175-196.

Yadav, R. L., and Patwardhan, A. W., (2008), Design aspects of ejectors: Effects of suction chamber geometry, *Chemical Engineering Science*, 63, 3886-3897

Yaici, W., Laurent, A., Midoux, N., and Charpentier, J.C., (1988), Determination of gas-side mass transfer coefficients in trickle-bed reactors in the presence of an aqueous or an organic liquid phase, *International chemical Engineering*, 28 (2), 299-305.

Yamagiwa, K., Kusabiraki, D., and Ohkawa, A., (1990), Gas holdup and gas entrainment rate in down flow bubble column with gas entrainment by a liquid jet operating at high liquid throughput, *Journal of Chemical Engineering of Japan*, 23, 343-348

Yamashita, F. and Inoue, H., (1975), Gas Holdup in Bubble Columns, *J. Chern. Eng. (Japan)*, 8, 334-340.

Yongyingsakthavorn, P., Vallikul, P., Fungtammasan, B., Dumouchel, C., and Joulain, P., (2004), An Investigation on Line-of-Sight and Local Drop Size Distributions of Palm Oil Based Biodiesel Sprays Using Laser Diffraction Data, *The Joint International Conference on Sustainable Energy and Environment (SEE)*, December 1-3.

Yung, S. C., Barbarika, H. F., and Calvert, S., (1977), Pressure loss in venturi scrubbers, *J. Air Pollut. Control Assoc.*, 27, 348–351.

Yung, S., Calvert, S., and Barbarlka, H. F., (1978), *Venturi Scrubber Performance Model Environmental Science & Technology*, 1978, 456-459.

Yusuf Adewuyi G., Xiangdong H. E., Henry Shaw & Wanna Lolertpihop, (1999), Simultaneous absorption and oxidation of no and SO₂ by aqueous solutions of sodium chlorite, *Chemical Engineering Communications*, 174, 1, 21-51.

Zahradnik, J., and Fialova, M., (1996), The effect of bubbling regime on gas and liquid phase mixing in bubble column reactors, *Chemical Engineering Science*, 51(10), 2491-2500.

Zahradnik, J., Fialova, M., Linek, V., Sinkule, J., Renickoca, J., and Kastanek, F., (1997), Dispersion efficiency of ejector-type gas distributors in different operating modes, *Chem. Eng. Sci.*, 52 (24), 4499–4510.

Zahradnik, J., Kratochvil, J., and Rylek, M., (1985), Gas holdup and interfacial mass transfer in gas-liquid tower contactors with ejector type gas distributors, *Collect. Czech. Chem. Commun.*, 50, 2535–2544.

Zahradnlk, J., and Kastanek, F., (1982), Hydrodynamics and mass transfer in uniformly aerated bubble column reactors, *Collect, Czech. Chem. Commun.*, 47, 262-276.

Zehner, P., (1975), Stoffaustausfläche und Gasverteilung in einer neu entwickelten Ejektor Strahlduse, *Chem. Ing. Tech.*, 47, 209-214.

Zheng, Q., and Jasuja, A., (1994), Droplet size and velocity correlations for a coaxial airblast atomized jet, *In Proc. ICLASS*, 664–671.

Zheng, S., Yao, Y., Guo, F., Bi, R., and Li, J., (2010), Local bubble size distribution, gas-liquid interfacial areas and gas holdups in an up-flow ejector, *Chemical Engineering Science*, 65, 5264–5271.

Ziegler, H., Meister, D., Dunn, I. J., Blanch, H. W., and Russel, W. F., (1977) Schlaufen reaktoren, *Biotech. Bioeng.*, 19, 507-511.

Zlokarnik, M., (1980), Eigung und Leistungsfähigkeit von Belüftungs Vorrichtungen für die biologische Abwasserreinigung, *Chem. Ing. Tech.*, 52, 330-331.