



INDEX

Chapter 1	Introduction	1- 5
Chapter 2	Literature review	6 - 54
2.1	Introduction	6
2.1.1	Limitations of producing 3D shapes from 2D woven fabrics by making-up	6
2.1.2	Proposed solutions to over come drawbacks associated with conventional making-up	7
2.1.2.1	Thermal moulding	7
2.1.2.2	Automation of making up	7
2.1.2.3	3D Shape Weaving	8
2.2	Unfoldable type 3D shape weaving with progressive elimination of ends	10
2.3	Weaving machine for producing seamless 3D shapes	23
2.3.1	A rapier loom for producing directly 3D seamless woven shapes	27
2.3.1.1	Rapier weaving machine producing 3D shapes by changing spacing of warp and weft threads	27
2.3.1.1.1	Changing warp thread distances	30
2.3.1.1.1.1	Changing warp thread distances using reed with curved dents	30
2.3.1.1.1.2	Changing warp thread spacing by reed with displaceable dents	30
2.3.1.1.2	Changing spacing of picks with segmented take up	32
2.3.1.1.3	Warp brake (Tensioners) for individual warp threads	35
2.3.1.1.4	Arrangement for keeping warp threads in line with reed dents	35
2.3.1.2	Weaving 3D shapes using multi-part shapers	40
2.3.1.3	Role of weave in 3D shape weaving	44
2.3.2	Producing fabric with variable width	46
2.3.3	Weaving tubular garments directly on loom	47
Chapter 3	Experimental work	55 - 195
3.1	Aim of work	55
3.1.2	Progress of the work	57
3.2	Producing 3D woven shape manually	60
3.2.1	Outcome of weaving 3D shape manually	60
3.3	Producing 3D shape on handloom	60
3.3.1	Producing 3D shape using shaped rods	60
3.3.1.2	Outcome of weaving with shaped rods	63

3.3.2	Producing 3D shapes using shaped fins	63
3.3.2.1	Outcome of weaving with shaped slotted fins	66
3.3.3	Observations from weaving 3D shapes on handloom	66
3.3.4	Factors influencing space between successive ends and picks	68
3.3.4.1	Changing end spacing by reed	69
3.3.4.1.1	Reed with sliding dent wires	69
3.3.4.1.1.1	Outcome of effort of working on concept of developing reed with sliding dent wires	72
3.3.4.1.2	Reed with shaped dent wires	72
3.3.4.1.2.1	Determining dent shapes for reed to produce a pyramidal shape	75
3.3.4.1.2.1.1	Weaving pyramidal shape using reed with shaped dent wires	
3.3.4.1.2.2	Determining dent shapes of individual dent wires of reed to produce a hemispherical shape	82
3.3.5	Mathematical tool for determining curve shapes of individual reed dent wires for weaving pyramidal and hemispherical shapes	88
3.3.5.1	Generating curve shapes of individual reed dent wires mathematically for hemispherical shape	88
3.3.5.1.2	Fabrication of a reed for weaving a hemispherical shape	101
3.3.5.2	Generating curve shapes of individual reed wires mathematically for pyramidal shape	101
3.3.5.2.1	Application of geometric transform for Shape Weaving	109
3.3.5.3	Weaving pyramidal and hemispherical shapes on handloom using reeds with shaped dent wires	111
3.3.5.3.1	Weaving a pyramidal shape	111
3.3.5.3.2	Weaving a hemispherical shape	111
3.3.5.3.3	Outcome of weaving on hemispherical and pyramidal shapes on handloom using reed with shaped dent wires	118
3.4	Weaving any other shapes	120
3.5	Weaving 3D shapes on a power loom	120
3.5.1	Essential requirements on power loom for 3D shape weaving	122
3.5.1.1	Warp supply	122
3.5.1.2	Dent slope and reed displacement	122
3.5.1.3	Reed fabrication and significance of dent rigidity	124
3.5.1.4	Arrangement for reed displacement	125
3.5.1.5	Shuttle guidance through shed	125
3.5.1.6	Fabric control at fell of the cloth	126
3.5.1.7	Shedding mechanism requirement	126
3.5.1.8	Selection of comber board	126
3.5.2	Establishing set up for 3D shape weaving on a power loom	127
3.5.2.1	Procurement of suitable power loom	128
3.5.2.2	Design, development and fabrication of warp feeding creel	130
3.5.2.3	Modification in loom for guidance of shuttle through shed without support of reed	134
3.5.2.4	Design, development and fabrication of bracket for mounting and supporting reed	134
3.5.2.5	Fabrication of reed with shaped dent wires	137
3.5.2.6	Mechanism for displacing reed vertically	140
3.5.2.7	Design, development and fabrication of fell control	143

	mechanism	
3.5.3	Out come of weaving on power loom	146
3.5.3.1	Necessary requirements for further development	156
3.5.4	Weaving set up for 3D shape weaving with jacquard shedding and programmable stepper motor drive for reed position control and other improvements	156
3.5.4.1	Bracket for supporting reed	156
3.5.4.2	Programmable stepper motor drive	158
3.5.4.2.1	Stepper motor	158
3.5.4.2.2	PLC controller for stepper motor	158
3.5.4.3	Mechanisms to transmit drive from stepper motor to reed	161
3.5.4.3.1	Screw mechanism for reed displacement	161
3.5.4.3.1.1	Performance of screw mechanism	163
3.5.4.3.2	Pulley and cord mechanism for reed displacement	163
3.5.4.3.2.1	Performance of pulley and cord mechanism for reed displacement	165
3.5.4.4	PLC programming for weaving a 3D shape	165
3.5.4.4.1	Stepper motor programming through a computer	173
3.5.4.5	Setting up jacquard shedding	173
3.5.5	Weaving pyramidal shape on loom	179
3.5.5.1	Pyramid dimensions	179
3.5.5.2	Selection of warp yarn, weft yarn, weave and thread density	179
3.5.5.3	Design and fabrication of reed	180
3.5.5.4	Jacquard design development	182
3.5.5.5	Weaving pyramidal shape	182
3.5.5.5.1	Fell control using full width spiked rollers	183
3.5.5.5.2	Conical roller for control of shuttle flight	183
3.5.5.6	Weaving with fell control using spiked roller and conical roller for shuttle flight control	185
3.5.5.7	Differential take up	190
Chapter 4	Results and Discussions	196 - 236
4.1	Introduction	196
4.2	Producing 3D woven shape manually	196
4.3	Producing 3D shape on handloom	197
4.3.1	Producing hemispherical shape using shaped rods	197
4.3.1.1	Reason for why 3D shape could not be produced	197
4.3.1.2	Out come of attempt of producing hemispherical shape using shaped rods	197
4.3.2	Producing 3D shapes using shaped fins	198
4.3.2.1	Dimensions of shapes woven	198
4.3.2.2	Limitations of weaving 3D shape using shaped fins	198
4.3.2.3	Out come of weaving using shaped fins	200
4.3.3	Fundamental requirements for weaving 3D shapes	200
4.3.3.1	Producing 3D shape by shifting planes of cross over points	201
4.3.3.2	Producing 3D shape by changing spacing of ends and picks	201

4.3.3.2.1	Changing spacing of ends by reed	202
4.3.3.2.1.1	Reed with displaceable dent wires	202
4.3.3.2.1.2	Reed with shaped dent wires	203
4.4	Establishing set up for weaving 3D shape on power loom	221
4.4.1	Procurement of a power loom	221
4.4.2	Warp feeding creel	221
4.4.3	Shuttle guidance through the shed	222
4.4.4	Bracket for supporting reed	222
4.4.5	Fabrication of reed with shaped dent wires	222
4.4.6	Mechanisms for reed displacement vertically	223
4.4.6.1	Mechanical system for vertical reed position control	223
4.4.6.2	Programmable stepper motor drive	224
4.4.6.2.1	Screw mechanism	225
4.4.6.2.2	Pulley and cord mechanism	226
4.4.7	Shedding mechanism	227
4.4.7.1	Dobby shedding	227
4.4.7.2	Jacquard shedding	228
4.4.8	Mechanism to control fabric, under situation of changing width at cloth fell during weaving of shaped region	229
4.4.8.1	Fell control mechanism using combs	229
4.4.8.2	Fell control using series of spiked rollers across full width	229
4.4.9	Conical roller for control of shuttle flight	229
4.5	Results of weaving 3D shapes on power loom	230
 Chapter 5	 Conclusions	 237 - 241
 Chapter 6	 Scope for the further work	 242 - 243
	 Appendix	 244 - 256
	 Bibliography	 257 - 258