

LIST OF TABLES

Table No.	Title
1.1	Physical, chemical & mineralogical features of NaNO_3 & CaCO_3 .
1.2	Conversion tables for indices of planes and directions.
1.3	Standard forms/family of planes of Holosymmetric trigonal crystal (calcite) in Miller-Bravais and Miller notation.
1.4	Table of transformation of Miller indices (MI) to Miller-Bravais indices (MBI) of some prominent/major planes in rhombohedral crystals.
2.1	Table for magnifications of optical microscope.
2.2	Table for chemical assay and impurities of NaNO_3 .
3.1	Table for types of indenters.
4.1	Table of logarithms of longer diagonal length of Knoop indentation mark corresponding to logarithms of load at various orientations of the Knoop indenter and quenching temperature (A) for NaNO_3 , (B) CaCO_3 .
4.2	Table consisting load P, diagonal length d, log P, log d, d^2 , d^n , (P-W), log (P-W); for orientation 0° of Knoop indenter with direction [100]; (A) for NaNO_3 at 298°K , (B) for CaCO_3 at 303°K .
4.3(A)	Table consisting angle A, slopes n_{obs} , n_{mod} , W, b, a, of the plots log d Vs. log P for NaNO_3 at various quenching temperatures.
4.3(B)	Table consisting angle A, slopes $n_1 \text{ obs}$, $n_1 \text{ mod}$, W_1 , b_1 , a_1 , load at kink P_K , $n_2 \text{ obs}$, $n_2 \text{ mod}$, W_2 , b_2 , a_2 of the plots log d Vs. log P for CaCO_3 at various quenching temperatures for LLR & HLR.

Table No.	Title
5.1	Knoop hardness numbers corresponding to different loads for various orientations of Knoop indenter with the direction [100] at various quenching temperatures for NaNO_3 .
5.2	Knoop hardness number corresponding to different loads for various orientations of Knoop indenter with the direction [100] at various quenching temperatures for CaCO_3 .
5.3(a)	Mean hardness values \bar{H} from the plots of H Vs. P for NaNO_3 for different orientations of Knoop indenter and various quenching temperatures.
5.3(b)	Calculation of H by using relation $H = 14230.a^{2/n}.P^{(n-2)/n}$ for NaNO_3 for different orientations and quenching temperatures.
5.3(c)	Calculation of H by using relation $H = 14230.b$ for NaNO_3 for different orientations and quenching temperatures.
5.3(d)	Percentage deviation of calculated H with respect to mean H for NaNO_3 .
5.4(a)	Mean hardness values \bar{H} from the plots of H Vs. P for CaCO_3 for different orientations of Knoop indenter and various quenching temperatures.
5.4(b)	Calculation of H by using relation $H = 14230.a^{2/n_2}.P^{(n_2-2)/n_2}$ for CaCO_3 for different orientations and quenching temperatures.
5.4(c)	Calculation of H by using relation $H = 14230.b$ for CaCO_3 for different orientations and quenching temperatures.
5.4(d)	Percentage deviation of calculated H with respect to mean H for CaCO_3 .

Table No.	Title
5.5	Table consisting load P, diagonal length d, (P-W), hardness H, H by using relation $H = 14230.(P-W)/d^2$ for NaNO_3 at 0° orientation and 298°K .
5.6	Knoop & Vickers hardness values from the graph of H Vs. P, and calculated values of H by using formulae $H = C.a_2^{2/n_1} P^{(n_1-2)/n_1}$; $H = C.b_2$ for NaNO_3 at various quenching temperatures.
5.7	Table consisting $\log \bar{H}T_q$, $\log T_q$, slope m, c, K for NaNO_3 at various orientations and quenching temperatures.
5.8	Table consisting $\log \bar{H}T_q$, $\log T_q$, slope m C, K for CaCO_3 at various orientations and quenching temperatures.
5.9	Values of load P, slope m_{Ar} , $C_{Ar}/\sqrt{P_r}$ and % variation from the plot of $\log T_q d$ Vs. $\log T_q$ for NaNO_3 at 0° .
5.10	Values of load P, d, C_A , K_A for NaNO_3 at different A & T_q 's.
6.1	Values of $\sqrt{\bar{H}A}$ for different A's and T_q 's (A) for NaNO_3 , (B) for CaCO_3 .
6.2	Values of slope m (calculated by formula, statistical, observed), intercept C (calculated by formula, statistical, observed) of the plot $\sqrt{\bar{H}A}$ Vs. A (a) for NaNO_3 , (b) for CaCO_3 .
6.3	Tables consisting A, H, $\sqrt{\bar{H}A}$ for different crystals.
6.4	Values of $\log T_q \sqrt{\bar{H}A}$, $\log T_q$, slope m_1 , C_1 , P, K, C, $(C_1^2 - A)/C$, T_q^{p-k} (a) for NaNO_3 , (b) for CaCO_3 .
7.1	Values of A, ϕ , λ , ψ , for different slip systems.
7.2	Values of orientation A and ERSS (mean).

Table No.	Title
9.1	Etch-pit shape with different concentration at 50°C for L(+) tartaric acid on calcite with photomicrograph.
9.2	Table of length L, breadth B of etch-pit and weight loss per cm ² for different etching times at various etching temperatures for L(+) tartaric acid of concentration 0.075 M.
9.3(A)	Table of rate of tangential dissolution V_{tL} , V_{tB} and surface dissolution rate V_s along with ratios V_{tL}/V_s , V_{tB}/V_s at different etching temperatures for various etchant concentrations.
9.3(B)	Table consisting the ratio V_{tL}/V_{tB} for different etchant concentrations and etching temperatures.
9.3(C)	Table consisting $1/T$, $\log V_{tL}$, $\log V_{tB}$, $\log V_s$, $\log \sigma$.
9.3(D)	Table consisting $\log \mu$ for different concentrations and temperature.
9.4	Different activation energies E_{tL} , E_{tB} , E_s , E_σ , E_μ and ratios E_{tL}/E_s , E_{tB}/E_s , E_{tL}/E_{tB} for L(+) tartaric acid.
9.5	Values of electrical conductivity σ of aqueous solution of L(+) tartaric acid at different etching temperatures for different etchant concentrations.
9.6	Values of viscosity μ of L(+) tartaric acid solution of varying concentrations at different etching temperatures.