

LIST OF TABLES

Table No.	Table Title	Page No.
1.1	Production of Sugarcane (Country wise)	4
1.2	Average bagasse composition	5
1.3	Chemical constituents of bagasse	6
3.1	Coding of the untreated and treated Sugarcane bagasse fibres	48
3.2	Composition of perchloric acid and acetic anhydride	49
3.3	Recipe for Acetylation using perchloric acid as a catalyst	49
3.4	Recipe for Cyanoethylation treatment	50
3.5	Recipe for Enzymatic treatment	51
3.6	Specification of oil used for testing	58
3.7	Coding for oil tested in different viscosities	59
4.1	Effect of varying treatment conditions on physical and chemical properties of the extracted fibres	62
4.2	Variance analysis of Tenacity, Fibre quantity, Cellulose and Lignin versus different fibre treatment conditions	63
4.3	Results of the statistical analysis for optimisation of extraction parameters	64
4.4	Optimised condition for Sugarcane bagasse fibre extraction	68
4.5	Tensile strength of extracted fibre	72
4.6 (a)	Oil sorption capacity of fibres after treatment at 1% concentration	74
4.6 (b)	Oil sorption capacity of fibres after treatment at 3% concentration	74
4.6 (c)	Oil sorption capacity of fibres after treatment at 5% concentration	75
4.7 (a)	Recovery of sorbed oil after treatment at 1% concentration	77

4.7 (b)	Recovery of sorbed oil after treatment at 3% concentration	77
4.7 (c)	Recovery of sorbed oil after treatment at 5% concentration	78
4.8 (a)	Reusability of samples after treatment at 1% concentration	79
4.8 (b)	Reusability of fibres after treatment at 3% concentration	79
4.8 (c)	Reusability of fibres after treatment at 5% concentration	80
4.9	Variance analysis (ANOVA) of oil sorption capacity of Acetylated fibre at different treatment parameters	81
4.10	Variance analysis (ANOVA) of recovery of sorbed oil from Acetylated fibre at different treatment parameters	84
4.11	Variance analysis (ANOVA) of reusability of Acetylated fibre at different treatment parameters	87
4.12	Results of the statistical analysis for optimisation of Acetylation parameters	89
4.13	Optimised parameters for acetylation treatment	91
4.14 (a)	Oil sorption capacity of fibres after treatment at 1% concentration	91
4.14 (b)	Oil sorption capacity of fibres after treatment at 5% concentration	92
4.14 (c)	Oil sorption capacity of fibres after treatment at 9% concentration	93
4.15 (a)	Recovery of oil from fibres after treatment at 1% concentration	94
4.15 (b)	Recovery of oil from fibres after treatment at 5% concentration	95
4.15 (c)	Recovery of oil from fibres after treatment at 9% concentration	95
4.16 (a)	Reusability of fibres after treatment at 1% concentration	96
4.16 (b)	Reusability of fibres after treatment at 5% concentration	97
4.16 (c)	Reusability of fibres after treatment at 9% concentration	97
4.17	Variance analysis (ANOVA) of oil sorption capacity of Cyanoethylated fibre at different treatment parameters	98

4.18	Variance analysis (ANOVA) of recovery of sorbed oil from Cyanoethylated fibre at different treatment parameters	101
4.19	Variance analysis (ANOVA) of reusability of Cyanoethylated fibre at different treatment parameters	104
4.20	Results of the statistical analysis for optimisation of Cyanoethylation treatment parameters	106
4.21	Optimised parameters for Cyanoethylation treatment	108
4.22 (a)	Oil sorption capacity of fibres after treatment at 1% concentration	108
4.22 (b)	Oil sorption capacity of fibres after treatment at 5% concentration	109
4.22 (c)	Oil sorption capacity of fibres after treatment at 9% concentration	110
4.23 (a)	Recovery of sorbed oil from fibres after treatment at 1% concentration	112
4.23 (b)	Recovery of sorbed oil from fibres after treatment at 5% concentration	112
4.23 (c)	Recovery of sorbed oil from fibres after treatment at 9% concentration	113
4.24 (a)	Reusability of fibres after treatment at 1% concentration	114
4.24 (b)	Reusability of fibres after treatment at 5% concentration	114
4.24 (c)	Reusability of fibres after treatment at 9% concentration	115
4.25	Variance analysis (ANOVA) of oil sorption capacity of Enzymatic treated fibre at different treatment parameters	116
4.26	Variance analysis (ANOVA) of recovery of sorbed oil from Enzymatic treated fibre at different treatment parameters	119
4.27	Variance analysis (ANOVA) of reusability of Enzymatic treated fibre at different treatment parameters	122

4.28	Results of the statistical analysis for optimisation of enzyme treatment parameters	124
4.29	Optimised parameters for Enzymatic treatment	126