

List of Figures

1.1	(a) Schematic representation of the process of glass formation and (b) DSC thermograph of Polyvinyl acetate (PVAc) representing the onset, offset, and transition temperature.	5
2.1	Stress-strain response of (a) Polypropylene carbonate (PPC), (b) High-density polyethylene (HDPE) and (c) Linear-low density polyethylene (LLDPE) for different sets of polymer films	34
2.2	Elastic response of (a) PPC, (b) HDPE, and (c) LLDPE. the solid black line indicates the slope of the linear region representing Young's modulus of the polymer film and the black dashed line represents the tensile strength of the polymer film	35
2.3	Plastic deformation region (a) PPC, (b) HDPE, and (c) LLDPE. The black dashed line indicated the yield point of the polymer films. . .	35
2.4	Plastic deformation region of stress-strain curves of (a) PPC, (b) HDPE, and (c) LLDPE for two different samples. The red curve shows the power law: $\sigma = K.\gamma^n$, with $n = -0.14531 \pm 0.000009$ for PPC1 and $n = -0.1283 \pm 0.00004$ for PPC2; $n = -0.6838 \pm 0.0004$ for HDPE1 and $n = -1.54 \pm 0.00001$ for HDPE2; $n = 0.4649 \pm 0.0003$ for LLDPE1.	37
2.5	Mechanical properties (a) Young's modulus, (b) Tensile strength, (c) Yield point and (d) % Elongation at break of polymer films. The mechanical properties were calculated as a mean of the quantities obtained for all the samples and the errorbars represent the standard deviation.	38

2.6	Two-component principal component analysis for the tensile properties (Young's modulus, tensile strength, and % elongation at break) for non-biobased nonbiodegradable (NB-NB), non-biobased biodegradable (NB-BP), biobased nonbiodegradable (BB-NB) and biobased biodegradable (BB-BP) polymers. The experimental observation for polyethylene (PE) and polypropylene carbonate (PPC) and highlighted in green and purple respectively.	44
2.7	(a) Schematic of Raman spectrometer (b) Calibration curve using Naphthalene crystals.	44
2.8	The thermal quench applied to the polymer films. T_{Max} is the maximum temperature to which the films are heated, and T_{hold} is the temperature at which the films are maintained after quenching.	48
2.9	(a) Raman spectrum at room temperature (25 °C) of PPC film representing the vibrational modes presented as peaks in the Raman spectrum. The inset in (a) represents Raman bands which can be deconvoluted into various Raman peaks. (b) represents deconvolution of the band between 750 cm^{-1} to 1000 cm^{-1} into peak 1, 2, 3 and 4 (c) represents deconvolution of the band between 1000 cm^{-1} to 1200 cm^{-1} into Peak 5, 6 and 7 (d) represents two closely appearing peaks at 1350 cm^{-1} (peak 8) and at 1460 cm^{-1} (peak 9) (e) represents peak 10 at cm^{-1} and (f) represents deconvolution of Raman band between 2800 cm^{-1} to 3100 cm^{-1} into peak 11, 12, 13, 14 and 15. All the peaks are found to fit well with the Lorentzian function (Equation 2.7).	51
2.10	(a) The Raman band appearing between 750 cm^{-1} to 1000 cm^{-1} for PPC film is deconvoluted into four peaks, peaks 1, 2, 3, and 4 using the Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maximum (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for peak 4 corresponding to C-C stretching mode present in the main chain of the polymer.	53

- 2.11 (a) The Raman peak appearing at 1750 cm^{-1} for PPC film corresponding to C=O stretching mode present in the side branch of the polymer fitted with a Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maxima (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for the peak. 54
- 2.12 (a) The Raman band appearing between 2800 cm^{-1} to 3100 cm^{-1} for PPC film is deconvoluted into five peaks: peak 11, 12, 13, 14, and 15 using the Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maxima (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for peak 13 corresponding to C-H asymmetric stretching mode present in the main chain as well as a side branch of the polymer. 56
- 2.13 (a) Raman spectrum at room temperature for HDPE for a region varying from 850 cm^{-1} to 1900 cm^{-1} and (b) for a region of CH-Stretching mode between 2300 cm^{-1} to 3100 cm^{-1} . (a) and (b) spectrum collected for the same sample with different gratings of spectral resolution 0.925 cm^{-1} and 0.86 cm^{-1} respectively. (c) represents deconvolution of three closely appearing peaks between 1000 cm^{-1} to 1200 cm^{-1} into peaks 1, 2, and 3 (d) represents peak 4 at 1292 cm^{-1} (e) represents deconvoluted peaks 5, 6 and 7 between 1350 cm^{-1} to 1550 cm^{-1} and (f) represents deconvolution of Raman band between 2800 cm^{-1} to 3100 cm^{-1} into peaks 8, 9 and 10. All the peaks fitted well with the Lorentzian function. 59

- 2.14 (a) The Raman band appearing between 1000 cm^{-1} to 1200 cm^{-1} for HDPE film is deconvoluted into three peaks: peaks 1, 2, and 3 using the Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maxima (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for peak 3 corresponding to C-C stretching mode present in the main chain of the polymer. 60
- 2.15 (a) The Raman band appearing between 1350 cm^{-1} to 1550 cm^{-1} for HDPE film is deconvoluted into three peaks: peaks 5, 6 and 7 using Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maxima (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for peak 5 corresponding to CH_2 scissoring mode present in the side chain of the polymer. 61
- 2.16 (a) The Raman band appearing between 2800 cm^{-1} to 3100 cm^{-1} for HDPE film is deconvoluted into three peaks: peaks 8, 9 and 10 using Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maxima (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for peak 8 corresponding to C-H stretching mode present in the main chain as well as side chain of the polymer. 62

- 2.17 (a) Raman spectrum at room temperature for LLDPE for a region varying from 850 cm^{-1} to 1900 cm^{-1} and (b) for a region of CH-Stretching mode between 2300 cm^{-1} to 3100 cm^{-1} . (a) and (b) spectrum collected for the same sample with different gratings of spectral resolution 0.925 cm^{-1} and 0.86 cm^{-1} respectively. (c) represents deconvolution of three closely appearing peaks between 1000 cm^{-1} to 1200 cm^{-1} into peaks 1, 2, and 3 (d) represents peak 4 at 1292 cm^{-1} (e) represents deconvoluted peaks 5, 6 and 7 between 1350 cm^{-1} to 1550 cm^{-1} and (f) represents deconvolution of Raman band between 2800 cm^{-1} to 3100 cm^{-1} into peaks 8, 9 and 10. All the peaks fitted well with the Lorentzian function. 65
- 2.18 (a) The Raman band appearing between 1000 cm^{-1} to 1200 cm^{-1} for LLDPE film is deconvoluted into three peaks: peaks 1, 2, and 3 using the Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maxima (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for peak 3 corresponding to C-C stretching mode present in the main chain of the polymer. 66
- 2.19 (a) The Raman band appearing between 1350 cm^{-1} to 1550 cm^{-1} for LLDPE film is deconvoluted into three peaks: peaks 5, 6 and 7 using Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maxima (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for peak 5 corresponding to CH_2 scissoring mode present in the side chain of the polymer. 67

2.20	(a) The Raman band appearing between 2800 cm^{-1} to 3100 cm^{-1} for LLDPE film is deconvoluted into three peaks: peaks 8, 9 and 10 using Lorentzian function. (b), (c), (d), and (e) show respectively the time evolution of the peak center, the full width at half maxima (FWHM) of the peak, the integrated peak intensity or the area under the peak (I_{INT}) and the maximum peak intensity (I_{Max}) for peak 8 corresponding to C-H stretching mode present in the main chain as well as side chain of the polymer.	68
2.21	(a) Thermal quench applied to the polymer films, the temperature is increased from room temperature ($RT=22\text{ }^{\circ}\text{C}$) to $T_{Max} = 70\text{ }^{\circ}\text{C}$ for HDPE and LLDPE and $T_{Max} = 40\text{ }^{\circ}\text{C}$ for PPC with a rate of $20\text{ }^{\circ}\text{C}/\text{min}$, after 15 minutes the temperature is quenched and maintained at $T_{hold} = 10\text{ }^{\circ}\text{C}$ with a rate of $60\text{ }^{\circ}\text{C}/\text{min}$. (b) Maximum Raman intensity I_{Max} at RT , T_{Max} and T_{hold} for the prominent vibrational modes discussed in section 2.6 are shown in the form of a bar graph.	69
2.22	Variation in percentage crystallinity of HDPE (blue) and LLDPE (red) as a function of time due to the thermal cycle applied to the polymer films. The black schematic in layer 1 represents the thermal cycle applied to the polymer films and layer 2 shows the change in crystallinity as a function of temperature and time.	71
2.23	Correlation matrix of Pearson's correlation coefficients between Raman peak parameters and Young's modulus (YM), tensile strength (TS) and yield point (YP) of polymer films for (a) C-C stretching vibrational mode and (b) C-H stretching vibrational mode.	73
2.24	Relative differential change in I_{Max} and I_{INT} as ϕ_H and ϕ_A respectively for C-C stretching mode (a) and (b), CH_2 scissoring mode (c) and (d) and C-H stretching mode (e) and (f) for the processed and drop casted films of HDPE	74

3.1	(a) The thermal ramp applied to the polymer in both unprocessed and film state (b) The thermal quench applied to the polymer, T_{Max} is the maximum temperature to which the films were heated and T_{hold} is the temperature at which the films were maintained after quenching.	90
3.2	(a) Raman spectrum at room temperature (25 °C) of unprocessed PVAc representing the vibrational modes presented as peaks in the Raman spectrum. The inset in (a) represents closely appearing Raman bands which can be deconvoluted into various Raman peaks. (b) represents deconvolution of peaks 1 and 2 1023 cm^{-1} and 1126 cm^{-1} using Lorentzian function (Equation 3.2) (c) represents deconvolution of the band between 1150 cm^{-1} to 1600 cm^{-1} into peaks 3, 4, 5 and 6 using Voigt function (Equation 3.3) (d) represents peak 7 at 1735 cm^{-1} fitted using Equation 3.3 and (f) represents deconvolution of Raman band between 2800 cm^{-1} to 3100 cm^{-1} into peaks 8, 9, 10 and 11 using Lorentzian function (Equation 3.2). The peaks are assigned their respective vibrational modes in Table 3.1	94
3.3	(a) Raman spectrum of PVAc film at room temperature ($\approx 25\text{ °C}$). (b) broad band appearing in the Raman spectrum of PVAc film, deconvoluted into two peaks using Voigt function (Equation 3.3) and (c) Raman band representing C-H stretching vibrational modes in PVAc film fitted using Lorentzian function (Equation 3.2).	96
3.4	Effect of temperature ramp (a) ramp 1 and (b) ramp 2 on the Raman spectrum of unprocessed PVAc. A prominent change in the Raman peaks is observed as a function of temperature during the heating (red) and cooling (green) cycles.	97
3.5	(a) C-C stretching peak (peak 2) of unprocessed PVAc fitted with Lorentzian function (Equation 3.2) at $T = 313\text{ K}$ contributing to the main chain/ backbone of the polymer. Evolution of this peak as a function of temperature for heating (red) and cooling (blue) cycles of ramp 1 (R1, solid) and ramp 2 (R2, dashed) for the peak parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	98

3.6	(a) C=O stretching peak (peak 7) of unprocessed PVAc fitted with Lorentzian function (Equation 3.2) at $T = 313$ K which contributes to the side branch of the polymer. Influence of temperature ramp during heating (red) and cooling (blue) cycles of ramp 1 (R1, solid) and ramp 2 (R2, dashed) for the peak parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	99
3.7	(a) C-H stretching peak (peak 8) of unprocessed PVAc fitted with Lorentzian function (Equation 3.2) at $T = 313$ K which contributes to the side branch of the polymer. Influence of temperature ramp during heating (red) and cooling (blue) cycles of ramp 1 (R1, solid) and ramp 2 (R2, dashed) for the peak parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	101
3.8	Effect of temperature ramp (a) ramp 1 and (b) ramp 2 on the Raman spectrum of PVAc film. A prominent change in the Raman peaks is observed as a function of temperature during heating (red) and cooling (green) cycles with a remarkable variation in ramp 2.	102
3.9	(a) The broad bands (peaks 2 and 3) appearing in the Raman spectrum of PVAc film, deconvoluted using Voigt function (Equation 3.3) at $T = 313$ K. Evolution of these peaks as a function of temperature for heating (red) and cooling (blue) cycles of ramp 1 (R1) for the peak parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	104
3.10	(a) The broad bands (peaks 2 and 3) appearing in the Raman spectrum of PVAc film, deconvoluted using Voigt function (Equation 3.3) at $T = 313$ K. Evolution of these peaks as a function of temperature for heating (red) and cooling (blue) cycles of ramp 2 (R2) for the peak parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	105
3.11	(a) C-H stretching mode (peak 4) appearing in the Raman spectrum of PVAc film, fitted using Lorentzian function (Equation 3.2) at $T = 313$ K. Effect of first temperature ramp (ramp 1) for heating (red) and cooling (blue) cycles for the peak parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	106

- 3.12 (a) C-H stretching mode (peak 4) appearing in the Raman spectrum of PVAc film, fitted using Lorentzian function (Equation 3.2) at $T = 313$ K. Effect of second temperature ramp (ramp 2) for heating (red) and cooling (blue) cycles for the peak parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center. . 107
- 3.13 (a) The area covered by the hysteresis loop for unprocessed PVAc and PVAc film due to the thermal ramp cycle, R1 = ramp 1 and R2 = ramp 2. (b) The change in the area under the peak I_{INT} during the heating and cooling cycle represented as ΔI_{INT} vs T/T_g for peak 2 of PVAc film and peak 7 of unprocessed PVAc. (c) The change in the area under the peak I_{INT} during the heating and cooling cycle represented as ΔI_{INT} vs T/T_g for peak 4 of PVAc film and peak 8 of unprocessed PVAc. 110
- 3.14 Time evolution of the Raman spectrum of unprocessed PVAc as a function of waiting time after quench (t_w) for two quench rates 60 °C/min (blue) and 100 °C/min (orange). 112
- 3.15 (a) C-C stretching peak (peak 2) of unprocessed PVAc fitted with Lorentzian function (Equation 3.2) which contributes to the side branch of the polymer. Time evolution of the peak fit parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM, and (e) peak center as a function of waiting time after quench (t_w) for two quench rates 60 °C/min (blue) and 100 °C/min (orange) 113
- 3.16 (a) C=O stretching peak (peak 7) of unprocessed PVAc fitted with Lorentzian function (Equation 3.2) which contributes to the side branch of the polymer. Time evolution of the peak fit parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM, and (e) peak center as a function of waiting time after quench (t_w) for two quench rates 60 °C/min (blue) and 100 °C/min (orange). 114
- 3.17 (a) C-H stretching peak (peak 8) of unprocessed PVAc fitted with Lorentzian function (Equation 3.2) which contributes to the side branch of the polymer. Time evolution of the peak fit parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM, and (e) peak center as a function of waiting time after quench (t_w) for two quench rates 60 °C/min (blue) and 100 °C/min (orange) 115

3.18	Time evolution of the Raman spectrum of PVAc film as a function of waiting time after quench (t_w) for two quench rates - 60 °C/min (blue) and 100 °C/min (orange).	117
3.19	(a) Peak 2 of the Raman band appearing in the Raman spectrum of PVAc film, fitted using Voigt function (Equation 3.3). Time evolution after quench for two quench rates - 60 °C/min (blue) and 100 °C/min (orange) of the peak fit parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	118
3.20	(a) Peak 3 of the Raman band appearing in the Raman spectrum of PVAc film, fitted using Voigt function (Equation 3.3). Time evolution after quench for two quench rates - 60 °C/min (blue) and 100 °C/min (orange) of the peak fit parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	120
3.21	(a) C-H stretching mode (peak 4) appearing in the Raman spectrum of PVAc film, fitted using Lorentzian function (Equation 3.2). Time evolution after quench for two quench rates - 60 °C/min (blue) and 100 °C/min (orange) of the peak fit parameters (b) peak height (I_{Max}), (c) peak area (I_{INT}), (d) FWHM and (e) peak center.	121
3.22	(a) The temperature dependence of normalized I_{INT} for peak 4 of PVAc film follows a VFT relation after T_g (shown by red dashed line and an Arrhenius equation before T_g). (b) The temperature dependence of normalized I_{INT} for peak 2 and peak 8 of unprocessed PVAc fitted with VFT relation.	123
3.23	Schematic representation of the thermal relaxations observed in PVAc film during the thermal ramp passing through T_g . A clear transition from the cooperative segmental dynamics to confined caging dynamics is observed on going below T_g	127

4.1	(a) Raman spectrum of unprocessed PVAc and its representative vibrational modes numbered in red. The inset shows closely appearing modes in the Raman spectrum. (b) Variation in integrated intensity (I_{INT}) as a function of temperature during thermal ramp for heating and cooling cycles of peak 8 representing the C-H stretching vibrational modes. (c) Variation in integrated intensity (I_{INT}) as a function of waiting time after quench through the glass transition temperature (T_g) of peak 8 representing the C-H stretching vibrational modes.	138
4.2	(a) Raman spectrum of PVAc film and its representative vibrational modes numbered in red. (b) Variation in integrated intensity (I_{INT}) as a function of temperature during thermal ramp for heating and cooling cycles of peak 4 representing the C-H stretching vibrational modes. (c) Variation in integrated intensity (I_{INT}) as a function of waiting time after quench through the glass transition temperature (T_g) at two different rates (60 °C/min and 100 °C/min) of peak 4 representing the C-H stretching vibrational modes.	139
4.3	Correlation matrix of Pearson's correlation coefficients for all Raman modes present in the Raman spectrum of (a) unprocessed PVAc and (b) PVAc film during the heating and cooling cycles of the thermal ramp.	140
4.4	Correlation matrix of Pearson's correlation coefficients for all Raman modes present in the Raman spectrum of (a) unprocessed PVAc and (b) PVAc film for the time evolution of the Raman modes after quenching with a rate of 60 °C/min.	141
4.5	Spatial variation of peak intensities (I_{Max}) on a surface of 100 μm \times 100 μm area on PVAc film for peaks 2, 3 and 4 appearing in the Raman spectrum (as labeled in Figure 4.2) (a) at room temperature and (b) after quenching at the rate of 60 °C/min.	142
4.6	Domain size distribution of the heterogeneous domains in peak 4 representing C-H stretching mode of PVAc film across a region of 100x100 μm (a) before quench (at room temperature) and (b) after the quench ($t_w = 0$). The normalized distribution of area follows an exponential character which is represented by the exponential fit (red line).	143

4.7	Time resolved spatial variation of peak intensities (I_{Max}) on a surface of $340\ \mu\text{m} \times 340\ \mu\text{m}$ area on PVAc film for peaks 2, 3 and 4 appearing in the Raman spectrum (as labeled in Figure 4.2 (a) immediately after quenching ($t_w = 0$) at the rate of $60\ ^\circ\text{C}/\text{min}$ and (b) 95 minutes after quenching ($t_w = 95\ \text{min.}$)).	144
4.8	Binary plot of the heterogeneities in the two-dimensional contour plot of Raman intensity for P2 in PVAc film (a) at $t_w = 0$ and (b) at $t_w = 95\ \text{min.}$ The black borders were detected by the boxcount algorithm to calculate the fractal dimensions. (c) variation of local fractal dimension d_F as a function of box size (r) (d) the number of boxes ($n(r)$) versus r, box size and their power law fitting ($n(r) = r^{-d_F}$; dashed red line) which determines the fractal dimension of the polymer.	145
4.9	Binary plot of the heterogeneities in the two-dimensional contour plot of Raman Intensity for P3 in PVAc film (a) $t_w = 0$ and (b) at $t_w = 95\ \text{min.}$ The black borders were detected by the boxcount algorithm to calculate the fractal dimensions. (c) variation of local fractal dimension d_F as a function of box size (r) (d) the number of boxes ($n(r)$) versus r, box size and their power law fitting ($n(r) = r^{-d_F}$; dashed red line) which determines the fractal dimension of the polymer.	146
4.10	Binary plot of the heterogeneities in the two-dimensional contour plot of Raman Intensity for P4 representing C-H stretching vibration in PVAc film (a) $t_w = 0$ and (b) $t_w = 95\ \text{min.}$ The black borders were detected by the boxcount algorithm to calculate the fractal dimensions. (c) Variation of local fractal dimension d_F as a function of box size (r) (d) the number of boxes ($n(r)$) versus r, box size and their power law fitting ($n(r) = r^{-d_F}$; dashed red line) which determines the fractal dimension of the polymer.	147
4.11	Intensity correlations as a function of waiting time after a quench for t_w varying between 0 to 5696 secs. and 5700 to 11396 secs. Hence, two $C(t_w, t + t_w)$ curves were obtained for each peak.	150

4.12	2D spatial correlations of I_{Max} in peak 2,3 and 4 instantly after quench ($t_w = 0$) in (a), (b) and (c) respectively and 95 minutes (5700 secs.) after a quench ($t_w = 95$ min.) in (d), (e) and (f) respectively.	150
4.13	(a) Evolution of the imaginary part of the experimental dynamic susceptibility $\chi''(\nu, T)$ at different temperatures as a function of the Raman shift ν on subjecting the PVAc film to a slow temperature ramp of rate $10^\circ\text{C}/\text{min}$. (b) $\chi''(\nu, T)$ grows as a function of T on approaching the glass transition temperature from 333 K , with a maximum at around 308 K . (c) $\chi_4(\nu, T)$ (Equation 8) as a function of $1/\nu$ for different temperatures. (d) $\chi_4(\nu, T)$ shows a peak denoted by $\chi_4^*(T_g)$ around 308 K which is close to the glass transition temperature (T_g).	154
4.14	(a) Evolution of the imaginary part of the experimental dynamic susceptibility $\chi''(\nu, T)$ at the different waiting time (t_w) as a function of the Raman shift ν on subjecting the PVAc film to a temperature quench of rate $60^\circ\text{C}/\text{min}$. (b) $\chi_4(\nu, T)$ (Equation 8) as a function of $1/\nu$ for different t_w . (c) Evolution of $\chi''(\nu, T)$ for a quench rate $100^\circ\text{C}/\text{min}$ and (d) its $\chi_4(\nu, T)$ as a function of $1/\nu$. (e) and (f) $\chi_4(\nu, T)$ grows as a function of t_w after the quench with maximum denoted by $\tau(T)$	155
5.1	(a) 100×100 pixel area photobleached during FRAP experiments for PEG solution. (b) Normalized fluorescence intensity profile with a spotwidth fitted to Gaussian function (Equation 5.1). (c) Normalized mean intensity curve for $50\text{ wt.}\%$ PEG. (d) Normalized recovery curves for 5 individual photobleached regions and its mean recovery profile for $50\text{ wt.}\%$ PEG. (e) Normalized recovery curves of $50\text{ wt.}\%$ PEG for different sizes of photobleached region.	165
5.2	Normalized recovery profiles for (a) Control (only water), (b) 5P, (c) 10P, (d) 20P and (e) 50P for 5 different regions and their mean normalized intensity with a fitting to Equation 5.3. (f) Fits of average recovery curves to Equation 5.6, for solutions of different PEG concentrations as mentioned in the legend.	171

5.3	Normalized recovery profiles on adding CMC nanofibers to 20P for 0.01%C, 0.1%C and 1%C in 20P along with 20P and their respective fits to Equation 5.3 in (a) and Equation 5.6 in (b). The control experiments for 0.01%C, 0.1%C and 1%C in water and their respective fits to Equation 5.3 in (c) and Equation 5.6 in (d). . .	175
5.4	Normalized recovery profiles on adding bentonite to 20P for 0.01%B, 0.1%B and 1%B in 20P along with 20P and their respective fits to Equation 5.3 in (a) and Equation 5.6 in (b). The control experiments for 0.01%B, 0.1%B and 1%B in water and their respective fits to Equation 5.3 in (c) and Equation 5.6 in (d).	177
5.5	(a) Cluster graph of diffusion half time ($t_{1/2}$) for fluorescein in different solutions indicated with different colors. (b) Comparison of D values calculated from 3 different methods. (c) D values for different concentrations of PEG (pink) represented by a non-entangled Rouse scaling $D \sim c^{-0.54}$ (d) D values for CMC aqueous solutions with a scaling $D \sim c^0$, indicating D for CMC is independent of c.	179
5.6	2D spatial correlation function for (a) 20P; (b) 20P+0.1B (c) 20P+1B; (d) 20P+0.1C and (e) 20P+1C solutions. (f) Static structure factor $S(Q)$ as a function of wave vector Q	183
5.7	Phase contrast microscope images of bentonite structures with different concentrations of PEG (a) 2P; (b) 5P; (c) 10P and (d) 20P in the aqueous solution (scale bar = 10 μm) and the corresponding normalized histograms of the area of these structures.	184
5.8	SAXS intensity $I(q)$ as a function of the scattering wave vector q (a) for q varying between 0.1 nm^{-1} to 3 nm^{-1} and (b) for q varying between 0.01 to 1 nm^{-1} for PEG + bentonite solutions. (c) MSANS intensity $I(q)$ as a function of the scattering wave vector q for PEG + bentonite solutions. The line curves are fits to Equation 5.18. . . .	187

- 5.9 Schematic representation of PEG solution without nanoparticles on the left followed by incorporating bentonite nanoparticles in PEG solution (in the middle) and on adding CMC nanofibers in PEG (on extreme right). The bentonite nanoparticles are disc-like structures that aggregate due to depletion interactions. The R_g is the radius of gyration of PEG and R is the length scale of bentonite aggregates obtained from scattering experiments. 190